



Tech Info Library

Apple IIGS: How To Start Up from Floppy Disk Using Aristotle

Revised: 9/13/91
Security: Everyone

Apple IIGS: How To Start Up from Floppy Disk Using Aristotle

=====
Article Created: 14 June 1991
Article Last Reviewed:
Article Last Updated:

TOPIC -----

I'm using Apple IIGS computers with a menu management program and a Macintosh file server. The menu management program is set as the startup application. I'm not using a network startup or "boot disk" and I don't want to. Here's my setup:

Slot 1	AppleTalk
Slot 7	AppleTalk
Startup	AppleTalk

I don't want to reconfigure my Control Panel just to be able to start up from a floppy disk. But with my current settings, if I press Control-Open-Apple-Reset, the floppy drives don't do anything.

I need a way to start up from a floppy without changing any of my Control Panel settings. Can I create a program in BASIC and put it in my menu management program? Would this BASIC program, when selected, cause my Apple IIGS to start up from the floppy drive?

DISCUSSION -----

There are two ways to do what you want:

First Method

-
- 1) Interrupt the boot process by pressing Control-Reset while the system is booting. This will give you the "]" prompt.
 - 2) Type "PR#6" to tell the computer to start up from the controller card in slot 6. (If you're starting up from a 3.5-inch floppy disk, use

5 instead.)

Second Method

To do the same thing through Aristotle, simply create a BASIC program with the following line:

```
10 PR#6
```

Save this program and set it up as an Aristotle menu item. The problem here is that you must start up all the way into Aristotle before you'll get back to the ability to boot from a local drive. Control-Reset will give you the ability to boot from a local drive much sooner.

Copyright 1991 Apple Computer, Inc.

Tech Info Library Article Number:8416