






# Lisa® Workshop C System



PAGES: 199

**EX LIBRIS  
DAVID T CRAIG**

# Lisa Workshop C User's Guide



## Limited Warranty on Media and Manuals

**ALL IMPLIED WARRANTIES ON THE MEDIA AND MANUAL, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO NINETY (90) DAYS FROM THE DATE OF THE ORIGINAL RETAIL PURCHASE OF THIS PRODUCT.**

Even though Apple has tested the software and reviewed the documentation, **APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS SOFTWARE OR ITS DOCUMENTATION, ITS QUALITY, PERFORMANCE, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS SOFTWARE AND ITS DOCUMENTATION ARE SOLD "AS IS," AND YOU, THE PURCHASER, ARE ASSUMING THE ENTIRE RISK AS TO THEIR QUALITY AND PERFORMANCE.**

**IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT IN THE SOFTWARE OR ITS DOCUMENTATION,** even if advised of the possibility of such damages. In particular, Apple shall have no liability for any programs or data stored in or used with Apple products, including the costs of recovering such programs or data.

**THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED.** No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

## Acknowledgments

Apple, Lisa, and the Apple logo are registered trademarks of Apple Computer, Inc. Macintosh is a trademark of McIntosh Laboratory, Inc. and is being used with express permission of its owner.

UNIX is a trademark of AT&T.

VAX and PDP are trademarks of Digital Equipment Corporation.

## Copyright

© 1985 Apple Computer, Inc.

© 1985 AT&T

© 1985 Green Hills Software, Inc.

All rights reserved

---

The released version of Workshop C cannot generate Lisa code - it's a cross-compiler only. If you know of someone with a Beta version, then you can use it to generate Lisa code. The Lisa support was stripped out in the final version.

---

*Apple Macintosh  
Tech Support*

# Lisa Workshop C User's Guide

## Table of Contents

Preface .....	1
1. The Workshop C Language.....	3
1.1 Data Types.....	3
1.2 Type Void.....	4
1.3 Type Enum.....	4
1.4 Register Variables.....	5
1.5 Structures.....	5
1.6 Return, Newline, and Vertical Tab.....	5
1.7 <code>_LINE_</code> and <code>_FILE_</code> .....	5
1.8 Predefined Symbols.....	5
1.9 Standard Apple Numeric Environment Extensions.....	5
1.9.1 Constants.....	6
1.9.2 Expressions.....	6
1.9.3 Comparisons.....	6
1.9.4 Functions.....	6
1.9.5 Input/Output.....	7
1.9.6 Numeric Environment.....	7
1.9.7 SANE Library.....	7
1.9.8 SANE Programming.....	7
1.10 Pascal-Compatible Functions.....	8
1.10.1 Pascal-Compatible Function Declarations.....	8
1.10.2 Pascal-Compatible Function Definitions.....	8
1.10.3 Parameter and Result Types.....	9
2. Implementation-Specific Language Details.....	10
2.1 Byte Ordering.....	10
2.2 Memory-Allocation Characteristics.....	10
2.3 Unsigned Char and Unsigned Short.....	11
2.4 Bit Fields.....	11
2.5 Evaluation Order.....	11
2.6 Case Statements.....	11
3. Implementation Notes.....	12
3.1 C Calling Conventions.....	12
3.1.1 Parameters.....	12
3.1.2 Function Results.....	12
3.1.3 Register Conventions.....	12
3.2 Pascal-Compatible Calling Conventions.....	12
3.2.1 Parameters.....	12
3.2.2 Results.....	13
3.2.3 Register Conventions.....	13
3.3 Compiler Limitations .....	13
4. Running the Compiler.....	14
4.1 Compiler Options .....	14
4.2 Include-File Search Rules .....	15
5. Files to Link With .....	16
6. Standard C Library .....	17
Error Numbers.....	18
ABS.....	20
ATOF.....	21
ATOL.....	22
CLOSE.....	23
CONV.....	24

CREAT.....	25
CTYPE.....	26
ECVT.....	27
EXIT.....	28
EXP.....	29
FCLOSE.....	30
FERROR.....	31
FLOOR.....	32
FOPEN.....	33
FREAD.....	35
FREXP.....	36
FSEEK.....	37
GETC.....	38
GETS.....	39
HYPOT.....	40
LSEEK.....	41
MALLOC.....	42
MEMORY.....	43
OPEN.....	44
PRINTF.....	45
PUTC.....	48
PUTS.....	50
RAND.....	51
READ.....	52
SCANF.....	53
SETBUF.....	57
SINH.....	58
STDIO.....	59
STRING.....	61
TRIG.....	63
UNGETC.....	65
UNLINK.....	66
WRITE.....	67
7. Macintosh Interface Libraries .....	68
Interface.....	69
CONTROLS.....	71
DESK.....	75
DEVICES.....	76
DIALOGS.....	78
DISKS.....	82
ERROR.....	84
EVENTS.....	85
FILES.....	88
FONTS.....	96
MEMORY.....	98
MENUS.....	101
OSEVENTS.....	104
OSUTILS.....	105
PACKAGES.....	109
PRINTING.....	114
QUICKDRAW.....	118
RESOURCES.....	130
RETRACE.....	133
SANE.....	134
SCRAP.....	138
SEGLOAD.....	139
SERIAL.....	140
SOUND.....	143

STRINGS.....	145
TEXTEDIT.....	146
TOOLUTILS.....	149
TYPES.....	152
WINDOWS.....	153
8. Library Index .....	158

## EXTRAS:

- A DISK COVERS
- B DISK CATALOGS
- C C-SPECIFIC HEADERS
- D C MAKE FILE
- E QDSAMPLE PROGRAM LISTING
- F LISA C PACKING SLIP





## Preface

This manual contains information you need to write C programs for the Macintosh™ by developing, compiling, and linking your programs under the Lisa® Workshop. Workshop C consists of a C compiler developed by Green Hills Software, the Standard C Library, and the Macintosh Interface Libraries.

### Contents of this Manual

This manual contains the following sections:

- Section 1...a definition of the Workshop C Language.
- Section 2...a clarification of implementation-specific details of the language definition.
- Section 3...notes describing calling conventions and other implementation issues.
- Section 4...details on how to run the compiler, including a list of compiler options.
- Section 5...a list of library files and notes on when to link with each file.
- Section 6...a complete definition of the Standard C Library provided with Workshop C.
- Section 7...the C definition of the Macintosh Interface Libraries.
- Section 8...a combined index to the Standard C Library and the Macintosh Interface Libraries.

### Reference Materials

You'll need to be familiar with these additional reference materials:

- *Lisa Workshop User's Guide*, Pascal Workshop 3.0, Apple Computer Inc.
- *The C Programming Language*, Kernighan and Ritchie (Prentice-Hall, 1978).
- *Inside Macintosh*.
- *Apple Numerics Manual*.
- "Putting Together A Macintosh Application," Macintosh Software Supplement, Apple Computer Inc.

*Inside Macintosh* and the *Apple Numerics Manual* will be published by Addison-Wesley in late 1985. A preliminary, promotional edition of *Inside Macintosh* is currently available from Apple Computer. The contents of the *Apple Numerics Manual* are available in the "Standard Apple Numeric Environment" manual in the Lisa Systems Software binder of the Pascal Workshop 3.0 documentation.

## Installation Notes

Lisa Workshop C is intended for use with the May 1985 Macintosh Software Supplement, which includes the Lisa Workshop 3.9. The files listed below are on the Workshop C release disks. They may be used directly or copied to a hard disk.

### Compiler

compiler	c.obj	Version 1.8.3
----------	-------	---------------

### Macintosh Sample Program

make file	mac/c/make.text
source	mac/c/sample/qdsample.c.text
resource file	mac/c/sample/qdsample.r.text

### Macintosh Libraries

headers	mac/c/include/... .h.text
objects	mac/c/lib/... .obj

## Lisa Workshop C User's Guide

### 1. The Workshop C Language

Workshop C is a complete implementation of the C programming language. *The C Programming Language* by Kernighan and Ritchie (Prentice-Hall, 1978) is currently the most authoritative written definition of C. However, the language has changed in several ways since the book was written. In addition, numerous details of the language definition are open to interpretation. Therefore, the de facto standard definition of C differs in several ways from the language originally defined by Kernighan and Ritchie. This de facto standard is loosely defined by the Portable C Compiler (PCC), the most widely used implementation of C.

*Standard C* is our name for the de facto standard definition of C as defined and implemented by the Berkeley 4.2 BSD VAX implementation of PCC, including the documented Western Electric extensions. Workshop C is based on this de facto standard (not on the proposed ANSI standard currently under development).

In addition, Apple has extended the standard language definition in several ways to facilitate writing programs for the Macintosh. Workshop C includes type void, enumeration data types, structure function parameters and results, enumeration data types, and a function modifier that allows calls to and from Pascal programs and the Macintosh Interface Libraries. The language has built-in support for the Standard Apple Numeric Environment (SANE). It recognizes the SANE data types, uses SANE for all C floating-point operations and conversions, and correctly handles NaNs (Not-a-Number) and infinities in comparisons and in ASCII-binary conversions. The language together with the SANE library support comprise a scrupulously conforming implementation of extended-precision IEEE Standard 754 floating-point arithmetic. Furthermore, source programs written using only float and double types and standard C operations compile and run without modification. These and other extensions are discussed in detail below.

#### 1.1 Data Types

The table below lists the arithmetic and pointer types available in Workshop C, and the number of bits allocated for variables of these types. Types int and longint, which are identical in this implementation, represent 32-bit integers. Pointers also require 32 bits. Enumeration types are allocated either 8, 16, or 32 bits, depending on the range of the enumeration literal values.

<u>Data Type</u>	<u>Bits</u>	<u>Description</u>
char	8	range -128 to 127
unsigned char	8	range 0 to 255
short	16	range -32,768 to 32,767
unsigned short	16	range 0 to 65,535
int	32	range -2,147,483,648 to 2,147,483,647

## Lisa Workshop C User's Guide

unsigned int	32	range 0 to 4,294,967,295
long	32	range -2,147,483,648 to 2,147,483,647
unsigned long	32	range 0 to 4,294,967,295
enum	8, 16 or 32	depends on the range of the enumeration literals
*	32	pointer types
float	32	IEEE single-precision floating point
double	64	IEEE double-precision floating point
comp	64	SANE signed integral values
extended	80	IEEE extended-precision floating point

## 1.2 Type Void

Type void has no values and no operators. Type void may be used as a type specifier in function declarations to indicate that the function has no meaningful return value. Specifying type void in Pascal-compatible function declarations reduces the number of instructions generated in calling the function. (See Section 1.10, Pascal-Compatible Functions.)

## 1.3 Type Enum

Type enum is a type analogous to the enumeration types of Pascal. Its syntax is similar to that of the struct and union declarations:

```
enum-specifier:
enum { enum-list }
enum identifier { enum-list }
enum identifier

enum-list:
enumeration-declaration
enumeration-declaration enum-list

enumeration-declaration:
identifier
identifier = constant-expression
```

The first identifier in *enum-specifier*, like the structure tag in a struct-specifier, names a particular enumeration. For example,

```
enum color {chartreuse, burgundy, claret, winedark};
enum color *cp, col;
```

This enumeration makes *color* the enumeration tag of a type describing various colors and then declares *cp* as a pointer to an object of that type and *col* as an object of that type.

The identifiers in *enum-list* are declared as constants and may appear wherever constants are required. If no enumerators with a *constant-expression* appear, the values of the constants begin at 0 and increase by 1 as the declaration is read from left to right. An enumerator with a *constant-expression* gives the associated identifier the value indicated; subsequent identifiers continue the progression by 1 from the assigned value.

Enumeration tags and constants must be unique. They are drawn from the set of ordinary identifiers, unlike structure tags and members. Objects of a given enumeration type have a type distinct from objects of all other types.

#### 1.4 Register Variables

The compiler allocates automatic variables in registers whenever possible. Register variables will be assigned to registers before other automatic variables. Enumeration, character, integer, and pointer variables qualify for register allocation unless their address is taken with the & operator. Floating-point variables are not allocated to registers.

Several data and address registers are available for use as automatic variables. The exact number depends on the calling conventions being used. The number of variables allocated to registers may exceed the total number of registers. Several variables whose useful lifetimes do not overlap may be assigned to the same register. Often all of the eligible variables within a function will reside in registers, rather than on the stack.

#### 1.5 Structures

Structures may be assigned, passed as parameters, and returned as function results. The left and right sides of a structure assignment must have the same type. Similarly, actual and formal parameters must have identical types. Other plausible operators, such as equality comparison, have not been implemented.

**Warning:** In functions that return structures, if an interrupt occurs during the return sequence and the same function is called reentrantly during the interrupt, the value returned from the first call may be corrupted. The problem can occur only in the presence of interrupts. Recursive calls are quite safe.

#### 1.6 Return, Newline, and Vertical Tab

The Return character, rather than newline, is represented by `\n` (a backslash character followed by a lowercase n). Return is the usual line termination character on the Macintosh. Return can also be represented by `\r`. Vertical tab is represented by `\v`.

#### 1.7 `__LINE__` and `__FILE__`

`__LINE__` is a predefined preprocessor symbol whose value is the current line number within the current source file. `__FILE__` is a similar symbol whose value is a character string consisting of the current file name. Both symbols begin and end with two underscore characters.

#### 1.8 Predefined Symbols

The symbols `MC68000`, `mc68000`, `m68k`, `ghs`, and `macintosh` are predefined. Each of the symbols has the value 1, as if a statement of this form had appeared at the beginning of the source code:

```
#define MC68000 1
```

#### 1.9 Standard Apple Numeric Environment Extensions

The Standard Apple Numeric Environment (SANE) is an extended-precision version of the IEEE Standard for Binary Floating-Point Arithmetic (754), together with an extra data type and basic functions for application development. Workshop C supports this environment. Much of SANE is provided through the run-time library `sanelib` and its include file `sane.h`. However, to use extended-precision arithmetic efficiently and effectively, and to handle IEEE NaNs (Not-a-Number) and infinities, some extensions to standard C are required.

## Lisa Workshop C User's Guide

A change from double to extended as the basic floating-point type is the most salient change to standard C. Since C was originally developed on the DEC PDP-11, the PDP-11 architecture is reflected in standard C in the use of float and double as floating-point types, with double as the basic type: floating-point expressions are evaluated to double, anonymous variables are double, and floating-point parameters and function results are passed as doubles. However, the low-level SANE arithmetic (as well as the floating-point chips Intel 8087, Motorola 68881, and Zilog Z8070) evaluates arithmetic operations to the range and precision of an 80-bit extended type. Thus, extended naturally replaces PDP-11 double as the basic arithmetic type for computing purposes. The types float (IEEE single), double, and comp serve as space-saving storage types, just as float does in conventional C.

The IEEE Standard specifies two special representations for its floating-point formats: NaNs (Not-a-Number) and infinities. Workshop C expands the syntax for I/O to accommodate NaNs and infinities, and includes the treatment of NaNs in relationals as required by the IEEE Standard.

The SANE extensions to standard C are backward compatible: programs written using only float and double floating-point types and standard C operations compile and run without modification. SANE does not affect integer arithmetic.

The *Apple Numerics Manual* contains detailed documentation of the Standard Apple Numeric Environment.

### 1.9.1 Constants

Numeric constants that include floating-point syntax—a point (.) or an exponent field—or that lie outside the range of longint are of type extended. Decimal-to-binary conversion for numeric constants is done at compile time (and hence is governed by the default numeric environment; compare Section 1.9.6).

### 1.9.2 Expressions

The SANE types—float, double, comp, and extended—can be mixed in expressions with each other and with integer types in the same manner that float and double can in standard C. An expression consisting solely of a SANE-type variable, constant, or function is of type extended. An expression formed by subexpressions and an arithmetic operation is of type extended if either of its subexpressions is. Extended-type expressions are evaluated using extended-precision SANE arithmetic, with conversions to type extended generated automatically as needed. Parentheses in extended-type expressions are honored. Initialization of external and static variables, which may include expression evaluation, is done at compile time; all other evaluation of extended-type expressions is done at run time.

### 1.9.3 Comparisons

The result of a comparison involving a NaN operand is unordered. The usual trichotomy of numbers is expanded to less (<), greater (>), equal (==), and unordered. For example, the negation of "a less than b" is not "a greater than or equal to b" but "(a greater than or equal to b) OR (a and b unordered)".

### 1.9.4 Functions

A numeric actual parameter passed by value is an expression and hence is of extended or integer type. All extended-type arguments are passed as extendeds. Similarly, all results of functions declared float, double, comp, or extended are returned as extendeds.

### 1.9.5 Input/Output

In addition to the usual syntax accepted for numeric input, the Standard C Library function *scanf* recognizes "INF" as infinity and "NaN" as a NaN. NaN may be followed by parentheses, which may contain an integer (a code indicating the NaN's origin). INF and NaN are optionally preceded by a sign and are case insensitive. *scanf* specifiers for SANE types extend standard C as follows: conversion characters *f*, *e*, and *g* indicate type float; *lf*, *le*, and *lg* indicate type double; *mf*, *me*, and *mg* indicate type comp; and *ne*, *nf*, and *ng* indicate type extended.

The Standard C Library function *printf* writes infinities as [-]INF and NaNs as [-]NAN(ddd), where ddd is the NaN code.

### 1.9.6 Numeric Environment

The numeric environment refers to rounding direction, rounding precision, halt enables, and exception flags. IEEE Standard defaults—rounding to nearest, rounding to extended precision, and all halts disabled—are in effect for compile-time arithmetic (including decimal-to-binary conversion). Each program begins with these defaults and with all exception flags clear. Functions for managing the environment are included in the library *sanelib*. The compiler, in optimizing, will not change any part of the numeric environment, including the exception-flag setting which is a side effect of arithmetic operations.

### 1.9.7 SANE Library

The SANE library rounds out the IEEE Standard implementation and provides the basic tools for developing a wide range of applications. The SANE library includes the following:

- logarithmic, exponential, and trigonometric functions
- financial functions
- random number generation
- binary-decimal conversion
- numeric scanning and formatting
- environment control
- other functions required or recommended by the IEEE Standard

Additional information can be found under the SANE entry in the Macintosh Interface Libraries section.

### 1.9.8 SANE Programming

Workshop C's automatic use of the extended type produces results that are generally better than those of other C systems. Extended precision yields more accuracy and extended range avoids unnecessary underflow and overflow of intermediate results. The programmer can further exploit the extended type by declaring all floating-point temporary variables to be type extended. This is both time- and space-efficient, since it reduces the number of automatic conversions among types. External data should be stored in one of the three smaller SANE types (float, double, or comp), not only for economy but also because the extended format may vary among SANE implementations. As a general rule, use float, double, or comp data as program input; extended arithmetic for computations; and float, double, or comp data as program output.

In many instances, IEEE arithmetic allows simpler algorithms than were possible without IEEE arithmetic. The handling of infinities enlarges the domain of some formulas. For example,  $1+1/x^2$  computes correctly even if  $x^2$  overflows. Running with halts disabled (the default), a program will never crash due to a floating-point exception. Hence by monitoring exception flags a program can test for exceptional cases after the fact. The alternative of screening out bad input is often infeasible, sometimes impossible.

**Lisa Workshop C User's Guide****1.10 Pascal-Compatible Functions**

The function-calling conventions used by Workshop C and Pascal differ radically in the order of parameters on the stack, the type coercions applied to parameters, the location of the return result, and the number of scratch registers. C has been extended to allow function calls between these languages. The specifier `pascal` in a function declaration or definition indicates a Pascal-compatible function.

**1.10.1 Pascal-Compatible Function Declarations**

A function or procedure written in Pascal (or written in assembly language following Pascal calling conventions) can be called from C. A Pascal-compatible external function declaration begins with the `pascal` specifier, contains the usual type specifiers, function name, and parameter list, and must also contain declarations for the parameters, followed by the word `extern`. Parameters whose declarations are omitted are assumed to be type `int`. For example, the C function declaration

```
pascal void DrawText (textBuf, firstByte, byteCount)
    Ptr textBuf;
    short firstByte, byteCount;
    extern;
```

would allow a C program to call the procedure `DrawText` defined in Pascal as follows:

```
PROCEDURE DrawText (textBuf: Ptr; firstByte, byteCount: INTEGER);
```

Pascal-compatible function declarations are used in the Macintosh Interface Libraries to allow C programs to directly call Macintosh library routines that use Pascal calling conventions. The word `extern` may be followed by a constant, which is interpreted as a 16-bit 68000 instruction that replaces the usual subroutine call (JRS) instruction in the calling sequence. This allows direct traps to the Macintosh ROM. For example:

```
pascal void OpenPort (port)
    GrafPtr port;
    extern 0xA86F;
```

**1.10.2 Pascal-Compatible Function Definitions**

A function definition (the actual function), like a function declaration, can also be preceded by the `pascal` specifier. The function then adheres to Pascal-compatible calling conventions and can be called from Pascal. For example, the following C function can be called from Pascal:

```
pascal void MyText (byteCount, textAddr, numer, denom)
    short byteCount;
    Ptr textAddr;
    Point numer, demon;
{
    ...
}
```

The corresponding Pascal function declaration would be

```
PROCEDURE MyText (bytecount: INTEGER; textAddr: Ptr; numer, denom: Point);
```

For compatibility with Pascal and assembly language, the compiler converts the names of Pascal-compatible functions to uppercase before writing them to the object file. When they are called in C



Lisa Workshop C User's Guide

programs, these routines should be capitalized exactly as they were declared in C. Pascal-compatible functions whose names differ only in their capitalization will become duplicate declarations when their names are converted to uppercase by the compiler; therefore such names should be avoided.

1.10.3 Parameter and Result Types

C and Pascal support different data types. Therefore when writing a Pascal-compatible function declaration in C, a translation of the parameter types and function-result type (from Pascal to C) is required. Often this translation is trivial, but other cases are surprising.

The table below summarizes this translation. Find the Pascal parameter or result type in the first column. Use the equivalent C type found in the second column when declaring the function in C. Comments in the table point out unusual cases which may require special attention.

<u>Pascal Parameter or Result Type</u>	<u>C Equivalent</u>	<u>Comments</u>
boolean var boolean boolean result	Boolean Boolean * Boolean	Boolean is defined in file types.h as enum {false,true}. In C, false is zero and true is often considered nonzero. In Pascal, false is zero and true is one.
enumeration ( <128 or >255 literals)	enum	Use identical ordering of the enumeration literals.
enumeration ( 128 to 255 literals)	short	Pascal passes enumerations with 128 or more literals as words.
var enumeration ( <128 or >255 literals)	enum *	
var enumeration ( 128 to 255 literals)	short *	
enumeration result ( <128 or >255 literals)	enum	
enumeration result ( 128 to 255 literals)	short	
char var char char result	short char * short	Surprise! Pascal passes chars as 16-bit values.
integer var integer short result	short short * short	16-bit signed values.
longint var longint longint result	int or long int * or long * int or long	32-bit signed values.
real var real real result	extended * float * float	Pascal passes real parameters as extended by address. Pascal returns real results by value.
double var double double result	extended * double * double	Pascal passes double parameters as extended by address. The caller supplies the address of the double result.
comp	extended *	Pascal passes comp parameters as extended by address.

**Lisa Workshop C User's Guide**

var comp	comp *	
comp result	comp	The caller supplies the address of the comp result.
extended	extended *	Pascal passes extended parameters by address.
var extended	extended *	
extended result	extended	The caller supplies the address of the extended result.
pointer	pointer	
var pointer	pointer *	32-bit addresses.
pointer result	pointer	
array (1 or 2 bytes)	short	Pascal passes small arrays by value.
array (3 or 4 bytes)	int or long	
array (5 or more bytes)	array	Pascal passes larger arrays by address.
var array	array	
array result	--	C does not allow array results.
record (1 to 4 bytes)	struct	Pascal passes small records by value.
record (5 or more bytes)	struct *	Pascal passes larger records by address.
var record (any size)	struct *	
record result (1 or 2 bytes)	short	Pascal returns small records by value.
record result (3 or 4 bytes)	int or long	
record result (1 or 2 bytes)	struct	The caller supplies the address of the record result.
set (1 to 7 elements)	char	Pascal passes sets with 1 to 7 elements as bytes.
set (8 to 16 elements)	short	Pascal passes sets with 8 to 16 elements as words.
set (≥17 elements)	struct	Pascal also passes larger sets by value.
var set (1 to 7 elements)	char *	
var set (8 to 16 elements)	short *	
var set (≥17 elements)	struct *	
set result (1 to 7 elements)	char	Pascal returns small sets by value.
set result (8 to 16 elements)	short	
set result (≥17 elements)	struct	The caller supplies the address of the set result.

**2. Implementation-Specific Language Details**

A number of details in any language definition are left to the discretion of its individual implementations. Most programs do not rely on these details and therefore yield the same results on the various implementations. However, knowledge of the major differences between implementations can help avoid reliance on language semantics that vary from implementation to implementation. This section explains several areas of the language definition that are specific to Workshop C.

**2.1 Byte Ordering**

On the MC68000, the microprocessor used in the Macintosh, the least significant byte of a short or long integer has the highest memory address. This byte ordering is also used on IBM/370 and Z8000 processors. The PDP-11 family, VAX, 8086, and NS16000 use a different ordering. Programs that rely on the order of the bytes within words and longs will not work correctly on both classes of machines.

**2.2 Memory-Allocation Characteristics**

The Workshop C compiler optimizes memory allocation in various ways. Automatic variables (locals) are allocated in registers whenever possible. Static and global variables are not necessarily allocated in the order in which they are specified. (However, the order of fields within records is preserved.) Static variables may

## Lisa Workshop C User's Guide

be allocated as if they were automatic if their values are always set before being referenced. Automatic and static variables that are never used may not be allocated at all. Programs should not rely on the compiler's allocation algorithms.

### 2.3 Unsigned Char and Unsigned Short

Types unsigned char and unsigned short are supported by the Workshop C compiler and by many implementations of PCC, although they are not required by the basic C language definition. The VAX implementation of PCC and the Workshop C compiler differ in the way they evaluate expressions involving these types. For example, the negation operator subtracts an unsigned short from  $2^{16}$  under PCC (this seems like a bug), and from  $2^{32}$  under Workshop C.

### 2.4 Bit Fields

Workshop C provides bit fields that are unsigned, as do all MC68000 versions of PCC of which we are aware. However, VAX implementations of C may support signed bit fields. In the following example, implementations using unsigned bit fields will set `i` to 3; implementations using signed bit fields will set `i` to -1.

```
struct {int field:2;} x;
x.field = 3;
i = x.field;
```

### 2.5 Evaluation Order

Workshop C does not define the evaluation order of certain expressions. Expressions with side effects, such as function calls and the "++" and "--" operators, may yield different results on different machines or with different compilers. Specifically, when a variable is modified as a side effect of an expression's evaluation and the variable is also used at another point in the same expression, the value used may be either the value before modification or the value after modification.

Programs that rely on the order of evaluation in these situations are in error. The function call `f(i,i++)` is an example of an expression whose value is undefined.

### 2.6 Case Statements

Some implementations of C, including PCC, allow cases of a switch statement to be nested within compound statements. Workshop C considers this an error. The following switch statement compiles using PCC but generates an error message using the Workshop C compiler. The error is that case 2: is within the if statement.

```
switch (i) {
case 1:
    if (j) {
        case 2:
            i = 3;
    }
}
```

## Lisa Workshop C User's Guide

### 3. Implementation Notes

The definition of C specifies the meaning of C programs. Implementations vary considerably in how they choose to implement this definition. Certain implementation details are of interest to assembly language programmers who want to write functions that either call or are called from C. This section provides those details.

#### 3.1 C Calling Conventions

Workshop C uses two different function-calling conventions. This section describes the usual C calling conventions. The Pascal-compatible calling conventions are described in section 3.2.

##### 3.1.1 Parameters

Parameters to C functions are evaluated from right to left and are pushed onto the stack in the order they are evaluated. Characters, integers, and enumeration types are passed as sign-extended 32-bit values. Pointers and arrays are passed as 32-bit addresses. Types float, double, comp, and extended are passed as extended 80-bit values. Structures are also passed on the stack. Their size is rounded up to a multiple of 16 bits (2 bytes). If rounding occurs, the unused storage has the highest memory address. The caller removes the parameters from the stack.

##### 3.1.2 Function Results

Characters, integers, enumeration types, and pointers are returned as sign-extended 32-bit values in register D0. Types float, double, comp, and extended are returned as extended values in registers D0, D1, and A0. The low-order 16 bits of D0 contain the sign and exponent bits; register D1 contains the high-order 32 bits of the significand; register A0 contains the low-order 32 bits of the significand. Structure values are returned as a 32-bit pointer in register D0. The pointer contains the address of a static variable into which the result is copied before returning. This implementation of structure function results is not reentrant.

##### 3.1.3 Register Conventions

Registers D0, D1, A0, and A1 are scratch registers and are not preserved by C functions. All other registers are preserved. Register A5 is the global frame pointer, register A6 is the local frame pointer, and register A7 is the stack pointer. Local stack frames are not necessarily created for simple functions.

#### 3.2 Pascal-Compatible Calling Conventions

This section describes the conventions used for calling Pascal functions from C and for functions written in C that use Pascal-compatible calling conventions. These conventions differ from the usual C calling conventions defined in section 3.1; they also differ from the calling conventions used by the Pascal compiler.

##### 3.2.1 Parameters

Parameters to Pascal-compatible functions are evaluated left to right and are pushed onto the stack in the order they are evaluated. Characters and enumeration types whose literal values fall in the range of types char or unsigned char are pushed as bytes. (This requires a 16-bit word on the stack. The value is in the high-order 8 bits; the low-order 8 bits are unused.) Short ints and enumeration types whose literal values fall in the range of types short or unsigned short are passed as 16-bit values. Ints, long ints, and the

**Lisa Workshop C User's Guide**

remaining enumeration types are passed as 32-bit values. Pointers and arrays are passed as 32-bit addresses. SANE types float, double, comp, and extended are passed as extended 80-bit values; however this doesn't correspond to the Pascal compiler's calling conventions, so a compiler warning is given. The table in Section 1.10.3 shows the recommended way to pass SANE-type values to Pascal. Structures are also passed by value on the stack, and also yield a compiler warning. Their size is rounded up to a multiple of 16 bits (2 bytes). If rounding occurs, the unused storage has the highest memory address. The function being called removes the parameters from the stack.

**3.2.2 Results**

Function results are returned on the stack. Stack space for the function result is reserved by the caller prior to pushing any parameters. Characters and enumeration types whose literal values fall in the range of types char or unsigned char are returned as bytes. (This requires a 16-bit word on the stack. The value is in the high-order 8 bits; the low-order 8 bits are unused.) Short ints and enumeration types whose literal values fall in the range of types short or unsigned short are returned as 16-bit values. Ints, long ints, and the remaining enumeration types are returned as 32-bit values. Pointers are returned as 32-bit addresses. Arrays may not be returned as function results. Results of type float are returned as 32-bit values. For structures and types double, comp, and extended the caller pushes the address of a structure, double, comp, or extended (respectively) in the function-result location on the stack. The procedure being called stores the result at this address. The caller removes the function results from the stack.

**3.2.3 Register Conventions**

Registers D0, D1, D2, A0, and A1 are scratch registers. Scratch registers are not preserved by Pascal-compatible functions. All other registers are preserved. Register A5 is the global frame pointer, register A6 is the local frame pointer, and register A7 is the stack pointer.

**3.3 Compiler Limitations**

On the Macintosh, the total size of all declared global variables, static variables, and string constants cannot exceed 32K bytes. Allocate large global arrays on the heap in order to avoid exceeding this limit.

It is impossible to compile very large functions on the Lisa because the compiler's internal data structures cannot fit in memory. As functions approach this limit, compilation time increases noticeably. This problem can be alleviated by eliminating unnecessary include files, reducing the number of global declarations, compiling large functions separately, and rewriting large functions as two or more smaller functions. In addition, renaming Workshop files system.debug and system.debug2, then rebooting, will give the compiler an additional 80K bytes of memory.

Static functions are not supported in this implementation of C due to limitations in the Lisa Workshop object-file definition. Use of static functions may result in this linker message:

```
*** Error - Reference to unknown module type. ***
```

Static functions can be eliminated by including the define

```
#define static
```

at the beginning of each compilation or source file.

## Lisa Workshop C User's Guide

### 4. Running the Compiler

The C compiler is named `c.obj`. To run the compiler, use the Lisa Workshop Run command, as shown in the example below. Source file names must end with the suffix `".c.text"`. The `".text"` suffix need not be specified in response to the input file prompt. The error-listing file is the console by default. The output file (object code file) name is by default the source file name, with the `".text"` suffix replaced by `".obj"`.

Compiler options may be specified by responding to any of the file name prompts by typing a question mark (?) and then pressing Return. The compiler will present a partial list of the available options (a complete list appears below). Enter the options you want, including minus sign (-) prefixes, on a single line separated by spaces. The compiler will then repeat the file name prompt.

The example below compiles the program `mac/c/sample/qdsample.c.text`, writing the error listing to the console and creating the object file `mac/c/sample/qdsample.obj`. The `-M` option is used to direct the code to segment `sample`. Prompts supplied by the Workshop and the compiler are shown in plain text. Default file names appear within the prompts in brackets. What you type is printed in boldface. "`<Return>`" means press the Return key.

```

r
Run what program? c <Return>
C-68/Lisa 1.8.3 Copyright (c) 1984, 1985 Green Hills Software, Inc.
Name of input file [.TEXT] ? <Return>
Useful options include:
-Mname      Compile into segment 'name'.
-Dname      Define 'name' with value 1.
-Dname=string Define 'name' with value 'string'.
-Uname:     Undefine 'name'.
-Iprefix    Add 'prefix' to include-file names.
-E          Write preprocessor output to file 'preproc.text'.
-g          Generate debug symbols in code.
Enter options separated by blanks and followed by <Return>
Options> -Msample <Return>
Name of input file [.TEXT] mac/c/sample/qdsample.c <Return>
Name of error listing file [-console] / [.TEXT] <Return>
Name of binary file [ mac/c/sample/qdsample.c ] [.OBJ] <Return>

```

#### 4.1 Compiler Options

The Workshop C compiler recognizes the following options:

<u>Option</u>	<u>Description</u>
<code>-Mname</code>	Name the object-code segment. Since a segment may not exceed 32K bytes, large programs require multiple segments with different names. The default segment name is 8 blanks.
<code>-Dname</code>	Define <code>name</code> to the preprocessor with the value 1. This is equivalent to writing <code>#define name 1</code> at the beginning of the source file.
<code>-Dname=string</code>	Define <code>name</code> to the preprocessor with the value "string". This is equivalent to writing <code>#define name string</code> at the beginning of the source file.
<code>-Uname</code>	Undefine the predefined preprocessor symbol <code>name</code> . This is equivalent to writing <code>#undef name</code> at the beginning of the source file.

- Istring**      Include file names that do not start with "-" are searched for with the file name prefix "string". Multiple **-I** options can be specified. They will be searched in the order encountered. The include-file search rules are explained in detail in section 4.2.
- w**              Suppress compiler warning messages. By default, warnings are written to the error listing file.
- E**              Do not compile the program. Instead, write the output of the preprocessor to file `preproc.text`. This option is useful for debugging preprocessor macros.
- C**              Include comments with the preprocessor output. By default, comments are not written to the preprocessor output.
- g**              Generate 8-byte function names embedded in the code for the debugger; generate frame pointers in A6 (`LINK A6,x ... UNLK A6`).
- ga**             Generate stack frame pointers in A6 (`LINK A6,x ... UNLK A6`) for all functions.
- X6**             Use `MOVE #0,x` instructions rather than `CLR x` instructions for nonstack addresses. This may be useful when writing device drivers.
- X9**             Disable local (peephole) optimizations.
- X12**            Generate 68010 code rather than 68000 code.
- Z6**             Always allocate 32 bits for enumerated data types. The default is to allocate 8, 16, or 32 bits.
- X55**            Make bit fields of type `int`, `short`, and `char` signed. The default is to make all fields unsigned.

#### 4.2 Include-File Search Rules

The compiler automatically searches for include files in the manner described below. The first file successfully opened using these rules is included.

<u>Include-File Name</u>	<u>Example</u>	<u>Search Rules</u>
Begins with "-"	<code>#include &lt;lower-consts.h&gt;</code> <code>#include "-lower-consts.h"</code>	Use the specified name. None of the other search rules apply.
In angle brackets.	<code>#include &lt;ctype.h&gt;</code>	Begin the search using the prefix "mac/c/include/". Continue the search by prefixing the file name with strings supplied as <b>-I</b> options.
In double quotes.	<code>#include "constants.h"</code>	Begin the search using the prefix (up to the final "/") of the source file that contains the include. Continue by prefixing the file name with strings supplied as <b>-I</b> options. Finally, try the include-file name without any prefix.

## Lisa Workshop C User's Guide

### 5. Files to Link With

Workshop C programs should be linked using the linker, `linker.obj`. Programs to be executed on the Macintosh must be linked with one or more of the object files listed below. Programs must be linked with the object files that correspond to the libraries the program uses.

If no Standard C Library functions are called, link with:

<code>mac/c/lib/runtime.obj</code>	Execution starting point.
------------------------------------	---------------------------

If Standard C Library functions are called, link with one of the following:

<code>mac/c/lib/cruntime.obj</code>	Doesn't prompt for <i>argv</i> and <i>argc</i> at the start of execution.
<code>mac/c/lib/cruntimeargv.obj</code>	Prompts for <i>argv</i> and <i>argc</i> .

If Standard C Library functions are called, also link with:

<code>mac/c/lib/stdclib.obj</code>	Standard C Library.
<code>mac/c/lib/stdprintf.obj</code>	Standard C Library <i>printf</i> functions.
<code>mac/c/lib/math.obj</code>	Standard C Library math functions.

If SANE library functions are called or floating-point arithmetic is used, also link with:

<code>mac/c/lib/sanelib.obj</code>	SANE numerics.
------------------------------------	----------------

If Macintosh Interface Libraries functions are called, also link with:

<code>mac/c/lib/interface.obj</code>	Macintosh Interface Libraries.
--------------------------------------	--------------------------------

If Macintosh Interface Libraries printing functions are called, also link with one of the following:

<code>obj/prlink.obj</code>	High-level printing interfaces.
<code>obj/prscreen.obj</code>	Low-level printing interfaces.



**Lisa Workshop C User's Guide**

**6. Standard C Library**

This section describes the Standard C Library provided with Workshop C. After an introductory discussion of error-number conventions, the section is arranged alphabetically by function name or category. The Library Index is an index of the defines, types, enumeration literals, global variables, and functions defined here and in the Macintosh Interface Libraries.

Remember that identifiers in C are case sensitive and should be spelled *exactly as shown in the synopsis*. Following English usage, we've capitalized the first letter of a lowercase identifier when it appears at the beginning of a sentence.

## Error Numbers

## Standard C Library

## Error Numbers

## NAME

Introduction to error numbers similar to those in UNIX operating systems.

## SYNOPSIS

```
#include <errno.h>

extern int errno;
```

## DESCRIPTION

Many of the Standard C Library functions have one or more error returns. An error condition is indicated by an otherwise impossible returned value. This is almost always `-1`; see descriptions of individual functions for details. An error number is also made available in the external variable `errno`. `Errno` is not cleared on successful calls, so it should be tested only after an error has been indicated.

The error name appears in brackets following the text in a library function description; for example,

```
"The next attempt to write a nonzero number of bytes will signal an
error. [ENOSPC]"
```

Not all possible error numbers are listed for each library function because many errors are possible for most of the calls. Some UNIX operating system error numbers do not apply to Macintosh and are not documented in this manual.

Here is a list of the error numbers and their names as defined in the `<errno.h>` file:

- 1 [EPERM] Not owner  
Typically this error indicates an attempt to modify a file in a way that is not permitted.
- 2 [ENOENT] No such file or directory  
This error occurs when a file whose filename is specified does not exist or when one of the directories in a pathname does not exist.
- 5 [EIO] I/O error  
Some physical I/O error has occurred. This error may in some cases be signaled on a call following the one to which it actually applies.
- 6 [ENXIO] No such device or address  
I/O on a special file refers to a subdevice that does not exist, or the I/O is beyond the limits of the device. This error may also occur when, for example, no disk is present in a drive.
- 9 [EBADF] Bad file number  
Either a file descriptor does not refer to an open file, or a read (or write) request is made to a file that is open only for writing (or reading).

Error Numbers	Standard C Library	Error Numbers
12	<b>[ENOMEM] Not enough space</b> The system ran out of memory while the library call was executing.	
13	<b>[EACCES] Permission denied</b> An attempt was made to access a file in a way forbidden by the protection system.	
17	<b>[EEXIST] File exists</b> An existing file was mentioned in an inappropriate context—e.g., <code>open(file, O_CREAT+O_EXCL)</code> .	
19	<b>[ENODEV] No such device</b> An attempt was made to apply an inappropriate system call to a device—e.g., read a write-only device.	
20	<b>[ENOTDIR] Not a directory</b> An object that is not a directory was specified where a directory is required—e.g., in a path prefix.	
21	<b>[EISDIR] Is a directory</b> An attempt was made to write on a directory.	
22	<b>[EINVAL]] Invalid argument</b> Some invalid argument was provided to a library function.	
23	<b>[ENFILE] File table overflow</b> The system's table of open files is full, so temporarily a call to <code>open()</code> cannot be accepted.	
24	<b>[EMFILE] Too many open files</b> No program may have more than 20 file descriptors open at a time.	
28	<b>[ENOSPC] No space left on device</b> During a <code>write()</code> to an ordinary file, there is no free space left on the device.	
29	<b>[ESPIPE] Illegal seek</b> An <code>lseek()</code> was issued incorrectly.	
30	<b>[EROFS] Read-only file system</b> An attempt to modify a file or directory was made on a device mounted for read-only access.	

**NOTE**

Calls that interface to the Macintosh I/O system—e.g., `open()`, `close()`, `read()`, `write()`, `ioctl()`, and others—set the external variable *MacOSErr* as well as *errno*. This manual documents only *errno* values. The equivalent Macintosh ROM error-return values set in *MacOSErr* are documented in *Inside Macintosh*. The appropriate include file for most values of *MacOSErr* is `<files.h>`.

**ABS**

**Standard C Library**

**ABS**

**NAME**

*abs*—return integer absolute value

**SYNOPSIS**

```
int abs (i)
int i;
```

**DESCRIPTION**

*Abs* returns the absolute value of its integer operand.

**NOTE**

The absolute value of the negative integer with largest magnitude is undefined.

**SEE ALSO**

*floor()*.

ATOF

Standard C Library

ATOF

## NAME

*atof*—convert ASCII string to floating-point number

## SYNOPSIS

```
extended atof (nptr)
char *nptr;
```

## DESCRIPTION

*Atof* converts a character string pointed to by *nptr* to an extended-precision floating-point number. The first unrecognized character ends the conversion. *Atof* recognizes an optional string of white-space characters (blanks or tabs), then an optional sign, then a string of digits optionally containing a decimal point, then an optional "e" or "E" followed by an optionally signed integer. If the string begins with an unrecognized character, *atof* returns a NaN.

## DIAGNOSTICS

*Atof* honors the floating-point exception flags—invalid operation, underflow, overflow, divide by zero, and inexact—as prescribed by the Standard Apple Numeric Environment (SANE).

## SEE ALSO

*scanf()*, *str2dec()*, *dec2num()*.  
*Apple Numerics Manual*.

ATOI

Standard C Library

ATOI

NAME

`atoi`—convert string to integer

SYNOPSIS

```
int atoi (str)
char *str;
```

DESCRIPTION

*Atoi* returns as an integer the decimal value represented by the character string *str*. The string is scanned up to the first nondigit character other than an optional leading minus sign (-). Leading white-space characters (blanks and tabs) are ignored.

NOTE

Overflow conditions are ignored.

SEE ALSO

`atof()`, `scanf()`.

**CLOSE**

**Standard C Library**

**CLOSE**

**NAME**

**close**—close a file descriptor

**SYNOPSIS**

```
int close (fildes)
int fildes;
```

**DESCRIPTION**

*Fildes* is a file descriptor obtained from a `creat()` or `open()` call. *Close* closes the file descriptor indicated by *fildes*.

*Close* fails if *fildes* is not a valid open file descriptor. [EBADF]

**RETURN VALUE**

Upon successful completion, a value of 0 is returned. Otherwise, a value of -1 is returned and *errno* is set to indicate the error.

**SEE ALSO**

`creat()`, `open()`.

CONV

Standard C Library

CONV

## NAME

*toupper*, *tolower*, *\_toupper*, *\_tolower*, *toascii*  
—translate characters

## SYNOPSIS

```
#include <ctype.h>

int toupper (c)
int c;

int tolower (c)
int c;

int _toupper (c)
int c;

int _tolower (c)
int c;

int toascii (c)
int c;
```

## DESCRIPTION

*Toupper* and *tolower* have as domain the range of *getc()*: the integers from -1 through 255. If the argument of *toupper* represents a lowercase letter, the result is the corresponding uppercase letter. If the argument of *tolower* represents an uppercase letter, the result is the corresponding lowercase letter. All other arguments in the domain are returned unchanged.

*\_Toupper* and *\_tolower* are macros that accomplish the same thing as *toupper* and *tolower* but have restricted domains and are faster. *Toupper* requires a lowercase letter as its argument; its result is the corresponding uppercase letter. *\_Toupper* requires an uppercase letter as its argument; its result is the corresponding lowercase letter. Arguments outside the domain cause undefined results.

*Toascii* yields its argument with all bits turned off that are not part of a standard ASCII character; it is intended for compatibility with other systems

## SEE ALSO

*ctype*, *getc()*.



**CREAT****Standard C Library****CREAT****NAME**

`creat`—create a new file or rewrite an existing file

**SYNOPSIS**

```
int creat (path)
char *path;
```

**DESCRIPTION**

*Creat* creates a new file or prepares to rewrite an existing file named by the pathname pointed to by *path*. If the file exists, the length of its data fork is truncated to 0.

*Creat* is equivalent to `open(path, O_WRONLY|O_TRUNC)`.

Upon successful completion, a nonnegative integer (the file descriptor) is returned and the file is open for writing. The file pointer is set to the beginning of the file. A maximum of 20 files may be open at a given time.

**RETURN VALUE**

Upon successful completion, a nonnegative integer (the file descriptor) is returned. Otherwise, a value of `-1` is returned and *errno* is set to indicate the error.

**SEE ALSO**

`close()`, `lseek()`, `open()`, `read()`, `write()`.

## CTYPE

## Standard C Library

## CTYPE

## NAME

*isalpha*, *isupper*, *islower*, *isdigit*, *isxdigit*, *isalnum*, *isspace*, *ispunct*, *isprint*,  
*isgraph*, *isctrl*, *isascii*  
 —classify characters

## SYNOPSIS

```
#include <ctype.h>

int isalpha (c)
int c;
```

## DESCRIPTION

These macros classify character-coded integer values by table lookup. Each is a predicate returning nonzero for true, zero for false. *isascii* is defined on all integer values; the rest are defined only where *isascii* is true and on the single non-ASCII value EOF (-1).

<i>isalpha</i>	<i>c</i> is a letter.
<i>isupper</i>	<i>c</i> is an uppercase letter.
<i>islower</i>	<i>c</i> is a lowercase letter.
<i>isdigit</i>	<i>c</i> is a digit [0-9].
<i>isxdigit</i>	<i>c</i> is a hexadecimal digit [0-9], [A-F], or [a-f].
<i>isalnum</i>	<i>c</i> is alphanumeric (letter or digit).
<i>isspace</i>	<i>c</i> is a space, tab, return, new line, vertical tab, or form feed.
<i>ispunct</i>	<i>c</i> is a punctuation character (neither control nor alphanumeric).
<i>isprint</i>	<i>c</i> is a printing character, code 040 (space) through 0176 (tilde).
<i>isgraph</i>	<i>c</i> is a printing character, similar to <i>isprint</i> except false for space.
<i>isctrl</i>	<i>c</i> is a delete character (0177) or an ordinary control character (less than 040).
<i>isascii</i>	<i>c</i> is an ASCII character, code less than 0200.

## DIAGNOSTICS

If the argument to any of these macros is not in the domain of the function, the result is undefined.

ECVT

Standard C Library

ECVT

## NAME

*ecvt*, *fcvt*—convert floating-point number to string

## SYNOPSIS

```
char *ecvt(value, ndigit, decpt, sign)
extended value;
int ndigit, *decpt, *sign;

char *fcvt(value, ndigit, decpt, sign)
extended value;
int ndigit, *decpt, *sign;
```

## DESCRIPTION

*Ecv* converts *value* to a null-terminated string of *ndigit* digits and returns a pointer to this string as the function result. The low-order digit is rounded.

The decimal point is not included in the returned string. The position of the decimal point is indicated by *decpt*, which indirectly stores the position of the decimal point relative to the returned string. If the int pointed to by *decpt* is negative, the decimal point lies to the left of the returned string. For example, if the string is "12345" and *decpt* points to an int of 3, the value of the string is 123.45; if *decpt* points to -3, the value of the string is .00012345.

If the sign of the converted value is negative, the word pointed to by *sign* is nonzero; otherwise it is zero.

*Fcv* and *ecvt* provide fixed-point output in the style of Fortran F-format output, with the following difference in the interpretation of *ndigit*:

In *fcvt*, *ndigit* specifies the number of digits to the right of the decimal point.  
In *ecvt*, *ndigit* specifies the number of digits in the string.

## NOTE

The string pointed to by the function result is static data whose content is overwritten by each call.

## SEE ALSO

`printf()`, `num2dec()`, `dec2str`.  
*Apple Numerics Manual*.

EXIT

Standard C Library

EXIT

NAME

`exit`, `_exit`—terminate the current application

SYNOPSIS

```
void exit(status)
int status;
void _exit(status)
int status;
```

DESCRIPTION

*Exit* terminates the current application, closing all of the open file descriptors. It also causes `stdio()` cleanup actions before the application terminates.

The function `_exit` circumvents all cleanup.

EXP

## Standard C Math Library

EXP

## NAME

`exp`, `log`, `log10`, `pow`, `sqrt`  
 —exponential, logarithm, power, square-root functions

## SYNOPSIS

```
#include <math.h>
```

```
extended exp(x)
extended x;
```

```
extended log(x)
extended x;
```

```
extended log10(x)
extended x;
```

```
extended pow(x, y)
extended x, y;
```

```
extended sqrt(x)
extended x;
```

## DESCRIPTION

*Exp* returns  $e^x$ , where  $e$  is the natural logarithm base.

*Log* returns the natural logarithm (base  $e$ ) of  $x$ .

*Log10* returns the logarithm base ten of  $x$ .

*Pow* returns  $x^y$ .

*Sqrt* returns the square root of  $x$ .

For special cases, these functions return a NaN or signed infinity as appropriate.

## DIAGNOSTICS

These functions honor the floating-point exception flags—invalid operation, underflow, overflow, divide by zero, and inexact—as prescribed by the Standard Apple Numeric Environment (SANE).

## SEE ALSO

`hypot()`, `sinh()`.  
*Apple Numerics Manual*.

FCLOSE

Standard C Library

FCLOSE

## NAME

*fclose*, *fflush*—close or flush a stream

## SYNOPSIS

```
#include <stdio.h>
```

```
int fclose (stream)
FILE *stream;
```

```
int fflush (stream)
FILE *stream;
```

## DESCRIPTION

*Fclose* causes any buffered data for *stream* to be written out; *stream* is then closed.

*Fclose* is performed automatically for all open files upon calling *exit()*.

*Fflush* causes any buffered data for *stream* to be written out; *stream* remains open.

## DIAGNOSTICS

These functions return 0 for success or EOF if an error was detected (such as trying to write to a file that has not been opened for writing).

## SEE ALSO

*close()*, *exit()*, *fopen()*, *setbuf()*.

## FERROR

## Standard C Library

## FERROR

## NAME

*feof*, *feof*, *clearerr*, *fileno*—stream status inquiries

## SYNOPSIS

```
#include <stdio.h>

int feof (stream)
FILE *stream;

int ferror (stream)
FILE *stream;

void clearerr (stream)
FILE *stream;

int fileno (stream)
FILE *stream;
```

## DESCRIPTION

*Feof* returns nonzero when end-of-file has previously been detected reading the named input stream; otherwise, it returns zero.

*Ferror* returns nonzero when an I/O error has previously occurred reading from or writing to the named stream; otherwise, it returns zero.

*Clearerr* resets the error indicator and end-of-file indicator to zero on the named stream.

*Fileno* returns the integer file descriptor associated with the named stream; see *open()*.

## NOTE

All these functions are implemented as macros; they cannot be declared or redeclared.

## SEE ALSO

*open()*, *fopen()*.

## FLOOR

## Standard C Math Library

## FLOOR

## NAME

floor, ceil, fmod, fabs—floor, ceiling, mod, absolute value functions

## SYNOPSIS

```
#include <math.h>
```

```
extended floor(x)  
extended x;
```

```
extended ceil(x)  
extended x;
```

```
extended fmod(x, y)  
extended x, y;
```

```
extended fabs(x)  
extended x;
```

## DESCRIPTION

*Floor* returns the largest integer (as an extended-precision number) not greater than *x*.

*Ceil* returns the smallest integer not less than *x*.

Whenever possible, *fmod* returns the number *f* with the same sign as *x*, such that  $x = iy + f$  for some integer *i*, and  $|f| < |y|$ . If *y* is zero, *fmod* returns a NaN.

*Fabs* returns  $|x|$ .

## SEE ALSO

*abs()*, *rint()*, *setround()*.  
*Apple Numerics Manual*.



FOPEN

Standard C Library

FOPEN

## NAME

*fopen*, *freopen*, *fdopen*—open a stream

## SYNOPSIS

```
#include <stdio.h>
```

```
FILE *fopen (filename, type)
char *filename, *type;
```

```
FILE *freopen (filename, type, stream)
char *filename, *type;
FILE *stream;
```

```
FILE *fdopen (fildes, type)
int fildes;
char *type;
```

## DESCRIPTION

*Fopen* opens the file named by *filename* and associates a stream with it. *Fopen* returns a pointer to the FILE structure associated with the stream.

*Filename* points to a character string that contains the name of the file to be opened.

*Type* is a character string having one of the following values:

- r**      open for reading
- w**      truncate or create for writing
- a**      **append:** open for writing at end-of-file, or create for writing.
- r+**     open for update (reading and writing).
- w+**     truncate or create for update
- a+**     **append:** open or create for update at end-of-file

*Freopen* substitutes the named file for the open stream. The original stream is closed, regardless of whether the open ultimately succeeds. *Freopen* returns a pointer to the FILE structure associated with *stream*.

*Freopen* is typically used to attach the previously opened streams associated with *stdin*, *stdout*, and *stderr* to other files.

*Fdopen* associates a stream with a file descriptor by formatting a file structure from the file descriptor. Thus, *fdopen* can be used to access the file descriptors returned by *open()* or *creat()*. (These calls open files but do not return pointers to a FILE structure.) The type of stream must agree with the mode of the open file.

When a file is opened for update, both input and output may be done on the resulting stream. However, output may not be directly followed by input without an intervening *fseek()* or *rewind()*, and input may not be directly followed by

**FOPEN****Standard C Library****FOPEN**

output without an intervening `fseek()`, `rewind()`, or an input operation that encounters end-of-file.

When a file is opened for append (i.e., when *type* is "a" or "a+"), it is impossible to overwrite information already in the file. `fseek()` may be used to reposition the file pointer to any position in the file, but when output is written to the file the current file pointer is disregarded. All output is written at the end of the file and causes the file pointer to be repositioned at the end of the output.

**DIAGNOSTICS**

*Fopen* and *freopen* return a null pointer on failure.

**SEE ALSO**

`open()`, `fclose()`.

FREAD

Standard C Library

FREAD

## NAME

fread, fwrite—binary input/output

## SYNOPSIS

```
#include <stdio.h>
```

```
int fread(ptr, size, nitems, stream)
```

```
char *ptr;
```

```
int size, nitems;
```

```
FILE *stream;
```

```
int fwrite(ptr, size, nitems, stream)
```

```
char *ptr;
```

```
int size, nitems;
```

```
FILE *stream;
```

## DESCRIPTION

*Fread* copies *nitems* items of data from the named input stream into an array beginning at *ptr*. An item of data is a sequence of bytes (not necessarily terminated by a null byte) of length *size*. *Fread* stops appending bytes if an end-of-file or error condition is encountered while reading *stream* or if *nitems* items have been read. *Fread* leaves the file pointer in *stream*, if defined, pointing to the byte following the last byte read if there is one. *Fread* does not change the contents of *stream*.

*Fwrite* appends at most *nitems* items of data to the named output stream from the array pointed to by *ptr*. *Fwrite* stops appending when it has appended *nitems* items of data or if an error condition is encountered on *stream*. *Fwrite* does not change the contents of the array pointed to by *ptr*.

The variable *size* is typically `sizeof(*ptr)` where the pseudo-function *sizeof* specifies the length of an item pointed to by *ptr*. If *ptr* points to a data type other than `char` it should be cast into a pointer to `char`.

## DIAGNOSTICS

*Fread* and *fwrite* return the number of items read or written. If *nitems* is zero or negative, no characters are read or written and zero is returned by both *fread* and *fwrite*.

## SEE ALSO

`fopen()`, `getc()`, `gets()`, `printf()`, `putc()`, `puts()`, `read()`,  
`scanf()`, `stdio()`, `write()`.

## FREXP

## Standard C Library

## FREXP

## NAME

`frexp`, `ldexp`, `modf`—manipulate parts of floating-point numbers

## SYNOPSIS

```
extended frexp(value, eptr)
extended value;
int *eptr;
```

```
extended ldexp(value, exp)
extended value;
int exp;
```

```
extended modf(value, iptr)
extended value, *iptr;
```

## DESCRIPTION

Every nonzero number can be written uniquely as  $x \cdot 2^n$ , where the mantissa (fraction)  $x$  is in the range  $0.5 \leq |x| < 1.0$ , and the exponent  $n$  is an integer. *Frexp* returns the mantissa of an extended value and stores the exponent indirectly in the location pointed to by *eptr*. Note that the mantissa here differs from the significand described in the *Apple Numerics Manual*, whose normal values are in the range  $1.0 \leq |x| < 2.0$ .

*Ldexp* returns the quantity  $value \cdot 2^{exp}$ .

*Modf* returns the signed fractional part of *value* and stores the integral part indirectly in the location pointed to by *iptr*.

## DIAGNOSTICS

*Ldexp* honors the floating-point exception flags—invalid operation, underflow, overflow, divide by zero, and inexact—as prescribed by the Standard Apple Numeric Environment (SANE).

## SEE ALSO

`logb()`, `scalb()`.  
*Apple Numerics Manual*.

FSEEK

Standard C Library

FSEEK

## NAME

*fseek*, *rewind*, *ftell*—reposition a file pointer in a stream

## SYNOPSIS

```
#include <stdio.h>

int fseek (stream, offset, ptrname)
FILE *stream;
long offset;
int ptrname;

void rewind (stream)
FILE *stream;

long ftell (stream)
FILE *stream;
```

## DESCRIPTION

*Fseek* sets the position of the next input or output operation on the stream. The new position is at the signed distance *offset* bytes from the beginning, the current position, or the end of the file, when the value of *ptrname* is 0, 1, or 2, respectively.

*Rewind*(stream) is equivalent to *fseek*(stream, 0L, 0) except that no value is returned.

*Fseek* and *rewind* undo any effects of *ungetc*().

After *fseek* or *rewind*, the next operation on a file opened for update may be either input or output.

*Ftell* returns the offset of the current byte relative to the beginning of the file associated with the named stream.

## DIAGNOSTICS

*Fseek* returns nonzero for improper seeks; otherwise it returns 0. An improper seek can be, for example, an *fseek* done on a file that has not been opened via *fopen*().

## SEE ALSO

*lseek*(), *fopen*().

GETC

Standard C Library

GETC

## NAME

*getc*, *getchar*, *fgetc*, *getw*—get character or word from stream

## SYNOPSIS

```
#include <stdio.h>
```

```
int getc(stream)
FILE *stream;
```

```
int getchar()
```

```
int fgetc(stream)
FILE *stream;
```

```
int getw(stream)
FILE *stream;
```

## DESCRIPTION

*Getc* returns the next character (i.e., byte) from the named input stream. It also moves the file pointer, if defined, ahead one character in *stream*. *Getc* is a macro and therefore cannot be used if a function is necessary; for example, you cannot have a function pointer point to it.

*Getchar* returns the next character from the standard input stream, *stdin*. Like *getc*, *getchar* is a macro.

*Fgetc* behaves like *getc* but is a function. *Fgetc* runs more slowly than *getc* but takes less space per invocation.

*Getw* returns the next "word" (i.e., four bytes) from the named input stream so that the order of bytes in the stream corresponds to the order of bytes in memory. *Getw* returns the constant EOF upon end-of-file or error. Since EOF is a valid integer value, *feof()* and *ferror()* should be used to check the success of *getw*. *Getw* increments the associated file pointer, if defined, to point to the next word. *Getw* assumes no special alignment in the file.

## DIAGNOSTICS

These functions return the integer constant EOF at end-of-file or upon an error.

## NOTE

Because it is implemented as a macro, *getc* treats incorrectly a stream argument with side effects. In particular, *getc(\*f++)* doesn't work as you would expect. Use *fgetc(\*f++)* instead.

## SEE ALSO

*fclose()*, *ferror()*, *fopen()*, *fread()*, *gets()*, *putc()*, *scanf()*, *stdio()*.

## GETS

## Standard C Library

## GETS

## NAME

*gets*, *fgets*—get a string from a stream

## SYNOPSIS

```
#include <stdio.h>
```

```
char *gets(s)  
char *s;
```

```
char *fgets(s, n, stream)  
char *s;  
int n;  
FILE *stream;
```

## DESCRIPTION

*Gets* reads characters from the standard input stream, *stdin*, into the array pointed to by *s*, until a newline character is read or an end-of-file condition is encountered. The newline character is discarded and the string is terminated with a null character.

*Fgets* reads characters from the stream into the array pointed to by *s* until *n*-1 characters are read, or a newline character is read and transferred to *s*, or an end-of-file condition is encountered. The string is then terminated with a null character.

## DIAGNOSTICS

If end-of-file is encountered and no characters have been read, no characters are transferred to *s* and a null pointer is returned. If a read error occurs, a null pointer is returned. Otherwise *s* is returned. (A read error will occur, for example, if you attempt to use these functions on a file that has not been opened for reading.)

## SEE ALSO

*ferror()*, *fopen()*, *fread()*, *getc()*, *scanf()*, *stdio()*.

## HYPOT

## Standard C Math Library

## HYPOT

## NAME

hypot—Euclidean distance function

## SYNOPSIS

```
#include <math.h>
```

```
extended hypot (x, y)
```

```
extended x, y;
```

## DESCRIPTION

*Hypot* returns

$$\sqrt{x * x + y * y}$$

taking precautions against unwarranted overflows.

## DIAGNOSTICS

*Hypot* honors the floating-point exception flags—invalid operation, underflow, overflow, divide by zero, and inexact—as prescribed by the Standard Apple Numeric Environment (SANE).

## SEE ALSO

`sqrt()`.

*Apple Numerics Manual*.



## LSEEK

## Standard C Library

## LSEEK

## NAME

`lseek`—move read/write file pointer

## SYNOPSIS

```
long lseek (fildes, offset, whence)
int fildes;
long offset;
int whence;
```

## DESCRIPTION

*Fildes* is a file descriptor returned from a `creat()` or `open()` call. *Lseek* sets the file pointer associated with *fildes* as follows:

If *whence* is 0, the pointer is set to *offset* bytes

If *whence* is 1, the pointer is set to its current location plus *offset*.

If *whence* is 2, the pointer is set to the size of the file plus *offset*.

Upon successful completion, the resulting pointer location as measured in bytes from the beginning of the file is returned.

*Lseek* fails and the file pointer remains unchanged if one or more of the following are true:

*Fildes* is not an open file descriptor. [EBADF]

*Whence* is not 0, 1, or 2. [EINVAL]

The resulting file pointer would be negative. [EINVAL]

Some devices are incapable of seeking. The value of the file pointer associated with such a device is undefined.

## RETURN VALUE

Upon successful completion, a nonnegative integer indicating the file pointer value is returned. Otherwise, a value of `-1` is returned and *errno* is set to indicate the error.

## NOTE

In previous versions of the Standard C Library, `tell(fildes)` was a function that returned the current file position. It is equivalent to the call `lseek(fildes, 0L, 1)`.

## SEE ALSO

`creat()`, `open()`.

## MALLOC

## Standard C Library

## MALLOC

## NAME

`malloc`, `free`, `realloc`, `calloc`—main memory allocator

## SYNOPSIS

```
char *malloc(size)
unsigned size;

void free(ptr)
char *ptr;

char *realloc(ptr, size)
char *ptr;
unsigned size;

char *calloc(nelem, elsize)
unsigned nelem, elsize;
```

## DESCRIPTION

*Malloc* and *free* provide a simple general-purpose memory allocation package. The memory that is allocated for a program's use is known as the "storage arena." The storage arena expands as *malloc* is called.

*Malloc* returns a pointer to a block of at least *size* bytes suitably aligned for any use. The argument to *free* is a pointer to a block previously allocated by *malloc*; after *free* is performed this space is made available for further allocation.

Undefined results occur if the space assigned by *malloc* is overrun or if some random value is handed to *free*.

*Malloc* allocates the first sufficiently large contiguous reach of free space it finds. It calls `NewPointer()` to get more memory from the system when there is no suitable space already free.

*Realloc* changes the size of the block pointed to by *ptr* to *size* bytes and returns a pointer to the (possibly moved) block. The contents are unchanged up to the lesser of the new and old sizes. If no free block of *size* bytes is available in the storage arena, *realloc* asks *malloc* to enlarge the storage arena by *size* bytes and then moves the data to the new space.

*Calloc* allocates space for an array of *nelem* elements of size *elsize*. The space is initialized to zeros.

## DIAGNOSTICS

*Malloc*, *realloc*, and *calloc* return a null pointer if there is no available memory or if the storage arena has been detectably corrupted by storing outside the bounds of a block. When this happens the block pointed to by *ptr* may have been destroyed.

## MEMORY

## Standard C Library

## MEMORY

## NAME

memccpy, memchr, memcmp, memcpy, memset—memory operations

## SYNOPSIS

```
char *memccpy(s1, s2, c, n)
char *s1, *s2;
int c, n;
```

```
char *memchr(s, c, n)
char *s;
int c, n;
```

```
int memcmp(s1, s2, n)
char *s1, *s2;
int n;
```

```
char *memcpy(s1, s2, n)
char *s1, *s2;
int n;
```

```
char *memset(s, c, n)
char *s;
int c, n;
```

## DESCRIPTION

These functions operate efficiently on memory areas (arrays of characters bounded by a count, not terminated by a null character). They do not check for the overflow of any receiving memory area.

*Memccpy* copies characters from memory area *s2* into *s1*, stopping after the first occurrence of character *c* has been copied or after *n* characters have been copied, whichever comes first. It returns either a pointer to the character after the copy of *c* in *s1* or a null pointer if *c* was not found in the first *n* characters of *s2*.

*Memchr* returns either a pointer to the first occurrence of character *c* in the first *n* characters of memory area *s* or a null pointer if *c* does not occur.

*Memcmp* compares its arguments, looking at the first *n* characters only. It returns an integer less than, equal to, or greater than 0, depending on whether *s1* is less than, equal to, or greater than *s2* in the ASCII collating sequence.

*Memcpy* copies *n* characters from memory area *s2* to *s1*. It returns *s1*.

*Memset* sets the first *n* characters in memory area *s* to the value of character *c*. It returns *s*.

## NOTE

Overlapping moves may yield unexpected results.

## OPEN

## Standard C Library

## OPEN

## NAME

`open`—open for reading or writing

## SYNOPSIS

```
#include <fcntl.h>

int open(path, oflag)
char *path;
int oflag;
```

## DESCRIPTION

*Path* points to a pathname naming a file. *Open* opens a file descriptor for the named file and sets the file status flags according to the value of *oflag*. *Oflag* values are constructed by or-ing flags from the following list (only one of the first three flags below may be used):

<code>O_RDONLY</code>	Open for reading only.
<code>O_WRONLY</code>	Open for writing only.
<code>O_RDWR</code>	Open for reading and writing.
<code>O_APPEND</code>	If set, the file pointer is set to the end of the file prior to each write.
<code>O_CREAT</code>	If the file does not exist, it is created.
<code>O_TRUNC</code>	If the file exists, its length is truncated to 0; the mode and owner are unchanged.
<code>O_EXCL</code>	If <code>O_EXCL</code> and <code>O_CREAT</code> are set, <i>open</i> fails if the file exists.

Upon successful completion a nonnegative integer, the file descriptor, is returned. No application may have more than 20 file descriptors open simultaneously. The file pointer used to mark the current position within the file is set to the beginning of the file.

The named file is opened unless one or more of the following are true:

- `O_CREAT` is not set and the named file does not exist. [ENOENT]
- 20 file descriptors are currently open. [EMFILE]
- `O_CREAT` and `O_EXCL` are set and the named file exists. [EEXIST]

## RETURN VALUE

Upon successful completion, a nonnegative integer (the file descriptor) is returned; otherwise, a value of `-1` is returned and *errno* is set to indicate the error.

## SEE ALSO

`close()`, `creat()`, `lseek()`, `read()`, `write()`.

## PRINTF

## Standard C Library

## PRINTF

NAME `printf`, `fprintf`, `sprintf`—print formatted output

## SYNOPSIS

```
#include <stdio.h>

int printf(format [ , arg ] ... )
char *format;

int fprintf(stream, format [ , arg ] ... )
FILE *stream;
char *format;

int sprintf(str, format [ , arg ] ... )
char *str, format;
```

## DESCRIPTION

*Printf* places formatted output on the standard output stream *stdout*. *Fprintf* places formatted output on the named output stream. *Sprintf* places formatted output, followed by the null character (`\0`), into the character array pointed to by *str*; it's your responsibility to ensure that enough storage is available. Each function returns the number of characters transmitted (not including the `\0` in the case of *sprintf*), or a negative value if an output error was encountered.

Each of these functions converts, formats, and prints its args under control of the format. The format is a character string that contains two types of objects: plain characters, which are simply copied to the output stream, and conversion specifications, each of which results in fetching zero or more args. The results are undefined if there are insufficient args for the format. If the format is exhausted while args remain, the extra args are ignored.

Each conversion specification is introduced by the character `%`. After `%`, the following appear in sequence:

- Zero or more flag characters, which modify the meaning of the conversion specification.
- An optional decimal digit string specifying a minimum field width. If the converted value has fewer characters than the field width, it will be padded to the field width on the left (default) or right (if the left-adjustment flag has been given); see below for flag specification.
- A precision that gives the minimum number of digits to appear for the `d`, `o`, `u`, `x`, or `X` conversions, the number of digits to appear after the decimal point for the `e`, `E`, and `f` conversions, the maximum number of significant digits for the `g` and `G` conversions, or the maximum number of characters to be printed from a string in `s` conversion. The format of the precision is a period (`.`) followed by a decimal digit string; a null digit string is treated as zero.
- An optional `l` specifying that a following `d`, `o`, `u`, `x`, or `X` conversion character applies to a long-integer arg. The `l` option is ignored in this implementation since integers and long integers both require 32 bits.

- A character that indicates the type of conversion to be applied.

A field width or precision may be indicated by an asterisk (\*) instead of a digit string. In this case, an integer arg supplies the field width or precision. The arg that is actually converted is not fetched until the conversion letter is seen; therefore, the args specifying field width or precision must appear immediately before the arg (if any) to be converted.

The flag characters and their meanings are:

- The result of the conversion will be left-justified within the field.
- + The result of a signed conversion always begins with a sign (+ or -).
- blank** If the first character of a signed conversion is not a sign, a blank will be prefixed to the result. This implies that if the **blank** and + flags both appear, the **blank** flag will be ignored.
- # This flag specifies that the value is to be converted to an "alternate form." For **c**, **d**, **s**, and **u** conversions, the flag has no effect. For **o** conversion, it increases the precision to force the first digit of the result to be a zero. For **x** (**X**) conversion, a nonzero result will have "0x" ("0X") prefixed to it. For **e**, **E**, **f**, **g**, and **G** conversions, the result will always contain a decimal point, even if no digits follow the point. (Normally, a decimal point appears in the result of these conversions only if a digit follows it.) For **g** and **G** conversions, trailing zeros in the fractional part will not be removed from the result (as they normally are).

The conversion characters and their meanings are:

- d,o,u,x,X** The integer arg is converted to signed decimal (**d**), unsigned octal (**o**), decimal (**u**), or hexadecimal notation (**x** and **X**), respectively; the letters "abcdef" are used for **x** conversion and the letters "ABCDEF" for **X** conversion. The precision specifies the minimum number of digits to appear; if the value being converted can be represented in fewer digits, it will be expanded with leading zeros. The default precision is 1. The result of converting a zero value with a precision of zero is a null string.
- f** The float, double, comp, or extended arg is converted to decimal notation in the style "[ - ]ddd.ddd", where the number of digits after the decimal point is equal to the precision specification. If the precision is missing, it is assumed to be 6; if the precision is explicitly 0, no decimal point appears. Infinities are printed as "[ - ]INF" and NaNs are printed as "[ - ]NAN(ddd)" where ddd is a code indicating why the result is not a number.
- e,E** The float, double, comp, or extended arg is converted in the style "[ - ]d.ddd±ddd", where there is one digit before the decimal point

## PRINTF

## Standard C Library

## PRINTF

and the number of digits after it is equal to the precision; when the precision is missing, it is assumed to be 6; if the precision is zero, no decimal point appears. The **E** format code produces a number with "E" instead of "e" introducing the exponent. The exponent always contains at least two digits. Infinities are printed as "INF" and NaNs are printed as "[*-*]NAN(*ddd*)", where *ddd* is a code indicating why the result is not a number.

- g,G** The float, double, comp, or extended arg is printed in style *f* or *e* (or in style **E** in the case of a **G** format code), with the precision specifying the number of significant digits. The style used depends on the value converted: style *e* is used only if the exponent resulting from the conversion is less than  $-4$  or greater than the precision. Trailing zeros are removed from the result. A decimal point appears only if it is followed by a digit.
- c** The character arg is printed.
- s** The arg is taken to be a string (character pointer) and characters from the string are printed until a NULL character ( $\backslash 0$ ) is encountered or the number of characters indicated by the precision specification is reached. If the precision is missing, it is taken to be infinite, so all characters up to the first null character are printed. If the string pointer arg has the value zero, the result is undefined. A null arg yields undefined results.
- %** Print a *%*; no argument is converted. In no case does a nonexistent or small field width cause truncation of a field; if the result of a conversion is wider than the field width, the field is simply expanded to contain the conversion result. Characters generated by *printf* and *fprintf* are printed as if *putc()* had been called.

## EXAMPLES

To print a date and time in the form "Sunday, July 3, 10:02", where weekday and month are pointers to null-terminated strings:

```
printf("%s, %s %d, %.2d:%.2d", weekday, month, day, hour, min);
```

To print pi to 5 decimal places:

```
printf("pi = %.5f", pi());
```

## SEE ALSO

*dec2str*, *ecvt()*, *num2dec()*, *putc()*, *scanf()*, *stdio()*.

PUTC

Standard C Library

PUTC

## NAME

`putc`, `putchar`, `fputc`, `putw`—put character or word on a stream

## SYNOPSIS

```
#include <stdio.h>

int putc(c, stream)
char c;
FILE *stream;

int putchar(c)
char c;

int fputc(c, stream)
char c;
FILE *stream;

int putw(w, stream)
int w;
FILE *stream;
```

## DESCRIPTION

*Putc* writes the character *c* to the output stream at the position pointed to by the file pointer, if one is defined. *Putchar*(*c*) is equivalent to `putc(c, stdout)`. *Putc* and *putchar* are macros.

*Fputc* behaves like *putc* but is a function rather than a macro. *Fputc* runs more slowly than *putc* but takes less space per invocation.

*Putw* writes the "word" *w* (i.e., four bytes) to the output stream at the position pointed to by the file pointer, if one is defined. *Putw* neither assumes nor causes special alignment in the file.

Output streams, with the exception of the standard error stream *stderr*, are by default buffered if the output refers to a file and line-buffered if the output refers to a window. *Stderr* is by default unbuffered, but use of `freopen()` causes it to become buffered or line-buffered. When an output stream is unbuffered information, it is queued for writing on the destination file or window as soon as written; when it is buffered, many characters are saved up and written as a block; when it is line-buffered, each line of output is queued for writing on the destination window as soon as the line is completed (i.e., as soon as a newline character is written or terminal input is requested). `Setbuf()` may be used to change the stream's buffering strategy.

## DIAGNOSTICS

On success, these functions each return the value they have written. On failure, they return the constant EOF. This occurs if the file stream is not open for writing or if the output file cannot be grown. Because EOF is a valid integer, `ferror()` should be used to detect *putw* errors.

## NOTE

Because it is implemented as a macro, *putc* treats incorrectly a stream argument with side effects. In particular, `putc(c, *f++)`; doesn't work as you would expect. *Fputc* should be used instead.



**PUTC**

**Standard C Library**

**PUTC**

**SEE ALSO**

`fclose()`, `ferror()`, `fopen()`, `fread()`, `getc()`, `printf()`, `puts()`,  
`setbuf()`, `stdio()`.

## PUTS

## Standard C Library

## PUTS

## NAME

`puts`, `fputs`—write a string to a stream

## SYNOPSIS

```
#include <stdio.h>
```

```
int puts(s)
char *s;
```

```
int fputs(s, stream)
char *s;
FILE *stream;
```

## DESCRIPTION

*Puts* writes the null-terminated string pointed to by *s*, followed by a newline character, to the standard output stream `stdout`.

*Fputs* writes the null-terminated string pointed to by *s* to the named output stream.

Neither function writes the terminating null character.

## DIAGNOSTICS

Both routines return EOF on error. This occurs if the routines try to write on a file that has not been opened for writing.

## NOTE

*Puts* appends a newline character while *fputs* does not.

## SEE ALSO

`ferror()`, `fopen()`, `fread()`, `printf()`, `putc()`, `stdio()`.

RAND

Standard C Library

RAND

## NAME

*rand*, *srand*—simple random-number generator

## SYNOPSIS

```
int rand( )
```

```
void srand(seed)  
unsigned seed;
```

## DESCRIPTION

*Rand* uses a multiplicative congruential random-number generator with period  $2^{32}$  that returns successive pseudorandom numbers in the range from 0 to  $2^{15}-1$ .

*Srand* can be called at any time to reset the random-number generator to a specific seed. The generator is initially seeded with a value of 1.

## SEE ALSO

*randomx*( ).

READ

Standard C Library

READ

## NAME

read—read from file

## SYNOPSIS

```
int read(fildes, buf, nbyte)
int fildes;
char *buf;
unsigned nbyte;
```

## DESCRIPTION

*Fildes* is a file descriptor obtained from a `creat()` or `open()` call.

*Read* attempts to read *nbyte* bytes from the file associated with *fildes* into the buffer pointed to by *buf*.

On devices capable of seeking, the read starts at a position in the file given by the file pointer associated with *fildes*. Upon return from *read*, the file pointer is incremented by the number of bytes actually read.

Nonseeking devices always read from the current position. The value of a file pointer associated with such a file is undefined.

Upon successful completion, *read* returns the number of bytes actually read and placed in the buffer; this number may be less than *nbyte* if the file is associated with a window or if the number of bytes left in the file is less than *nbyte* bytes. A value of 0 is returned when an end-of-file has been reached.

*Read* fails if *fildes* is not a valid file descriptor open for reading. [EBADF]

## RETURN VALUE

Upon successful completion a nonnegative integer is returned indicating the number of bytes actually read. Otherwise, -1 is returned and *errno* is set to indicate the error.

## SEE ALSO

`creat()`, `open()`, `stdio()`.

## SCANF

## Standard C Library

## SCANF

## NAME

scanf, fscanf, sscanf—convert formatted input

## SYNOPSIS

```
#include <stdio.h>

int scanf(format [ , pointer ] ... )
char *format;

int fscanf(stream, format [ , pointer ] ... )
FILE *stream;
char *format;

int sscanf(s, format [ , pointer ] ... )
char *s, *format;
```

## DESCRIPTION

*Scanf* reads characters from the standard input stream *stdin*. *Fscanf* reads characters from the named input stream, *stream*. *Sscanf* reads characters from the character string *s*. Each function converts the input according to a control string (*format*) and stores the results according to a set of *pointer* arguments that indicate where the converted output should be stored.

*Format*, the control string, contains specifications that control the interpretation of input sequences. The control string consists of characters to be matched in the input stream and/or conversion specifications that start with *%*. The control string may contain:

- White-space characters (blanks and tabs) that cause input to be read up to the next non-white-space character, except as described below.
- A character (any except *%*) that must match the next character of the input stream. To match a *%* character in the input stream, use "*%%*".
- Conversion specifications beginning with the character *%* and followed by an optional assignment suppression character *\**, an optional numeric maximum field width, an optional *l*, *m*, *n*, or *h* indicating the size of the receiving variable, and a conversion code.

An input field is defined relative to its conversion specification. The input field ends when the first character inappropriate for conversion is encountered or when the specified field width is exhausted. After conversion, the input pointer points to the inappropriate character.

A conversion specification directs the conversion of the next input field; the result is placed in the variable pointed to by the corresponding argument, which is a pointer to a basic C type such as *int* or *float*.

Assignment can be suppressed by preceding a format character with a *\**. Assignment suppression causes an input field to be skipped; the field is read and converted but not assigned. Therefore *pointer* should be omitted when assignment of the corresponding input field is suppressed.

SCANF

Standard C Library

SCANF

The format character dictates the interpretation of the input field. The following format characters are legal in a conversion specification, after %:

**%** A single % is expected in the input at this point; no assignment is done.

*The conversion characters d, u, o, and x may be preceded by l or h to indicate that a pointer to long or short, rather than int, is in the argument list. The l is ignored in this implementation because ints and longints are both 32 bits.*

**d** A decimal integer is expected; the corresponding argument should be an integer pointer.

**u** An unsigned decimal integer is expected; the corresponding argument should be an unsigned integer pointer.

**o** An octal integer is expected; the corresponding argument should be an integer pointer.

**x** A hexadecimal integer is expected; the corresponding argument should be an integer pointer.

*The conversion characters e, f, and g may be preceded by l, m, or n to indicate that a pointer to double, comp, or extended, rather than float, is in the argument list.*

**e,f,g** A floating-point number is expected; the next field is converted accordingly and stored through the corresponding argument, which should be a pointer to a float, double, comp, or extended, depending on the size specification. The input format for floating-point numbers is an optionally signed string of digits, possibly containing a decimal point, followed by an optional exponent field consisting of "E" or "e" followed by an optionally signed integer. In addition, infinity is represented by the string "INF", and NaNs are represented by the string "NaN", optionally followed by parentheses which may contain a string of digits (the NaN code). Case is ignored in the infinity and NaN strings.

**s** A character string is expected; the corresponding argument should be a character pointer to an array of characters large enough to accept the string; a terminating null character (0) is added automatically. The input field is terminated by a white-space (blank or tab) character.

**c** A character is expected; the corresponding argument should be a character pointer. The normal skip over white space is suppressed in this case; to read the next non-white-space character, use "%1s". If a field width is given, the corresponding argument should refer to a character array; the indicated number of characters is read.

**[** The left bracket introduces a scanset format. The input field is the maximal sequence of input characters consisting entirely of characters in

the scanset. When reading the input field, string data and the normal skip over leading white space are suppressed. The corresponding pointer argument must point to a character array large enough to hold the input field and the terminating null character (\0), which will be added automatically. The left bracket is followed by a set of characters (the scanset) and a terminating right bracket.

*The circumflex (^), when it appears as the first character in the scanset, serves as a complement operator and redefines the scanset as the set of all characters not contained in the remainder of the scanset string.*

*The right bracket (]) ends the scanset. To include the right bracket as an element of the scanset, it must appear as the first character (possibly preceded by a circumflex) of the scanset; otherwise it will be interpreted syntactically as the closing bracket.*

A range of characters may be represented by the construct *first-last*; thus the scanset [0123456789] may be expressed [0-9]. To use this convention, *first* must be less than or equal to *last* in the ASCII collating sequence; otherwise the minus (-) will stand for itself in the scanset. The minus will also stand for itself whenever it is the first or the last character in the scanset.

*Scanf* conversion terminates at EOF, at the end of the control string, or when an input character doesn't match the control string. In the latter case, the unmatched character is left unread in the input stream.

*Scanf* returns the number of successfully matched and assigned input items; this number can be zero when an early mismatch between an input character and the control string occurs. If the input ends before the first mismatch or conversion, EOF is returned.

#### EXAMPLES

Example 1. The call

```
int i; float x; char name[50];
scanf("%d%f%s", &i, &x, name);
```

with input

```
25 54.32E-1 hartwell
```

will assign the value 25 to *i*, and the value 5.432 to *x*; *name* will contain "hartwell\0".

Example 2. The call

```
int i; extended x; char name[50];
scanf("%2d%nf%d %[0-9]", &i, &x, name);
```

## SCANF

## Standard C Library

## SCANF

with input

```
56789 0123 56a72
```

will assign 56 to *i*, 789.0 to *x*, skip 0123, and place the string "560" in *name*. The next call to `getchar()` will return "a".

Example 3. The call

```
int i;  
scanf("answer1=%d", &i);
```

with input

```
answer1=51 answer2=45
```

will assign the value 51 to *i* since "answer1" is matched explicitly in the input stream; the input pointer will be left at the space before "answer2".

## DIAGNOSTICS

These functions return EOF on end of input and a short count for missing or illegal data items.

## NOTE

Trailing white space is left unread unless matched in the control string.

The success of literal matches and suppressed assignments is not directly determinable.

## SEE ALSO

`atof()`, `dec2num()`, `getc()`,  
*Apple Numerics Manual*.



## SETBUF

## Standard C Library

## SETBUF

## NAME

`setbuf`—assign buffering to a stream

## SYNOPSIS

```
#include <stdio.h>

void setbuf (stream, buf)
FILE *stream;
char *buf;
```

## DESCRIPTION

*Setbuf* is used after a stream has been opened but before it is read or written. *Setbuf* causes the character array pointed to by *buf* to be used instead of an automatically allocated buffer. If *buf* is a null character pointer, input/output will be completely unbuffered.

`BUFSIZ`, a constant defined in the `<stdio.h>` header file, indicates how big an array is needed:

```
char buf[BUFSIZ];
```

A buffer is normally obtained from `malloc()` at the time of the first `getc()` or `putc()` on the file, except that the standard error stream *stderr* is normally not buffered.

Output streams directed to windows are either line-buffered or unbuffered.

## NOTE

A common error is to allocate buffer space as an "automatic" variable in a code block and then fail to close the stream in the same block.

## SEE ALSO

`fopen()`, `getc()`, `malloc()`, `putc()`.

SINH

Standard C Math Library

SINH

## NAME

`sinh`, `cosh`, `tanh`—hyperbolic functions

## SYNOPSIS

```
#include <math.h>
```

```
extended sinh (x)  
extended x;
```

```
extended cosh (x)  
extended x;
```

```
extended tanh (x)  
extended x;
```

## DESCRIPTION

*Sinh*, *cosh*, and *tanh* return, respectively, the hyperbolic sine, cosine, and tangent of their argument.

## DIAGNOSTICS

*Sinh*, *cosh*, and *tanh* honor the floating-point exception flags—invalid operation, underflow, overflow, divide by zero, and inexact—as prescribed by the Standard Apple Numeric Environment (SANE).

## SEE ALSO

*Apple Numerics Manual*.

## STDIO

## Standard C Library

## STDIO

## NAME

`stdio`—standard buffered input/output package

## SYNOPSIS

```
#include <stdio.h>
```

```
FILE *stdin, *stdout, *stderr;
```

## DESCRIPTION

The standard I/O package constitutes an efficient user-level I/O buffering scheme. The inline macros `getc()` and `putc()` handle characters quickly. The macros `getchar()` and `putchar()`, and the higher-level routines `fgetc()`, `fgets()`, `fprintf()`, `fputc()`, `fputs()`, `fread()`, `fscanf()`, `fwrite()`, `gets()`, `getw()`, `printf()`, `puts()`, `putw()`, and `scanf()` all use `getc()` and `putc()`; they can be freely intermixed.

Any program that uses the standard I/O package must include the header file of pertinent macro definitions. The functions and constants mentioned in the standard I/O package are declared in the header file and need no further declaration. The header file is included as follows:

```
#include <stdio.h>
```

A file with associated buffering is called a *stream* and is declared to be a pointer to a defined type `FILE`. `Fopen()` creates certain descriptive data for a stream and returns a pointer to designate the stream in all further transactions. Normally, there are three open streams with constant pointers declared in the `<stdio.h>` header file and associated with the standard open files:

<code>stdin</code>	(standard input file)
<code>stdout</code>	(standard output file)
<code>stderr</code>	(standard error file)

A constant `NULL` (0) designates a nonexistent pointer.

An integer constant `EOF` (−1) is returned upon end-of-file or error by most integer functions that deal with streams. See the descriptions of the individual functions for details.

The constants and the following functions are implemented as macros: `getc()`, `getchar()`, `putc()`, `putchar()`, `feof()`, `ferror()`, `clearerr()`, and `fileno()`. Redefinition of these names should be avoided.

## NOTE

`<Stdio.h>` includes definitions other than those described above, but their use is not recommended.

## DIAGNOSTICS

Invalid stream pointers cause serious errors, possibly including program termination. Individual function descriptions describe the possible error conditions.

**STDIO**

**Standard C Library**

**STDIO**

**SEE ALSO**

`open()`, `close()`, `lseek()`, `read()`, `write()`, `fclose()`, `ferror()`,  
`fopen()`, `fread()`, `fseek()`, `getc()`, `gets()`, `printf()`, `putc()`,  
`puts()`, `scanf()`, `setbuf()`, `ungetc()`.

## STRING

## Standard C Library

## STRING

## NAME

*strcat*, *strncat*, *strcmp*, *strncmp*, *strcpy*, *strncpy*, *strlen*, *strchr*, *strrchr*  
—string operations

## SYNOPSIS

```
char *strcat (s1, s2)
char *s1, *s2;

char *strncat (s1, s2, n)
char *s1, *s2;
int n;

int strcmp (s1, s2)
char *s1, *s2;

int strncmp (s1, s2, n)
char *s1, *s2;
int n;

char *strcpy (s1, s2)
char *s1, *s2;

char *strncpy (s1, s2, n)
char *s1, *s2;
int n;

int strlen (s)
char *s;

char *strchr (s, c)
char *s, c;

char *strrchr (s, c)
char *s, c;
```

## DESCRIPTION

The arguments *s1*, *s2*, and *s* point to strings (arrays of characters terminated by a null character). The functions *strcat*, *strncat*, *strcpy*, and *strncpy* all alter *s1*. These functions do not check for overflow of the array pointed to by *s1*.

*Strcat* appends a copy of string *s2* to the end of string *s1*. *Strncat* appends at most *n* characters. Each function returns a pointer to the null-terminated result.

*Strcmp* performs a comparison of its arguments according to the ASCII collating sequence and returns an integer less than, equal to, or greater than 0 when *s1* is less than, equal to, or greater than *s2*, respectively. *Strncmp* makes the same comparison but looks at a maximum of *n* characters.

*Strcpy* copies string *s2* to string *s1*, stopping after the null character has been copied. *Strncpy* copies exactly *n* characters, truncating *s2* or adding null characters to *s1* if necessary. The result is not null-terminated if the length of *s2* is *n* or more. Each function returns *s1*.

*Strlen* returns the number of characters in *s*, not including the terminating null character.

STRING

Standard C Library

STRING

*Strchr* (*strrchr*) returns a pointer to the first (last) occurrence of character *c* in string *s*; it returns a null pointer if *c* does not occur in the string. The null character terminating a string is considered to be part of the string. In previous versions of the Standard C Library, *strchr* was known as *index()* and *strrchr* was known as *rindex()*.

WARNING

Overlapping moves may yield unexpected results

## TRIG

## Standard C Math Library

## TRIG

## NAME

*sin*, *cos*, *tan*, *asin*, *acos*, *atan*, *atan2*  
—trigonometric functions

## SYNOPSIS

```
#include <math.h>

extended sin (x)
extended x;

extended cos (x)
extended x;

extended tan (x)
extended x;

extended asin (x)
extended x;

extended acos (x)
extended x;

extended atan (x)
extended x;

extended atan2 (y, x)
extended x, y;
```

## DESCRIPTION

*Sin*, *cos*, and *tan* return, respectively, the sine, cosine, and tangent of their argument, which is in radians.

*Asin* returns the arcsine of  $x$ , in the range  $-\pi/2$  to  $\pi/2$ .

*Acos* returns the arccosine of  $x$ , in the range 0 to  $\pi$ .

*Atan* returns the arctangent of  $x$ , in the range  $-\pi/2$  to  $\pi/2$ .

*Atan2* returns the arctangent of  $y/x$ , in the range  $-\pi$  to  $\pi$ , using the signs of both arguments to determine the quadrant of the return value.

For special cases, these functions return a NaN or infinity as appropriate.

## DIAGNOSTICS

These functions honor the floating-point exception flags—invalid operation, underflow, overflow, divide by zero, and inexact—as prescribed by the Standard Apple Numeric Environment (SANE).

## NOTE

*Sin*, *cos*, and *tan* have periods based on the nearest extended-precision representation of mathematical  $\pi$ . Hence these functions diverge from their mathematical counterparts as their argument becomes far from zero.

## SEE ALSO

*Apple Numerics Manual*.





## UNGETC

## Standard C Library

## UNGETC

## NAME

`ungetc`—push character back into input stream

## SYNOPSIS

```
#include <stdio.h>

int ungetc (c, stream)
char c;
FILE *stream;
```

## DESCRIPTION

*Ungetc* inserts the character *c* into the buffer associated with an input stream. That character, *c*, will be returned by the next `getc()` call on that stream. *Ungetc* returns *c* and leaves the file stream unchanged.

One character of pushback is guaranteed provided something has been read from the stream and the stream is actually buffered.

If *c* equals EOF, *ungetc* does nothing to the buffer and returns EOF.

`fseek()` erases all memory of inserted characters.

## DIAGNOSTICS

For *ungetc* to perform correctly, a read must have been performed prior to the call of the *ungetc* function. *Ungetc* returns EOF if it can't insert the character. If *stream* is *stdin*, *ungetc* allows exactly one character to be pushed back onto the buffer without a previous read statement.

## SEE ALSO

`fseek()`, `getc()`, `setbuf()`.

**UNLINK**

**Standard C Library**

**UNLINK**

**NAME**  
unlink—remove a file

**SYNOPSIS**  
int unlink (path)  
char \*path;

**DESCRIPTION**  
*Unlink* deletes the file named by the pathname pointed to by *path*.

**RETURN VALUE**  
Upon successful completion, a value of 0 is returned. Otherwise, a value of -1 is returned and *errno* is set to indicate the error.

## WRITE

## Standard C Library

## WRITE

## NAME

`write`—write on a file

## SYNOPSIS

```
int write (fildes, buf, nbyte)
int fildes;
char *buf;
unsigned nbyte;
```

## DESCRIPTION

*Fildes* is a file descriptor obtained from a `creat()` or `open()` call.

*Write* attempts to write *nbyte* bytes from the buffer pointed to by *buf* to the file associated with the *fildes*. Internal limitations may cause *write* to write fewer bytes than requested; the number of bytes actually written is indicated by the return value. Several calls to *write* may therefore be necessary to write out the contents of *buf*.

On devices capable of seeking, the actual writing of data proceeds from the position in the file indicated by the file pointer. Upon return from *write*, the file pointer is incremented by the number of bytes actually written.

On nonseeking devices, writing always starts at the current position. The value of a file pointer associated with such a device is undefined.

If the `O_APPEND` file status flag is set—see `open()`—the file pointer is set to end-of-file prior to each write.

*Write* fails and the file pointer remains unchanged if *fildes* is not a valid file descriptor open for writing. [EBADF]

If you try to write more bytes than there is room for on the device, *write* writes as many bytes as possible. For example, if *nbyte* is 512 and there is room for 20 bytes more on the device, *write* writes 20 bytes and returns a value of 20. The next attempt to write a nonzero number of bytes will signal an error. [ENOSPC]

## RETURN VALUE

Upon successful completion the number of bytes actually written is returned. Otherwise, `-1` is returned and *errno* is set to indicate the error.

## SEE ALSO

`creat()`, `lseek()`, `open()`.

## Lisa Workshop C User's Guide

### 7. Macintosh Interface Libraries

This section contains the C definition of the Macintosh Interface Libraries. For complete documentation of these libraries, see *Inside Macintosh*.

This section is arranged alphabetically by library name. The Library Index, Section 8, indexes the defines, types, enumeration literals, global variables, and functions defined here and in the Standard C Library.

## Interface

## Macintosh Interface Libraries

## Interface

## NAME

C interface to the Macintosh libraries

## SYNOPSIS

```
#include <types.h>           /* common defines and types */
#include <strings.h>         /* string conversions */
#include <resources.h>       /* Resource Manager */
#include <quickdraw.h>      /* QuickDraw */
#include <fonts.h>           /* Font Manager */
#include <events.h>         /* Event Manager */
#include <windows.h>        /* Window Manager */
#include <controls.h>       /* Control Manager */
#include <menus.h>          /* Menu Manager */
#include <textedit.h>        /* TextEdit */
#include <dialogs.h>        /* Dialog Manager */
#include <desk.h>           /* Desk Manager */
#include <scrap.h>          /* Scrap Manager */
#include <toolutils.h>      /* Toolbox Utilities */
#include <printing.h>       /* Printing Manager */
#include <osutils.h>        /* Operating System Utilities */
#include <memory.h>         /* Memory Manager */
#include <segload.h>        /* Segment Loader */
#include <osevents.h>       /* OS Event Manager */
#include <files.h>          /* File Manager */
#include <devices.h>        /* Device Manager */
#include <disks.h>          /* Disk Driver */
#include <sound.h>          /* Sound Driver */
#include <retrace.h>        /* Vertical Retrace Manager */
#include <serial.h>         /* Serial Drivers */
#include <packages.h>       /* packages */
#include <error.h>          /* System Error Handler */
#include <sane.h>           /* SANE Numerics */
```

## DESCRIPTION

The C Interface provides C programs with access to all of the libraries defined in *Inside Macintosh*. Constants, types, and library routines are provided. The list of libraries appears above.

**Header Files**—Include the ".h" files in C programs to declare the defines, types, and functions provided by these libraries. Each library definition lists the includes necessary for use of that library. Functions whose declarations can be inferred from calls have been omitted from the header files. List the includes in the order in which the libraries are listed above.

**Object File**—The interface code is contained in file `interface.obj`. Link this file with the C program and other libraries. Not all functions require interface code. The linker includes interface code for only those routines that are called.

**Interface Implementation**—Most library routines are declared as external Pascal routines with trap numbers, and are trapped to directly by compiled code. Other routines are declared to be C routines and are called through interface glue.

**Parameter Types**—The C interfaces expect structures (including Points) to be passed by address. String parameters are C strings (i.e., zero-terminated) unless

otherwise indicated. ResTypes and OSTypes can be expressed as character literals (e.g., 'MENU').

**Spelling and Capitalization**—The spelling and capitalization of identifiers is exactly as specified in *Inside Macintosh*. Constants, variables, parameter names, fields within structures, and enumeration-type elements begin with a lowercase letter. Routines and data types begin with an uppercase letter. Letters that begin new words in English are capitalized. All other letters are lowercase. When a name includes an acronym, the case of the entire acronym is determined by the case of the first letter (e.g., GetOSEvent, teJustLeft).

## CONTROLS

## Macintosh Interface Libraries

## CONTROLS

## NAME

controls—Control Manager

## SYNOPSIS

```

#include <types.h>
#include <controls.h>

/* Control Definition Procedures IDs */

#define pushButProc      0
#define checkBoxProc    1
#define radioButProc    2
#define useWFont        8
#define scrollBarProc    16

/* FindControl Result Codes */

#define inButton         10
#define inCheckbox      11
#define inUpButton      20
#define inDownButton    21
#define inPageUp        22
#define inPageDown      23
#define inThumb         129

/* DragControl Axis Constraints */

#define noConstraint     0
#define hAxisOnly       1
#define vAxisOnly       2

/* Messages to Control definition function */

#define drawCntl        0
#define testCntl        1
#define calcCRgns      2
#define initCntl        3
#define dispCntl        4
#define posCntl         5
#define thumbCntl       6
#define dragCntl        7
#define autoTrack       8

typedef struct ControlRecord {
    struct ControlRecord **nextControl;
    struct GrafPort *contrlOwner;
    Rect                contrlRect;
    unsigned char       contrlVis;
    unsigned char       contrlHilite;
    short               contrlValue;
    short               contrlMin;
    short               contrlMax;
    ProcHandle          contrlDefProc;
    Handle              contrlData;
    ProcPtr             contrlAction;
}

```

## CONTROLS

## Macintosh Interface Libraries

## CONTROLS

```

    long          contrlrfCon;
    Str255        contrlTitle;
} ControlRecord, *ControlPtr, **ControlHandle;

/* Initialization and Allocation */

ControlHandle NewControl(theWindow, boundsRect, title, visible, value,
    min, max, procID, refCon)
    struct GrafPort *theWindow;
    Rect *boundsRect;
    char *title;
    Boolean visible;
    short value;
    short min;
    short max;
    short procID;
    long refCon;
pascal ControlHandle GetNewControl(controlID, theWindow)
    short controlID;
    struct GrafPort *theWindow;
pascal void DisposeControl(theControl)
    ControlHandle theControl;
pascal void KillControls(theWindow)
    struct GrafPort *theWindow;

/* Control Display */

void SetCTitle(theControl, title)
    ControlHandle theControl;
    char *title;
void GetCTitle(theControl, title)
    ControlHandle theControl;
    char *title;
pascal void HideControl(theControl)
    ControlHandle theControl;
pascal void ShowControl(theControl)
    ControlHandle theControl;
pascal void DrawControls(theWindow)
    struct GrafPort *theWindow;
pascal void HiliteControl(theControl, hiliteState)
    ControlHandle theControl;
    short hiliteState;

/* Mouse Location */

short TestControl(theControl, thePoint)
    ControlHandle theControl;
    Point *thePoint;
short FindControl(thePoint, theWindow, theControl)
    Point *thePoint;
    struct GrafPort *theWindow;
    ControlHandle *theControl;
short TrackControl(theControl, startPt, actionProc)
    ControlHandle theControl;
    Point *startPt;
    ProcPtr actionProc;

```



## CONTROLS

## Macintosh Interface Libraries

## CONTROLS

```

/* Control Movement and Sizing */

pascal void MoveControl(theControl,h,v)
    ControlHandle theControl;
    short h,v;
void DragControl(theControl,startPt,limitRect,slopRect,axis)
    ControlHandle theControl;
    Point *startPt;
    Rect *limitRect;
    Rect *slopRect;
    short axis;
pascal void SizeControl(theControl,w,h)
    ControlHandle theControl;
    short w,h;

/* Control Settings and Range */

pascal void SetCtlValue(theControl,theValue)
    ControlHandle theControl;
    short theValue;
pascal short GetCtlValue(theControl)
    ControlHandle theControl;
pascal void SetCtlMin(theControl,minValue)
    ControlHandle theControl;
    short minValue;
pascal short GetCtlMin(theControl)
    ControlHandle theControl;
pascal void SetCtlMax(theControl,maxValue)
    ControlHandle theControl;
    short maxValue;
pascal short GetCtlMax(theControl)
    ControlHandle theControl;

/* Miscellaneous Utilities */

pascal void SetCRefCon(theControl,data)
    ControlHandle theControl;
    long data;
pascal long GetCRefCon(theControl)
    ControlHandle theControl;
pascal void SetCtlAction(theControl,actionProc)
    ControlHandle theControl;
    ProcPtr actionProc;
pascal ProcPtr GetCtlAction(theControl)
    ControlHandle theControl;

```

## USER ROUTINES

```

pascal void MyAction()
pascal void MyAction(theControl,partCode)
    ControlHandle theControl;
    short partCode;

pascal long MyControl(varCode,theControl,message,param)
    short varCode;
    ControlHandle theControl;

```

**CONTROLS**

**Macintosh Interface Libraries**

**CONTROLS**

short message;  
long param;

**DESCRIPTION**

The Control Manager provides routines for creating and manipulating controls (e.g., buttons, scroll bars).

For more detailed information see the Control Manager chapter of *Inside Macintosh*.

DESK

Macintosh Interface Libraries

DESK

## NAME

desk—Desk Manager

## SYNOPSIS

```
#include <types.h>
#include <desk.h>

/* Opening and Closing Desk Accessories */

short OpenDeskAcc(theAcc)
    char *theAcc;
pascal void CloseDeskAcc(refNum)
    short refNum;

/* Handling Events in Desk Accessories */

pascal void SystemClick(theEvent,theWindow)
    struct EventRecord *theEvent;
    struct GrafPort *theWindow;
pascal Boolean SystemEdit(editCmd)
    short editCmd;

/* Performing Periodic Actions */

pascal void SystemTask()

/* Advanced Routines */

pascal Boolean SystemEvent(theEvent)
    struct EventRecord *theEvent;
pascal void SystemMenu(menuResult)
    long menuResult;
```

## DESCRIPTION

The Desk Manager supports desk accessories.

**Warning:** The names of desk accessories start with a null byte. The output parameter from `GetMenuItem` will return a string that begins with a null byte when a desk accessory is selected from the Apple menu. `OpenDeskAcc` skips over this null byte when interpreting its parameter

For more detailed information see the Desk Manager chapter of *Inside Macintosh*.

## NOTE

Desk accessories do not have an A5 global area. Therefore all of the code for a desk accessory must reside in a single segment; no global variables may be declared; and no string constants may be used.

## DEVICES

## Macintosh Interface Libraries

## DEVICES

## NAME

devices—Device Manager

## SYNOPSIS

```

#include <types.h>
#include <osutils.h>
#include <devices.h>

/* error codes */

#define abortErr      (-27) /* I/O request aborted by KillIO */
#define badUnitErr   (-21) /* RefNum doesn't match unit table */
#define controlErr   (-17) /* Driver can't respond to this call */
#define dInstErr     (-26) /* Couldn't find driver in resource file */
#define dRemoveErr   (-25) /* Tried to remove an open driver */
#define noErr        0     /* No error */
#define notOpenErr   (-28) /* Driver isn't open */
#define openErr      (-23) /* Requested r/w permission doesn't */
                          /* match driver's open permission */
#define readErr      (-19) /* Driver can't respond to Read calls */
#define statusErr    (-18) /* Driver can't respond to Status call */
#define unitEmptyErr (-22) /* Reference number specifies nil handle */
                          /* in unit table */
#define writErr      (-20) /* Driver can't respond to Write calls */

typedef struct CntrlParam {
    struct QElem *qLink; /* next queue entry */
    short qType; /* queue type */
    short ioTrap; /* routine trap */
    Ptr ioCmdAddr; /* routine address */
    ProcPtr ioCompletion; /* completion routine */
    OSErr ioResult; /* result code */
    char *ioNamePtr; /* volume or file name */
    short ioVRefNum; /* volume refnum or drive number */
    short ioCRefNum; /* refnum for I/O operations */
    short csCode; /* word for control status code */
    short csParam[11]; /* operation-defined parameters */
} CntrlParam;

typedef struct DctlEntry {
    Ptr dctlDriver; /* ptr to ROM or handle to RAM driver */
    short dctlFlags; /* flags */
    QHdr dctlQHdr; /* driver's I/O queue */
    long dctlPosition; /* byte pos used by read and write */
    Handle dctlStorage; /* handle to RAM driver's storage */
    short dctlRefNum; /* driver's reference number */
    long dctlCurTicks; /* counter for timing system task calls */
    Ptr dctlWindow; /* ptr to driver's window (if any) */
    short dctlDelay; /* # of ticks between sysTask calls */
    short dctlEMask; /* desk accessory event mask */
    short dctlMenu; /* menu ID of menu associated w/ driver */
} DctlEntry, *DctlPtr, **DctlHandle;

```

## DEVICES

## Macintosh Interface Libraries

## DEVICES

```

/* High-Level Routines */

OSErr OpenDriver(name, refNum)
    char *name;
    short *refNum;
OSErr CloseDriver(refNum)
    short refNum;
OSErr Control(refNum, csCode, csParam)
    short refNum, csCode;
    Ptr csParam;
OSErr Status(refNum, csCode, csParam)
    short refNum, csCode;
    Ptr csParam;
OSErr KillIO(refNum)
    short refNum;

/* Low-Level Routines */

OSErr PBControl(paramBlock, async)
    CntrlParam *paramBlock;
    Boolean async;
OSErr PBStatus(paramBlock, async)
    CntrlParam *paramBlock;
    Boolean async;
OSErr PBKillIO(paramBlock, async)
    CntrlParam *paramBlock;
    Boolean async;

/* Accessing a Driver's I/O Queue */

DCtlHandle, GetDCtlEntry(refNum)
    short refNum;

```

## DESCRIPTION

The Device Manager controls the exchange of information between an application and devices.

For more detailed information see the Device Manager chapter of *Inside Macintosh*.

## DIALOGS

## Macintosh Interface Libraries

## DIALOGS

## NAME

dialogs—Dialog Manager

## SYNOPSIS

```

#include <types.h>
#include <quickdraw.h>
#include <windows.h>
#include <dialogs.h>

/* Item types */

#define ctrlItem      4      /* add to following four constants */
#define btnCtrl      0      /* standard button control */
#define chkCtrl      1      /* standard check box control */
#define radCtrl      2      /* standard "radio button" control */
#define resCtrl      3      /* control defined in control template */
#define statText     8      /* static text */
#define editText    16      /* editable text (dialog only) */
#define iconItem     32      /* icon */
#define picItem      64      /* Quickdraw picture */
#define userItem     0      /* application-defined item (dialog only) */
#define itemDisable 128     /* add to any of above to disable */

/* Item numbers of OK and Cancel buttons */

#define ok           1      /* OK button is first by convention */
#define cancel      2      /* Cancel button is second by convention */

/* Resource IDs of Alert icons */

#define stopIcon    0
#define noteIcon    1
#define ctnIcon     2

typedef WindowPtr DialogPtr;
typedef struct DialogRecord {
    WindowRecord window;
    Handle items;
    struct TERec **textH;
    short editField;
    short editOpen;
    short aDefItem;
} DialogRecord, *DialogPeek;

typedef struct DialogTemplate {
    Rect boundsRect;
    short procID;
    Boolean visible;
    Boolean filler1;
    Boolean goAwayFlag;
    Boolean filler2;
    long refCon;
    short itemsID;
    Str255 title;
} DialogTemplate, *DialogTPtr, **DialogTHndl;

```

## DIALOGS

## Macintosh Interface Libraries

## DIALOGS

```

typedef long StageList;

typedef struct AlertTemplate {
    Rect    boundsRect;
    short   itemsID;
    StageList stages;
} AlertTemplate, *AlertTPtr, **AlertTHndl;

/* Initialization */

pascal void InitDialogs(restartProc)
    ProcPtr restartProc;
pascal void ErrorSound(soundProc)
    ProcPtr soundProc;
void SetDAFont(fontNum)
    short fontNum;

/* Creating and Disposing of Dialogs */

DialogPtr NewDialog(dStorage,boundsRect,title,visible,procID,behind,
    goAwayFlag,refCon,items);
    Ptr dStorage;
    Rect *boundsRect;
    char *title;
    Boolean visible;
    short procID;
    WindowPtr behind;
    Boolean goAwayFlag;
    long refCon;
    Handle items;
pascal DialogPtr GetNewDialog(dialogID,dStorage,behind)
    short dialogID;
    Ptr dStorage;
    WindowPtr behind;
pascal void CloseDialog(theDialog)
    DialogPtr theDialog;
pascal void DisposDialog(theDialog)
    DialogPtr theDialog;
pascal void CouldDialog(dialogID)
    short dialogID;
pascal void FreeDialog(dialogID)
    short dialogID;

/* Handling Dialog Events */

pascal void ModalDialog(filterProc,itemHit)
    ProcPtr filterProc;
    short *itemHit;
pascal Boolean IsDialogEvent(theEvent)
    struct EventRecord *theEvent;
pascal Boolean DialogSelect(theEvent,theDialog,itemHit)
    struct EventRecord *theEvent;
    DialogPtr *theDialog;
    short *itemHit;
void DlgCut(theDialog)

```

## DIALOGS

## Macintosh Interface Libraries

## DIALOGS

```

    DialogPtr theDialog;
void DlgCopy(theDialog)
    DialogPtr theDialog;
void DlgPaste(theDialog)
    DialogPtr theDialog;
void DlgDelete(theDialog)
    DialogPtr theDialog;
pascal void DrawDialog(theDialog)
    DialogPtr theDialog;

/* Invoking Alerts */

pascal short Alert(alertID,filterProc)
    short alertID;
    ProcPtr filterProc;
pascal short StopAlert(alertID,filterProc)
    short alertID;
    ProcPtr filterProc;
pascal short NoteAlert(alertID,filterProc)
    short alertID;
    ProcPtr filterProc;
pascal short CautionAlert(alertID,filterProc)
    short alertID;
    ProcPtr filterProc;
pascal void CouldAlert(alertID)
    short alertID;
pascal void FreeAlert(alertID)
    short alertID;

/* Manipulating Items in Dialogs and Alerts */

void ParamText(param0,param1,param2,param3)
    char *param0;
    char *param1;
    char *param2;
    char *param3;
pascal void GetDItem(theDialog,itemNo,type,item,box)
    DialogPtr theDialog;
    short itemNo;
    short *type;
    Handle *item;
    Rect *box;
pascal void SetDItem(theDialog,itemNo,type,item,box)
    DialogPtr theDialog;
    short itemNo;
    short type;
    Handle item;
    Rect *box;
void GetIText(item,text)
    Handle item;
    char *text;
void SetIText(item,text)
    Handle item;
    char *text;
pascal void SelIText(theDialog,itemNo,startSel,endSel)
    DialogPtr theDialog;
    short itemNo;

```



## DIALOGS

## Macintosh Interface Libraries

## DIALOGS

```
    short startSel;  
    short endSel;  
short GetAlrtStage()  
void ResetAlrtStage()
```

## USER ROUTINES

```
pascal void MyItem(theWindow,itemNo)  
    struct GrafPort *theWindow;  
    short itemNo;  
pascal void MySound(soundNo)  
    short soundNo;  
pascal Boolean MyFilter(theDialog,theEvent,itemHit)  
    DialogPtr theDialog;  
    struct EventRecord *theEvent;  
    short *itemHit;
```

## DESCRIPTION

The Dialog Manager supports dialog boxes and the alert mechanism.

For more detailed information see the Dialog Manager chapter of *Inside Macintosh*.

## NOTE

StageList is defined as a long, rather than specifying the bits.

## DISKS

## Macintosh Interface Libraries

## DISKS

## NAME

disks—Disk Driver

## SYNOPSIS

```

#include <types.h>
#include <disks.h>

/* error codes */

#define firstDskErr (-84) /* First of the range of disk errors */
#define lastDskErr (-64) /* Last of the range of disk errors */

#define badBtSlpErr (-70) /* Bad address mark */
#define badCksmErr (-69) /* Bad address mark */
#define badDBtSlp (-73) /* Bad data mark */
#define badDCksum (-72) /* Bad data mark */
#define cantStepErr (-75) /* Hardware error */
#define dataVerErr (-68) /* Read-verify failed */
#define initIWMErr (-77) /* Hardware error */
#define noAdmKErr (-67) /* Can't find an address mark */
#define noDriveErr (-64) /* Drive isn't connected */
#define noDtaMkErr (-71) /* Can't find data mark */
#define noErr 0 /* No error */
#define noNybErr (-66) /* Disk is probably blank */
#define nsDrvErr (-56) /* No such drive */
#define offLinErr (-65) /* No disk in drive */
#define paramErr (-50) /* Bad positioning information */
#define sectNFErr (-81) /* Can't find sector */
#define seekErr (-80) /* Hardware error */
#define spdAdjErr (-79) /* Hardware error */
#define tk0BadErr (-76) /* Hardware error */
#define twoSideErr (-78) /* Tried to read side 2, or 1 side drive */
#define wPrErr (-44) /* Disk is locked */
#define wrUnderrun (-74) /* write underrun occurred */

typedef struct DrvSts {
    short track; /* current track */
    char writeProt; /* bit 7=1 if volume is locked */
    char diskInPlace; /* disk in place */
    char installed; /* drive installed */
    char sides; /* bit 7=0 if single-sided drive */
    struct QElem *qLink; /* next queue entry */
    short qType; /* not used */
    short dQDrive; /* drive number */
    short dQRefNum; /* driver reference number */
    short dQFSID; /* file-system identifier */
    char twoSideFmt; /* -1 if two-sided disk */
    char needsFlush; /* reserved */
    short diskErrs; /* error count */
} DrvSts;

OSErr DiskEject(drvNum)
    short drvNum;
OSErr SetTagBuffer(buffPtr)
    Ptr buffPtr;

```

**DISKS**

**Macintosh Interface Libraries**

**DISKS**

```
OSErr DriveStatus (drvNum, status)
    short drvNum;
    DrvSts *status;
```

**DESCRIPTION**

The Disk Driver is a Macintosh device driver used for storing and retrieving information on Macintosh 3 1/2-inch disk drives.

For more detailed information see the Disk Driver chapter of *Inside Macintosh*.

ERROR

Macintosh Interface Libraries

ERROR

NAME

error—System Error Handler

SYNOPSIS

```
#include <error.h>

/* error codes */

#define dsBusErr 1 /* Bus Error */
#define dsAddressErr 2 /* Address Error */
#define dsIllInstErr 3 /* Illegal Instruction */
#define dsZeroDivErr 4 /* Zero Divide */
#define dsChkErr 5 /* Check Exception */
#define dsOverflowErr 6 /* TrapV Exception */
#define dsPrivErr 7 /* Privilege Violation */
#define dsTraceErr 8 /* Trace Exception */
#define dsLineAErr 9 /* Line 1010 Exception */
#define dsLineFErr 10 /* Line 1111 Exception */
#define dsMiscErr 11 /* Miscellaneous Exception */
#define dsCoreErr 12 /* Unimplemented Core Routine */
#define dsIrqErr 13 /* Spurious Interrupt */
#define dsIOCoreErr 14 /* I/O System Error */
#define dsLoadErr 15 /* Segment Loader Error */
#define dsFPERR 16 /* Floating Point Error */
#define dsNoPackErr 17 /* Can't Load Package 0 */
#define dsNoPk1 18 /* Can't Load Package 1 */
#define dsNoPk2 19 /* Can't Load Package 2 */
#define dsNoPk3 20 /* Can't Load Package 3 */
#define dsNoPk4 21 /* Can't Load Package 4 */
#define dsNoPk5 22 /* Can't Load Package 5 */
#define dsNoPk6 23 /* Can't Load Package 6 */
#define dsNoPk7 24 /* Can't Load Package 7 */
#define dsMemFullErr 25 /* Out of Memory */
#define dsBadLaunch 26 /* Segment Loader Error */
#define dsFSErr 27 /* File Map Trashed */
#define dsStkNHeap 28 /* Stack Overflow Error */
#define dsReinsert 30 /* Please Insert the Disk */
#define dsNotThe1 31 /* This is Not the Correct Disk */
#define dsSysErr 32767 /* System Error */
```

```
void SysError(errorCode)
    short errorCode;
```

DESCRIPTION

The System Error Handler is the part of the Macintosh Operating System that assumes control when a fatal error occurs. For more detailed information see the System Error Handler chapter of *Inside Macintosh*.

## EVENTS

## Macintosh Interface Libraries

## EVENTS

## NAME

events—Toolbox Event Manager

## SYNOPSIS

```

#include <types.h>
#include <events.h>

/* Event Types */

#define nullEvent      0
#define mouseDown     1
#define mouseUp       2
#define keyDown       3
#define keyUp         4
#define autoKey       5
#define updateEvt     6
#define diskEvt       7
#define activateEvt   8
#define networkEvt    10
#define driverEvt     11
#define app1Evt       12
#define app2Evt       13
#define app3Evt       14
#define app4Evt       15

/* Masks for accessing keyboard event message */

#define charCodeMask  0x000000FF
#define keyCodeMask  0x0000FF00

/* Event Masks */

#define mDownMask     2
#define mUpMask       4
#define keyDownMask   8
#define keyUpMask     16
#define autoKeyMask   32
#define updateMask    64
#define diskMask      128
#define activMask     256
#define networkMask   1024
#define driverMask    2048
#define app1Mask      4096
#define app2Mask      8192
#define app3Mask      16384
#define app4Mask      (-32768)
#define everyEvent    (-1)

/* Modifiers */

#define activeFlag    1
#define btnState      128
#define cmdKey        256
#define shiftKey      512
#define alphaLock     1024
#define optionKey     2048

```

## EVENTS

## Macintosh Interface Libraries

## EVENTS

```

typedef struct EventRecord {
    short what;
    long message;
    long when;
    Point where;
    short modifiers;
} EventRecord;

typedef long KeyMap[4];

/* Accessing Events */

pascal Boolean GetNextEvent(eventMask, theEvent)
    short eventMask;
    EventRecord *theEvent;
pascal Boolean EventAvail(eventMask, theEvent)
    short eventMask;
    EventRecord *theEvent;

/* Reading the Mouse */

pascal void GetMouse(mouseLoc)
    Point *mouseLoc;
pascal Boolean Button()
pascal Boolean StillDown()
pascal Boolean WaitMouseUp()

/* Reading the Keyboard and Keypad */

pascal void GetKeys(theKeys)
    KeyMap *theKeys;

/* Miscellaneous Routines */

pascal long TickCount()
long GetDbtTime()
long GetCaretTime()

```


## DESCRIPTION

The Toolbox Event Manager provides access to the Macintosh keyboard, keypad, and mouse. The keyboard bit map returned by the function `GetKeys()` is organized as shown below. The bits aren't numbered as you might expect. Here is the actual numbering scheme, corresponding to the key code numbers given in the Key Codes figure in the Toolbox Event Manager chapter of *Inside Macintosh*.

EVENTS

Macintosh Interface Libraries

EVENTS



## FILES

## Macintosh Interface Libraries

## FILES

## NAME

files—File Manager

## SYNOPSIS

```

#include <types.h>
#include <files.h>

/* error codes */

#define badMDBErr    (-60)    /* Master directory block is bad, reinit */
#define bdNamErr    (-37)    /* Bad file or volume name (zero length?) */
#define dirFulErr    (-33)    /* File directory full */
#define dskFulErr    (-34)    /* All allocation blocks are full */
#define dupFNerr     (-48)    /* File by that name already exists */
#define eofErr       (-39)    /* Logical EOF reached during read */
#define extFSErr     (-58)    /* External file system; identifier is */
                          /* non-zero or refNum is > 1024 */
#define fBsyErr      (-47)    /* One or more files are open */
#define fLckdErr     (-45)    /* File Locked */
#define fnfErr       (-43)    /* File not found */
#define fnOpnErr     (-38)    /* File not open */
#define fsRnErr      (-59)    /* Problem during rename */
#define ioErr        (-36)    /* Disk I/O error */
#define noErr         0      /* No error */
#define nsDrvErr     (-56)    /* No such drive in the drive queue */
#define noMacDskErr (-57)    /* Volume lacks Mac-format directory */
#define nsvErr       (-35)    /* Specified volume doesn't exist */
#define opWrErr      (-49)    /* Only one writer allowed */
#define paramErr     (-50)    /* Parameter's don't specify an existing */
                          /* volume and there's no default volume */
#define permErr      (-54)    /* Permission doesn't allow writing */
#define posErr       (-40)    /* Attempted to position before start */
#define rfNumErr     (-51)    /* Bad reference number */
#define tmfoErr      (-42)    /* Only 12 files can be open at once */
#define volOffLinErr (-53)    /* Volume not on-line */
#define volOnLinErr (-55)    /* Volume is already mounted and on-line */
#define vLckdErr     (-46)    /* Volume is locked by a software flag */
#define wrPermErr    (-61)    /* Permission does not allow writing */
#define wPrErr       (-44)    /* Volume is locked by a hardware setting */

/* Flags in file information used by the Finder */

#define fHasBundle    8192    /* set if file has a bundle */
#define fInvisible    16384   /* set if file's icon is invisible */
#define fTrash        (-3)    /* file is in trash window */
#define fDesktop      (-2)    /* file in on desktop */
#define fDisk          0      /* file is in disk window */

/* Values for posMode and ioPosMode */

#define fsAtMark      0      /* at current position of mark */
                          /* (posOff or ioPosOffset ignored) */
#define fsFromStart   1      /* offset relative to beginning of file */
#define fsFromLEOF    2      /* offset relative to logical EOF */

```



## FILES

## Macintosh Interface Libraries

## FILES

```

#define fsFromMark      3      /* offset relative to current mark */
#define rdVerify        64     /* added to above for read-verify */

/* Values for requesting read/write access */

#define fsCurPerm      0      /* whatever is currently allowed */
#define fsRdPerm        1      /* request to read only */
#define fsWrPerm        2      /* request to write only */
#define fsRdWrPerm      3      /* request to read and write */

typedef struct FInfo {
    OSType      fdType;        /* the type of the file */
    OSType      fdCreator;     /* file's creator */
    short       fdFlags;       /* flags. hasBundle, invisible, etc. */
    Point       fdLocation;    /* file's location in window */
    short       fdFldr;        /* folder containing file */
} FInfo;

/* Parameter Blocks */

typedef struct IOParam {
    struct QElem *qLink;       /* next queue entry */
    short        qType;        /* queue type */
    short        ioTrap;       /* routine trap */
    Ptr          ioCmdAddr;     /* routine address */
    ProcPtr      ioCompletion;  /* completion routine */
    OSErr        ioResult;     /* result code */
    StringPtr    ioNamePtr;    /* volume of file name */
    short        ioVRefNum;     /* volume refnum or drive number */
    short        ioRefNum;     /* path reference number */
    char         ioVersNum;     /* version number */
    char         ioPermssn;     /* read/write permission */
    Ptr          ioMisc;       /* miscellaneous (Note: use high byte
                               /*   for PBSetFVers) */
    Ptr          ioBuffer;     /* data buffer */
    long         ioReqCount;    /* requested number of bytes */
    long         ioActCount;    /* actual byte count completed */
    short        ioPosMode;     /* newline char and type of positioning */
    long         ioPosOffset;   /* size of positioning offset */
} IOParam;

typedef struct FileParam {
    struct QElem *qLink;       /* next queue entry */
    short        qType;        /* queue type */
    short        ioTrap;       /* routine trap */
    Ptr          ioCmdAddr;     /* routine address */
    ProcPtr      ioCompletion;  /* completion routine */
    OSErr        ioResult;     /* result code */
    StringPtr    ioNamePtr;    /* volume of file name */
    short        ioVRefNum;     /* volume refnum or drive number */
    short        ioFRefNum;     /* path reference number */
    char         ioFVersNum;    /* version number */
    char         filler1;       /* not used */
}

```

## FILES

## Macintosh Interface Libraries

## FILES

```

short    ioFDirIndex;    /* sequence number of file */
char     ioFlAttrib;     /* file attributes */
char     ioFlVersNum;    /* version number */
FInfo    ioFlFndrInfo;   /* information used by the Finder */
long     ioFlNum;        /* file number */
short    ioFlStBlk;      /* first block of data fork */
long     ioFlLgLen;      /* logical EOF of data fork */
long     ioFlPyLen;      /* physical EOF of data fork */
short    ioFlRStBlk;     /* first block of resource fork */
long     ioFlRLgLen;     /* logical EOF of resource fork */
long     ioFlRPyLen;     /* physical EOF of resource fork */
long     ioFlCrDat;      /* date and time of creation */
long     ioFlMdDat;      /* date and time of last modification */
} FileParam;

typedef struct VolumeParam {
    struct QElem *qLink;    /* next queue entry */
    short    qType;        /* queue type */
    short    ioTrap;       /* routine trap */
    Ptr      ioCmdAddr;    /* routine address */
    ProcPtr  ioCompletion; /* completion routine */
    OSErr    ioResult;     /* result code */
    StringPtr ioNamePtr;   /* volume of file name */
    short    ioVRefNum;    /* volume refnum or drive number */
    long     filler2;      /* not used */
    short    ioVolIndex;   /* volume index */
    long     ioVCrDate;    /* date and time of initialization */
    long     ioVLSBkUp;    /* date and time of last volume backup */
    short    ioVAtrb;      /* bit 15=1 if volume locked */
    short    ioVNmFls;     /* number of files in file directory */
    short    ioVDirSt;     /* first block of file directory */
    short    ioVB1Ln;      /* number of blocks in file directory */
    short    ioVNmA1Blks;  /* number of alloc blocks on volume */
    long     ioVA1BlkSiz;  /* number of bytes per alloc block */
    long     ioVClpSiz;    /* number of bytes to Allocate */
    short    ioA1BlSt;     /* first block in volume block map */
    long     ioVNxtFNum;   /* next free file number */
    short    ioVFrBlk;     /* number of free allocation blocks */
} VolumeParam;

typedef struct VCB {
    struct QElem *qLink;    /* next queue entry */
    short    qType;        /* not used */
    short    vcbFlags;     /* bit 15=1 if dirty */
    short    vcbSigWord;   /* always 0xd2d7 */
    long     vcbCrDate;    /* date volume was initialized */
    long     vcbLSBkUp;    /* date of last backup */
    short    vcbAtrb;      /* volume attributes */
    short    vcbNmFls;     /* number of files in directory */
    short    vcbDirSt;     /* directory's first block */
    short    vcbB1Ln;      /* length of file directory */
    short    vcbNmBlks;    /* number of allocation blocks */
    long     vcbA1BlkSiz;  /* size of allocation blocks */
    long     vcbClpSiz;    /* number of bytes to Allocate */
    short    vcbA1BlSt;    /* first block in block map */
}

```

## FILES

## Macintosh Interface Libraries

## FILES

```

    long      vcbNxtFNum;      /* next unused file number */
    short     vcbFreeBks;     /* number of unused blocks */
    String(27) vcbVN;         /* volume name */
    short     vcbDrvNum;      /* drive number */
    short     vcbDRefNum;     /* driver reference number */
    short     vcbFSID;        /* file system identifier */
    short     vcbVRefNum;     /* volume reference number */
    Ptr       vcbMAdr;        /* location of block map */
    Ptr       vcbBufAdr;     /* location of volume buffer */
    short     vcbMLen;        /* number of bytes in block map */
    short     vcbDirIndex;    /* used internally */
    short     vcbDirBlk;     /* used internally */
} VCB;

typedef struct DrvQEl {
    struct QElem *qLink;      /* next queue entry */
    short        qType;       /* not used */
    short        dQDrive;     /* drive number */
    short        dQRefNum;    /* drive reference number */
    short        dQFSID;      /* file system identifier */
    short        dQDrvSize;   /* number of logical blocks */
} DrvQEl, *DrvQElPtr;

/* --- High-Level Routines ----- */

/* Accessing Volumes */

OSErr GetVInfo(drvNum, volName, vRefNum, freeBytes)
    short drvNum;
    char *volName;
    short *vRefNum;
    long *freeBytes;
OSErr GetVol(volName, vRefNum)
    char *volName;
    short *vRefNum;
OSErr SetVol(volName, vRefNum)
    char *volName;
    short vRefNum;
OSErr FlushVol(volName, vRefNum)
    char *volName;
    short vRefNum;
OSErr UnmountVol(volName, vRefNum)
    char *volName;
    short vRefNum;
OSErr Eject(volName, vRefNum)
    char *volName;
    short vRefNum;

/* Changing File Contents */

OSErr Create(fileName, vRefNum, creator, fileType)
    char *fileName;
    short vRefNum;

```

## FILES

## Macintosh Interface Libraries

## FILES

```

    OSType creator, fileType;
OSErr FSOpen(fileName, vRefNum, refNum)
    char *fileName;
    short vRefNum, *refNum;
OSErr OpenRF(fileName, vRefNum, refNum)
    char *fileName;
    short vRefNum, *refNum;
OSErr FSRead(refNum, count, buffPtr)
    short refNum;
    long *count;
    Ptr buffPtr;
OSErr FSWrite(refNum, count, buffPtr)
    short refNum;
    long *count;
    Ptr buffPtr;
OSErr GetFPos(refNum, filePos)
    short refNum;
    long *filePos;
OSErr SetFPos(refNum, posMode, posOff)
    short refNum, posMode;
    long posOff;
OSErr GetEOF(refNum, logEOF)
    short refNum;
    long *logEOF;
OSErr SetEOF(refNum, logEOF)
    short refNum;
    long logEOF;
OSErr Allocate(refNum, count)
    short refNum;
    long *count;
OSErr GetVRefNum(pathRefNum, vRefNum)
    short pathRefNum;
    short *vRefNum;
OSErr FSClose(refNum)
    short refNum;

/* Changing Information About Files */

OSErr GetFInfo(fileName, vRefNum, fndrInfo)
    char *fileName;
    short vRefNum;
    FInfo *fndrInfo;
OSErr SetFInfo(fileName, vRefNum, fndrInfo)
    char *fileName;
    short vRefNum;
    FInfo *fndrInfo;
OSErr SetFLock(fileName, vRefNum)
    char *fileName;
    short vRefNum;
OSErr RstFLock(fileName, vRefNum)
    char *fileName;
    short vRefNum;
OSErr Rename(oldName, vRefNum, newName)
    char *oldName;
    short vRefNum;
    char *newName;

```

## FILES

## Macintosh Interface Libraries

## FILES

```

OSErr FSDelete(fileName, vRefNum)
    char *fileName;
    short vRefNum;

/* --- Low-Level Routines ----- */

void FInitQueue()
void AddDrive(drvrRefNum, drvNum, qEl);
    short drvrRefNum, drvNum;
    drvQElPtr qEl;

/* Accessing Volumes */

OSErr PBMountVol(paramBlock)
    VolumeParam *paramBlock;
OSErr PBGetVInfo(paramBlock, async)
    VolumeParam *paramBlock;
    Boolean async;
OSErr PBGetVol(paramBlock, async)
    VolumeParam *paramBlock;
    Boolean async;
OSErr PBSetVol(paramBlock, async)
    VolumeParam *paramBlock;
    Boolean async;
OSErr PBFlushVol(paramBlock, async)
    VolumeParam *paramBlock;
    Boolean async;
OSErr PBUnmountVol(paramBlock)
    VolumeParam *paramBlock;
OSErr PBOffLine(paramBlock)
    VolumeParam *paramBlock;
OSErr PBEject(paramBlock)
    VolumeParam *paramBlock;

/* Changing File Contents */

OSErr PBCreate(paramBlock, async)
    FileParam *paramBlock;
    Boolean async;
OSErr PBOpen(paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBOpenRF(paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBRead(paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBWrite(paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBGetFPos(paramBlock, async)
    IOParam *paramBlock;

```

## FILES

## Macintosh Interface Libraries

## FILES

```

    Boolean async;
OSErr PBSetFPos (paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBGetEOF (paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBSetEOF (paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBAllocate (paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBFlushFile (paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBClose (paramBlock, async)
    IOParam *paramBlock;
    Boolean async;

/* Changing Information About Files */

OSErr PBGetFInfo (paramBlock, async)
    FileParam *paramBlock;
    Boolean async;
OSErr PBSetFInfo (paramBlock, async)
    FileParam *paramBlock;
    Boolean async;
OSErr PBSetFLock (paramBlock, async)
    FileParam *paramBlock;
    Boolean async;
OSErr PBRstFLock (paramBlock, async)
    FileParam *paramBlock;
    Boolean async;
OSErr PBSetFVers (paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBRename (paramBlock, async)
    IOParam *paramBlock;
    Boolean async;
OSErr PBDelete (paramBlock, async)
    FileParam *paramBlock;
    Boolean async;

/* Accessing Queues */

struct QHdr *GetFSQHdr ()
struct QHdr *GetVCBQHdr ()
struct QHdr *GetDrvQHdr ()

```

## DESCRIPTION

The File Manager controls the exchange of information between an application and files.

FILES

Macintosh Interface Libraries

FILES

**Warning:** The low-level routines that use strings take as input and return as output pointers to Pascal-style strings (string length in first byte). However, the high-level routines use C-style strings (terminated by a null character) as input and output parameters.

For more detailed information see the File Manager chapter of *Inside Macintosh*.

**NOTE**

An I/O completion routine cannot reliably access any globals, strings, or other functions outside its segment.

## FONTS

## Macintosh Interface Libraries

## FONTS

## NAME

fonts—Font Manager

## SYNOPSIS

```

#include <types.h>
#include <font.h>

#define systemFont 0
#define applFont 1
#define newYork 2
#define geneva 3
#define monaco 4
#define venice 5
#define london 6
#define athens 7
#define sanFran 8
#define toronto 9
#define cairo 11
#define losAngeles 12
#define times 20
#define helvetica 21
#define courier 22
#define symbol 23
#define taliesin 24
#define kanji 25

#define commandMark '\021'
#define checkMark '\022'
#define diamondMark '\023'
#define appleMark '\024'

#define propFont 0x9000
#define fixedFont 0xB000
#define fontWid 0xACB0

typedef struct FMInput {
    short family; /* e.g. New York */
    short size; /* e.g. 12 Point */
    Style face; /* e.g. bold | underline */
    Boolean needBits; /* bits or just measurement */
    short device; /* always 0 for display */
    Point numer; /* current drawing scale */
    Point denom; /* current drawing scale */
} FMInput;

typedef struct FMOutput {
    short errNum; /* not used */
    Handle fontHandle; /* Handle to font */
    unsigned char boldPixels; /* pixels of horizontal smear */
    unsigned char italicPixels; /* pixels of horizontal shear */
    unsigned char ulOffset; /* pixels below baseline */
    unsigned char ulShadow; /* pixels in halo */
    unsigned char ulThick; /* thickness of underline */
    unsigned char shadowPixels; /* pixels to shadow (0 .. 3) */
    char extra; /* extra white pixels/char */
    unsigned char ascent; /* ascent */
}

```



## FONTS

## Macintosh Interface Libraries

## FONTS

```

    unsigned char descent;      /* descent */
    unsigned char widMax;      /* maximum character width */
    char leading;              /* leading between lines */
    char unused;               /* not used */
    Point numer;               /* current drawing scale */
    Point denom;               /* current drawing scale */
} FMOutput, *FMOutPtr;

typedef struct FontRec {
    short fontType;            /* font type */
    short firstChar;           /* ASCII code of first character */
    short lastChar;           /* ASCII code of last character */
    short widMax;              /* maximum character width */
    short kernMax;            /* negative of maximum character kern */
    short nDescent;           /* negative of descent */
    short fRectWidth;         /* width of font rectangle */
    short fRectHeight;        /* height of font rectangle */
    short owTLoc;             /* offset to offset/width table */
    short ascent;              /* ascent */
    short descent;            /* descent */
    short leading;            /* leading */
    short rowWords;           /* row width of bit image / 2 */
    /*
    short bitImage[(rowWords-1)+1][(fRectHeight-1)+1];
    short locTable[(lastChar+2-firstChar)+1];
    short owTable[(lastChar+2-firstChar)+1];
    */
} FontRec;

pascal void InitFonts()
void GetFontName(fontNum, theName)
    short fontNum;
    char *theName;
void GetFNum(fontName, theNum)
    char *fontName;
    short *theNum;
pascal Boolean RealFont(fontNum, size)
    short fontNum;
    short size;
pascal void SetFontLock(lockFlag)
    Boolean lockFlag;
pascal FMOutPtr SwapFont(inRec)
    FMInput *inRec;

```

## DESCRIPTION

The Font Manager supports the character fonts used to draw text with QuickDraw. For more detailed information see the Font Manager chapter of *Inside Macintosh*.

## MEMORY

## Macintosh Interface Libraries

## MEMORY

## NAME

memory—Memory Manager

## SYNOPSIS

```

#include <types.h>
#include <memory.h>

#define maxSize    0x800000    /* maximum block size */

/* Result Codes */

#define memFullErr    (-108)    /* not enough room in zone */
#define memLockedErr (-117)    /* block is locked */
#define memPurErr    (-112)    /* attempt to purge a locked block */
#define memWZErr     (-111)    /* attempt to operate on a free block */
#define nilHandleErr (-109)    /* nil master pointer */
#define noErr        0        /* no error */

typedef long Size;

typedef struct Zone {
    Ptr    bkLim;                /* limit pointer */
    Ptr    purgePtr;            /* used internally */
    Ptr    hFstFree;            /* first free master pointer */
    long   zcbFree;             /* number of free bytes */
    ProcPtr gzProc;             /* grow zone function */
    short  moreMast;            /* master pointers to allocate */
    short  flags;               /* used internally */
    short  cntRel;              /* relocatable blocks */
    short  maxRel;              /* maximum cntRel value */
    short  cntNRel;             /* nonrelocatable blocks */
    short  maxNRel;             /* maximum maxRel value */
    short  cntEmpty;            /* empty master pointers */
    short  cntHandles;          /* total master pointers */
    long   minCBFree;           /* minimum zcbFree value */
    ProcPtr purgeProc;          /* purge warning procedure */
    Ptr    sparePtr;            /* used internally */
    Ptr    allocPtr;            /* used internally */
    short  heapData;            /* first usable byte in zone */
} Zone, *THz;

/* Initialization and Allocation */

void InitApplZone()
void SetApplBase(startPtr)
    Ptr startPtr;
void InitZone(pGrowProc,cMoreMasters,limitPtr,startPtr)
    ProcPtr pGrowProc;
    short cMoreMasters;
    Ptr limitPtr,startPtr;
void SetApplLimit(zoneLimit)
    Ptr zoneLimit;
Ptr GetApplLimit()
void MaxApplZone()
void MoreMasters()

```

## MEMORY

## Macintosh Interface Libraries

## MEMORY

```

/* Heap Zone Access */

THz GetZone()
void SetZone(hz)
    THz hz;
THz SystemZone()
THz ApplicZone()

/* Allocating and Releasing Relocatable Blocks */

Handle NewHandle(logicalSize)
    Size logicalSize;
void DisposHandle(h)
    Handle h;
Size GetHandleSize(h)
    Handle h;
void SetHandleSize(h,newSize)
    Handle h;
    Size newSize;
THz HandleZone(h)
    Handle h;
Handle RecoverHandle(p)
    Ptr p;
void ReallocHandle(h,logicalSize)
    Handle h;
    Size logicalSize;

/* Allocating and Releasing Nonrelocatable Blocks */

Ptr NewPtr(logicalSize)
    Size logicalSize;
void DisposPtr(p)
    Ptr p;
Size GetPtrSize(p)
    Ptr p;
void SetPtrSize(p,newSize)
    Ptr p;
    Size newSize;
THz PtrZone(p)
    Ptr p;

/* Freeing Space in the Heap */

long FreeMem()
Size MaxMem(grow)
    Size *grow;
Size CompactMem(cbNeeded)
    Size cbNeeded;
void ResrvMem(cbNeeded)
    Size cbNeeded;
void PurgeMem(cbNeeded)
    Size cbNeeded;
void EmptyHandle(h)

```

## MEMORY

## Macintosh Interface Libraries

## MEMORY

```

    Handle h;

    /* Properties of Relocatable Blocks */

    void HLock(h)
        Handle h;
    void HUnlock(h)
        Handle h;
    void HPurge(h)
        Handle h;
    void HNoPurge(h)
        Handle h;

    /* Grow Zone Operations */

    void SetGrowZone(growZone)
        ProcPtr growZone;
    Boolean GZCritical()
    Handle GZSaveHnd()

    /* Miscellaneous Routines */

    BlockMove(sourcePtr, destPtr, byteCount)
        Ptr sourcePtr, destPtr;
        long byteCount;
    Ptr TopMem()
    void MoveHHi(h)
        Handle h;
    OSErr MemError()

```

## USER ROUTINES

```

    pascal Size MyGrowZone(cbNeeded)
        Size cbNeeded;

```

## DESCRIPTION

The Memory Manager provides dynamic allocation of both relocatable and nonrelocatable memory space within the system and application heaps.

For more detailed information see the Memory Manager chapter of *Inside Macintosh*.

## MENUS

## Macintosh Interface Libraries

## MENUS

## NAME

menus—Menu Manager

## SYNOPSIS

```
#include <types.h>
#include <menus.h>

/* Special Characters */

#define noMark          '\0'

/* Messages to Menu Definition Functions */

#define mDrawMsg        0
#define mChooseMsg     1
#define mSizeMsg       2

/* Resource ID of Standard Menu Definition Procedure */
#define textMenuProc    0

typedef struct MenuInfo {
    short    menuID;
    short    menuWidth;
    short    menuHeight;
    ProcHandle menuProc;
    long     enableFlags;
    Str255   menuData;
} MenuInfo, *MenuPtr, **MenuHandle;

/* Initialization and Allocation */

pascal void InitMenus()
MenuHandle NewMenu(menuID,menuTitle)
    short menuID;
    char *menuTitle;
pascal MenuHandle GetMenu(resourceID)
    short resourceID;
pascal void DisposeMenu(theMenu)
    MenuHandle theMenu;
void AppendMenu(theMenu,data)
    MenuHandle theMenu;
    char *data;
pascal void AddResMenu(theMenu,theType)
    MenuHandle theMenu;
    ResType theType;
pascal void InsertResMenu(theMenu,theType,afterItem)
    MenuHandle theMenu;
    ResType theType;
    short afterItem;

/* Forming the Menu Bar */

pascal void InsertMenu(theMenu,beforeID)
```

## MENUS

## Macintosh Interface Libraries

## MENUS

```

    MenuHandle theMenu;
    short beforeID;
    pascal void DrawMenuBar()
    pascal void DeleteMenu(menuID)
        short menuID;
    pascal void ClearMenuBar()
    pascal Handle GetNewMBar(menuBarID)
        short menuBarID;
    pascal Handle GetMenuBar()
    pascal void SetMenuBar(menuList)
        Handle menuList;

    /* Choosing From a Menu */

    long MenuSelect(startPt)
        Point *startPt;
    pascal long MenuKey(ch)
        short ch;
    pascal void HiliteMenu(menuID)
        short menuID;

    /* Controlling Items' Appearance */

    void SetItem(theMenu,item,itemString)
        MenuHandle theMenu;
        short item;
        char *itemString;
    void GetItem(theMenu,item,itemString)
        MenuHandle theMenu;
        short item;
        char *itemString;
    pascal void DisableItem(theMenu,item)
        MenuHandle theMenu;
        short item;
    pascal void EnableItem(theMenu,item)
        MenuHandle theMenu;
        short item;
    pascal void CheckItem(theMenu,item,checked)
        MenuHandle theMenu;
        short item;
        Boolean checked;
    pascal void SetItemMark(theMenu,item,markChar)
        MenuHandle theMenu;
        short item;
        short markChar;
    pascal void GetItemMark(menu,item,markChar)
        MenuHandle menu;
        short item;
        short *markChar;
    pascal void SetItemIcon(theMenu,item,iconNum)
        MenuHandle theMenu;
        short item;
        short iconNum;
    pascal void GetItemIcon(theMenu,item,iconNum)
        MenuHandle theMenu;

```

## MENUS

## Macintosh Interface Libraries

## MENUS

```

    short item;
    short *iconNum;
    pascal void SetItemStyle(theMenu, item, chStyle)
        MenuHandle theMenu;
    short item;
    Style chStyle;
    pascal void GetItemStyle(menu, item, chStyle)
        MenuHandle menu;
    short item;
    Style *chStyle;

/* Miscellaneous Utilities */

    pascal void CalcMenuSize(theMenu)
        MenuHandle theMenu;
    pascal short CountMItems(theMenu)
        MenuHandle theMenu;
    pascal MenuHandle GetMHandle(menuID)
        short menuID;
    pascal void FlashMenuBar(menuID)
        short menuID;
    pascal void SetMenuFlash(count)
        short count;

```

## USER ROUTINES

```

    pascal void MyMenu(message, theMenu, menuRect, hitPt, whichItem)
        short message;
        MenuHandle theMenu;
        Rect *menuRect;
        Point hitPt;
        short *whichItem;

```

## DESCRIPTION

The Menu Manager provides routines for creating and using menus.

**Warning:** The names of desk accessories start with a null byte. The output parameter from `GetMenuItem` will return a string that begins with a null byte when a desk accessory is selected from the Apple menu. `OpenDeskAcc` skips over the null byte when interpreting its parameter.

For more detailed information see the Menu Manager chapter of *Inside Macintosh*.

## OSEVENTS

## Macintosh Interface Libraries

## OSEVENTS

## NAME

osevents—Operating System Event Manager

## SYNOPSIS

```
#include <types.h>
#include <osevents.h>

typedef struct EvQEl {
    struct QElem *qLink;
    short    qType;
    short    evtQWhat;
    long     evtQMessage;
    long     evtQWhen;
    Point    evtQWhere;
    short    evtQModifiers;
} EvQEl;

/* Setting the System Event Mask */

void SetEventMask(theMask)
    short theMask;

/* Posting and Removing Events */

OSErr PostEvent(eventCode, eventMsg)
    short eventCode;
    long eventMsg;
void FlushEvents(eventMask, stopMask)
    short eventMask;
    short stopMask;

/* Accessing Events */

Boolean GetOSEvent(eventMask, theEvent)
    short eventMask;
    struct EventRecord *theEvent;
Boolean OSEventAvail(eventMask, theEvent)
    short eventMask;
    struct EventRecord *theEvent;

/* Directly Accessing the Event Queue */

struct QHdr *GetEvQHdr()
```

## DESCRIPTION

The Operating System Event Manager provides a low-level interface to the Macintosh keyboard, keypad, and mouse.

For more detailed information see the Operating System Event Manager chapter of *Inside Macintosh*.



## OSUTILS

## Macintosh Interface Libraries

## OSUTILS

## NAME

osutils—Operating System Utilities

## SYNOPSIS

```

#include <types.h>
#include <osutils.h>

#define noErr          0      /* no error */
#define qErr          (-1)   /* element not in specified queue */
#define clkRdErr      (-85)  /* unable to read clock */
#define clkWrErr      (-86)  /* time written did not verify */
#define prWrErr       (-87)  /* parameter RAM written did not verify */
#define prInitErr     (-88)  /* validity status is not 0xa8 */
#define memFullErr    (-108) /* not enough room in heap */
#define nilHandleErr  (-109) /* nil master pointer */
#define memWZErr      (-111) /* attempt to operate on a free block */

/* Serial Port configuration constants for config field of SysParmType */

#define useFree        0      /* use undefined */
#define useATalk       1      /* AppleTalk */
#define useAsync       2      /* Async */

/* Machine type returned by "Environ" routine */

#define macXMLMachine  0      /* Macintosh XL (a.k.a. Lisa) */
#define macMachine     1      /* Macintosh */

/* typedef long  OStype;  appears in file TYPES */
/* typedef short OSErr;  appears in file TYPES */

typedef struct SysParmType {
    char    valid;           /* validity status */
    char    aTalkA;         /* AppleTalk node # hint for port A */
    char    aTalkB;         /* AppleTalk node # hint for port B */
    char    config;         /* AppleTalk serial port configuration */
                                /* port A = bits 4-7, B = bits 0-3 */
    short   portA;          /* modem port configuration */
    short   portB;          /* printer port configuration */
    long    alarm;         /* alarm setting */
    short   font;           /* default application font number - 1 */
    short   kbdPrint;       /* auto-key threshold and rate, printer */
                                /* connection */
    short   volClik;        /* speaker volume, double-click and */
                                /* caret-blink times */
    short   misc;           /* mouse scaling, system startup disk, */
                                /* menu blink */
} SysParmType, *SysPPtr;

typedef struct QElem {
    struct QElem *qLink;    /* next queue entry */
    short        qType;     /* queue type */
    short        qData[0];  /* queue type specific data */
} QElem, *QElemPtr;

```

```

typedef struct QHdr
    short      qFlags          /* queue flags */
    QElemPtr   qHead;         /* first queue entry */
    QElemPtr   qTail;        /* last queue entry */
} QHdr, *QHdrPtr;

typedef enum {
    dummyType,
    vType,          /* vertical retrace queue type */
    ioQType,       /* file I/O or driver I/O type */
    drvQType,     /* drive queue type */
    evType,        /* event queue type */
    fsQType,      /* volume-control-block queue type */
} QTypes;

typedef struct DateTimeRec
    short      year;          /* four-digit year */
    short      month;        /* 1 to 12 for January to December */
    short      day;          /* 1 to 31 */
    short      hour;         /* 0 to 23 */
    short      minute;       /* 0 to 59 */
    short      second;       /* 0 to 59 */
    short      dayOfWeek;    /* 0 to 7 for Sunday to Saturday */
} DateTimeRec;

/* Pointer and Handle Manipulation */

OSErr HandToHand(theHndl)
    Handle *theHndl;
OSErr PtrToHand(srcPtr, dstHndl, size)
    Ptr srcPtr;
    Handle *dstHndl;
    long size;
OSErr PtrToXHand(srcPtr, dstHndl, size)
    Ptr srcPtr;
    Handle dstHndl;
    long size;
OSErr HandAndHand(aHndl, bHndl)
    Handle aHndl, bHndl;
OSErr PtrAndHand(pntr, hndl, size)
    Ptr pntr;
    Handle hndl;
    long size;

/* String Comparison */

Boolean EqualString(aStr, bStr, caseSens, diacSens)
    char *aStr, *bStr;
    Boolean caseSens, diacSens;
void UprString(theString, diacSens)
    char *theString;

```

OSUTILS

Macintosh Interface Libraries

OSUTILS

```

        Boolean marks;

/* Date and Time Operations */
OSErr ReadDateTime(secs)
    long *secs;
void GetDateTime(secs)
    long *secs;
OSErr SetDateTime(secs)
    long secs;
void Date2Secs(date,secs)
    DateTimeRec *date;
    long *secs;
void Secs2Date(secs,date)
    long secs;
    DateTimeRec *date;
void GetTime(date)
    DateTimeRec *date;
void SetTime(date)
    DateTimeRec *date;

/* Parameter RAM Operations */
OSErr InitUtil()
SysPPtr GetSysPPtr()
OSErr WriteParam()

/* Queue Manipulation */
void Enqueue(qElement,theQueue)
    QElemPtr qElement;
    QHdrPtr theQueue;
OSErr Dequeue(qElement,theQueue)
    QElemPtr qElement;
    QHdrPtr theQueue;

/* Dispatch Table Utilities */
void SetTrapAddress(trapAddr,trapNum)
    long trapAddr;
    short trapNum;
long GetTrapAddress(trapNum)
    short trapNum;

/* Miscellaneous Utilities */
void Delay(numTicks,finalTicks)
    long numTicks,*finalTicks;
pascal void SysBeep(duration)
    short duration;
void Environs(rom,machine)
    short *rom,*machine;

```

OSUTILS

Macintosh Interface Libraries

OSUTILS

```
void Restart()
```

**DESCRIPTION**

The Operating System Utilities are a set of routines and data types in the Operating System that perform generally useful operations such as manipulating pointers and handles, comparing strings, and reading the date and time.

For more detailed information see the Operating System Utilities chapter of *Inside Macintosh*.

## PACKAGES

## Macintosh Interface Libraries

## PACKAGES

## NAME

packages—

Package Manager, Disk Initialization, Standard File Package, International Utilities,  
Binary-Decimal Conversion

## SYNOPSIS

```

#include <types.h>
#include <packages.h>

/* Package Manager ----- */

/* Resource IDs for packages */

#define dskInit      2      /* Disk Initialization */
#define stdFile     3      /* Standard File */
#define flPoint     4      /* Floating-Point Arithmetic */
#define trFunc      5      /* Transcendental Functions */
#define intUtil     6      /* International Utilities */
#define bdConv      7      /* Binary/Decimal Conversion */

pascal void InitAllPacks()
pascal void InitPack(packID)
    short packID;

/* Disk Initialization Package ----- */

void DIload()
void DIunload()
short DIBadMount(where, evtMessage)
    Point where;
    long evtMessage;
OSErr DIFormat(drvNum)
    short drvNum;
OSErr DIVerify(drvNum)
    short drvNum;
OSErr DIZero(drvNum, volName)
    short drvNum;
    char *volName;

/* Standard File Package ----- */

#define putDlgID    (-3999) /* SFPutFile dialog template ID */

#define putSave     1      /* Save button */
#define putCancel   2      /* Cancel button */
#define putEject    5      /* Eject button */
#define putDrive    6      /* Drive button */
#define putName     7      /* editText item for file name */

#define getDlgID    (-4000) /* SFGetFile dialog template ID */

#define getOpen     1      /* Open button */
#define getCancel   3      /* Cancel button */
#define getEject    5      /* Eject button */

```

## PACKAGES

## Macintosh Interface Libraries

## PACKAGES

```

#define getDrive      6      /* Drive button */
#define getNmList    7      /* userItem for file name list */
#define getScroll    8      /* userItem for scroll bar */

typedef struct SFReply {
    Boolean good;          /* FALSE if ignore command */
    Boolean copy;         /* not used */
    OSType fType;        /* file type or not used */
    short vRefNum;       /* volume reference number */
    short version;      /* file's version number */
    String(63) fName;   /* file name */
} SFReply;

typedef OSType SFTypelist[4];

void SFPutFile(where, prompt, origName, dlgHook, reply)
    Point *where;
    char *prompt;
    char *origName;
    ProcPtr dlgHook;
    SFReply *reply;
void SFPPutFile(where, prompt, origName, dlgHook, reply, dlgID, filterProc)
    Point *where;
    char *prompt;
    char *origName;
    ProcPtr dlgHook;
    SFReply *reply;
    short dlgID;
    ProcPtr filterProc;
void SFGetFile(where, prompt, fileFilter, numTypes, typeList, dlgHook, reply)
    Point *where;
    char *prompt;
    ProcPtr fileFilter;
    short numTypes;
    SFTypelist typeList;
    ProcPtr dlgHook;
    SFReply *reply;
void SFPGetFile(where, prompt, fileFilter, numTypes, typeList, dlgHook, reply,
    dlgID, filterProc)
    Point *where;
    char *prompt;
    ProcPtr fileFilter;
    short numTypes;
    SFTypelist typeList;
    ProcPtr dlgHook;
    SFReply *reply;
    short dlgID;
    ProcPtr filterProc;

/* International Utilities Package ----- */
/* Masks for currency format */

#define currSymLead    16    /* set if currency symbol leads */
#define currNegSym     32    /* set if minus sign for negative */
#define currTrailingZ 64    /* set if trailing decimal zeroes */

```

## PACKAGES

## Macintosh Interface Libraries

## PACKAGES

```

#define currLeadingZ 128    /* set if leading integer zeroes */

/* Order of short date elements */

#define mdy          0    /* month day year */
#define dmy          1    /* day month year */
#define ymd          2    /* year month day */

/* Masks for short date format */

#define dayLdingZ    32    /* set if leading zero for day */
#define mntLdingZ    64    /* set if leading zero for month */
#define century      128   /* set if century included */

/* Masks for time format */

#define secLeadingZ    32    /* set if leading zero for seconds */
#define minLeadingZ    64    /* set if leading zero for minutes */
#define hrLeadingZ     128   /* set if leading zero for hours */

/* Country Codes -- high-order byte of version information */

#define verUS         0
#define verFrance     1
#define verBritain    2
#define verGermany    3
#define verItaly       4
#define verNetherlands 5
#define verBelgiumLux  6
#define verSweden      7
#define verSpain       8
#define verDenmark     9
#define verPortugal    10
#define verFrCanada    11
#define verNorway      12
#define verIsrael      13
#define verJapan        14
#define verAustralia   15
#define verArabia       16
#define verFinland     17
#define verFrSwiss     18
#define verGrSwiss     19
#define verGreece      20
#define verIceland     21
#define verMalta        22
#define verCyprus       23
#define verTurkey      24
#define verYugoslavia  25

typedef struct Intl0Rec {
    char decimalPt;    /* decimal point character */
    char thousSep;     /* thousands separator */
    char listSep;      /* list separator */
    char currSym1;     /* currency symbols (3 bytes long) */
    char currSym2;
    char currSym3;
    unsigned char currFmt; /* currency format */

```

## PACKAGES

## Macintosh Interface Libraries

## PACKAGES

```

    unsigned char dateOrder; /* short date order - dmy, ymd or mdy */
    unsigned char shrtDateFmt; /* short date format */
    char dateSep; /* date separator */
    unsigned char timeCycle; /* 0 if 24-hour cycle, 255 if 1- hour */
    unsigned char timeFmt; /* time format */
    char mornStr[4]; /* trailing string for first 12 hours */
    char eveStr[4]; /* trailing stringfor last 12 hours */
    char timeSep; /* time separator */
    char time1Suff; /* trailing string for 24-hour cycle */
    char time2Suff;
    char time3Suff;
    char time4Suff;
    char time5Suff;
    char time6Suff;
    char time7Suff;
    char time8Suff;
    unsigned char metricSys; /* 255 for metric, 0 if not */
    short intl0Vers; /* version information - country, vers */
} Intl0Rec, *Intl0Ptr, **Intl0Hndl;

typedef struct Intl1Rec {
    String(15) days[7]; /* day names */
    String(15) months[12]; /* month names */
    unsigned char suppressDay; /* 0 for day name, 255 for none */
    unsigned char lngDateFmt; /* order of long date elements */
    unsigned*char dayLeading0; /* 255 for leading 0 in day number */
    unsigned char abbrLen; /* length for abbreviating names */
    char st0[4]; /* date punctuation */
    char st1[4];
    char st2[4];
    char st3[4];
    char st4[4];
    short intl1Vers; /* version information */
    short localRtn[0]; /* routine for string comparison */
} Intl1Rec, *Intl1Ptr, **Intl1Hndl;

typedef enum {shortDate,longDate,abbrevDate} DateForm;

void IUDateString(dateTime, form, result)
    long dateTime;
    DateForm form;
    char *result;
void IUDatePString(dateTime, form, result, intlParam)
    long dateTime;
    DateForm form;
    char *result;
    Handle intlParam;
void IUTimeString(dateTime, wantSeconds, result)
    long dateTime;
    Boolean wantSeconds;
    char *result;
void IUTimePString(dateTime, wantSeconds, result, intlParam)
    long dateTime;
    Boolean wantSeconds;
    char *result;
    Handle intlParam;
Boolean IUMetric()

```



## PACKAGES

## Macintosh Interface Libraries

## PACKAGES

```

Handle IUGetIntl(theID)
  short theID;
void IUSetIntl(refNum,theID,intlParam)
  short refNum;
  short theID;
  Handle intlParam;
short IUCompString(aStr,bStr)
  char *aStr;
  char *bStr;
short IUMagString(aPtr,bPtr,aLen,bLen)
  Ptr aPtr,bPtr;
  short aLen,bLen;
short IUEqualString(aStr,bStr)
  char *aStr;
  char *bStr;
short IUMagIDString(aPtr,bPtr,aLen,bLen)
  Ptr aPtr,bPtr;
  short aLen,bLen;

/* Binary-Decimal Conversion Package ----- */

void StringToNum(theString,theNum)
  char *theString;
  long *theNum;
void NumToString(theNum,theString)
  long theNum;
  char *theString;

```

## USER ROUTINES

```

/* Standard File Package ----- */

short MyDlg(item,theDialog)
  short item;
  DialogPtr theDialog;

Boolean MyFileFilter(paramBlock)
  ParmBlkPtr paramBlock;

```

## DESCRIPTION

The Package Manager provides for the initialization of packages.

For more detailed information see the following chapters of *Inside Macintosh*: Package Manager, Disk Initialization Package, Standard File Package, International Utilities Package, Binary-Decimal Conversion Package.

## PRINTING

## Macintosh Interface Libraries

## PRINTING

## NAME

printing—Printing Manager

## SYNOPSIS

```

#include <types.h>
#include <quickdraw.h>
#include <printing.h>

/* Printing Methods */

#define bDraftLoop          0 /* draft printing */
#define bSpoolLoop         1 /* spooling */

/* Printer specification in prStl field of print record */

#define bDevCItoh          1 /* ImageWriter printer */
#define bDevLaser          3 /* LaserWriter printer */

/* Maximum number of pages in a spool file */

#define iPFMaxPgs          128 /* max pages in a spool file */
#define iPrPgFract         120 /* paper units per inch */

/* Result codes */

#define noErr               0 /* no error */
#define iPrSavPFil         (-1) /* saving spool file */
#define iIOAbort           (-27) /* I/O abort error */
#define iMemFullErr        (-108) /* not enough room in heap zone */
#define iPrAbort           128 /* application or user requested abort */

/* Printer Driver Control Call Parameters */

#define iPrDevCtl           7 /* device control */
#define lPrReset           0x00010000 /* reset printer */
#define lPrLineFeed        0x00030000 /* start new line */
#define lPrLFSixth         0x0003FFFF /* standard 1/6" line feed */
#define lPrPageEnd         0x00020000 /* start new page */
#define iPrBitsCtl         4 /* bit map printing */
#define lScreenBits        0 /* configurable */
#define lPaintBits         1 /* 72 x 72 dots */
#define iPrIOCtl           5 /* text streaming */

/* Printing Resources */

#define sPrDrv              ".Print" /* Printer Driver resource name */
#define iPrDrvRef           (-3) /* Printer Driver reference number */

/* Type definitions */

typedef Rect *TPRect;

typedef struct TPrPort {
    GrafPort gPort; /* graph port to draw in */

```

PRINTING

Macintosh Interface Libraries

PRINTING

```

    QDProcs  gProcs;      /* pointers to drawing routines */
    long     lGParam1;   /* internal */
    long     lGParam2;   /* internal */
    long     lGParam3;   /* internal */
    long     lGParam4;   /* internal */
    Boolean   fOurPtr;    /* internal */
    Boolean   fOurBits;   /* internal */
} TPrPort, *TPPrPort;

typedef struct TPrInfo {
    short    iDev;        /* printer information */
    short    iVRes;       /* printer vertical resolution */
    short    iHRes;       /* printer horizontal resolution */
    Rect     rPage;       /* page rectangle */
} TPrInfo;

typedef enum {feedCut,feedFanfold,feedMechCut,feedOther} TFeed;

typedef struct TPrStl {
    short    wDev;        /* high byte specifies device */
    short    iPageV;      /* paper height */
    short    iPageH;      /* paper width */
    char     bPort;       /* printer or modem port - ignored */
    TFeed    feed;        /* paper type */
} TPrStl;

typedef enum {scanTB,scanBT,scanLR,scanRL} TScan;

typedef struct TPrXInfo {
    short    iRowBytes;   /* bytes per row */
    short    iBandV;      /* vertical dots */
    short    iBandH;      /* horizontal dots */
    short    iDevBytes;   /* size of bit image */
    short    iBands;      /* bands per page */
    char     bPatScale;    /* used by QuickDraw */
    char     bUlThick;     /* underline thickness */
    char     bUlOffset;    /* underline offset */
    char     bUlShadow;    /* underline descender */
    TScan    scan;        /* scan direction */
    char     bXInfoX;      /* not used */
} TPrXInfo;

typedef struct TPrJob {
    short    iFstPage;    /* first page to print */
    short    iLstPage;    /* last page to print */
    short    iCopies;     /* number of copies */
    char     bJDocLoop;   /* printing method */
    Boolean   fFromUser;  /* true if called from application */
    ProcPtr  pIdleProc;   /* background procedure */
    StringPtr pFileName; /* spool file name */
    short    iFileVol;    /* volume reference number */
    char     bFileVers;   /* version number of spool file */
    char     bJobX;       /* not used */
} TPrJob;

typedef struct TPrint {
    short    iPrVersion; /* Printing Manager version */

```

```

    TPrInfo prInfo;      /* printing information */
    Rect    rPaper;     /* paper rectangle */
    TPrStl  prStl;     /* style information */
    TPrInfo prInfoPT;   /* copy of prInfo */
    TPrXInfo prXInfo;   /* band information */
    TPrJob  prJob;     /* job information */
    short   printX[19] /* internal */
} TPrint, *TPPrint, **THPrint;

typedef struct TPrStatus {
    short   iTotPages; /* total number of pages */
    short   iCurPage; /* page being printed */
    short   iTotCopies; /* number of copies */
    short   iCurCopy; /* copy begin printed */
    short   iTotBands; /* bands per page */
    short   iCurBand; /* band being printed */
    Boolean  fPgDirty; /* true if started printing page */
    Boolean  fImaging; /* true if imaging */
    THPrint  hPrint;   /* print record */
    TPPrPort pPrPort; /* printing port */
    PicHandle hPic;   /* internal */
} TPrStatus;

/* Initialization and Termination */

pascal void PrOpen()
pascal void PrClose()

/* Print Records and Dialogs */

pascal void PrintDefault(hPrint)
    THPrint hPrint;
pascal Boolean PrValidate(hPrint)
    THPrint hPrint;
pascal Boolean PrStlDialog(hPrint)
    THPrint hPrint;
pascal Boolean PrJobDialog(hPrint)
    THPrint hPrint;
pascal void PrJobMerge(hPrintSrc,hPrintDst)
    THPrint hPrintSrc,hPrintDst;

/* Document Printing */

pascal TPPrPort PrOpenDoc(hPrint,pPrPort,pIOBuf)
    THPrint hPrint;
    TPPrPort pPrPort;
    Ptr pIOBuf;
pascal void PrCloseDoc(pPrPort)
    TPPrPort pPrPort;
pascal void PrOpenPage(pPrPort,pPageFrame)
    TPPrPort pPrPort;
    TRect pPageFrame;
pascal void PrClosePage(pPrPort)
    TPPrPort pPrPort;

/* Spool Printing */

```

```

pascal void PrPicFile(hPrint,pPrPort,pIOBuf,pDevBuf,prStatus)
    THPrint hPrint;
    TPrPort pPrPort;
    Ptr pIOBuf,pDevBuf;
    TPrStatus *prStatus;

/* Handling Errors */

pascal short PrError()
pascal void PrSetError(iErr)
    short iErr;

/* Low Level Driver Access */

pascal void PrDrvOpen()
pascal void PrDrvClose()
pascal void PrCtlCall(iWhichCtl,lParam1,lParam2,lParam3)
    short iWhichCtl;
    long lParam1,lParam2,lParam3;
pascal Handle PrDrvDCE()
pascal short PrDrvVers()

```

**DESCRIPTION**

The Printing Manager supports printing on a variety of devices.

For more detailed information see the Printing Manager chapter of *Inside Macintosh*.

**NOTE**

The current Pascal implementation has additional constants and data types that aren't documented in *Inside Macintosh* because they're not generally used. This interface follows *Inside Macintosh*.

Programs that call the high-level printing routines must be linked with object file `prlink.obj`. Programs that call the low-level driver routines must link with `prscreen.obj`. Linking with both files yields duplicate definitions. Therefore a program can't call both the high-level routines and the driver routines.

## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

## NAME

quickdraw—QuickDraw

## SYNOPSIS

```

#include <types.h>
#include <quickdraw.h>

/* 16 Transfer Modes */

#define srcCopy      0
#define srcOr       1
#define srcXor      2
#define srcBic      3
#define notSrcCopy  4
#define notSrcOr    5
#define notSrcXor   6
#define notSrcBic   7
#define patCopy     8
#define patOr       9
#define patXor     10
#define patBic     11
#define notPatCopy  12
#define notPatOr    13
#define notPatXor   14
#define notPatBic   15

/* QuickDraw Color Separation Constants */

#define normalBit    0
#define inverseBit  1
#define redBit       4    /* RGB Additive Mapping */
#define greenBit     3
#define blueBit      2
#define cyanBit      8    /* CMYBk Subtractive Mapping */
#define magentaBit   7
#define yellowBit    6
#define blackBit     5
#define blackColor  33    /* Colors Expressed in these Mappings */
#define whiteColor  30
#define redColor    205
#define greenColor  341
#define blueColor   409
#define cyanColor   273
#define magentaColor 137
#define yellowColor  69

/* Picture Comments */

#define picLParen    0
#define picRParen    1

/* Type Style Constants */

#define normal       0x00
#define bold         0x01
#define italic       0x02
#define underline    0x04

```

## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

```

#define outline      0x08
#define shadow      0x10
#define condense    0x20
#define expand      0x40

/* Types */

typedef unsigned char Pattern[8];
typedef short Bits16[16];
typedef enum {frame,paint,erase,invert,fill} GrafVerb;

/* typedefs Style, Point, and Rect appear in file TYPES */

typedef struct FontInfo {
    short    ascent;
    short    descent;
    short    widMax;
    short    leading;
} FontInfo;

typedef struct BitMap {
    Ptr      baseAddr;
    short    rowBytes;
    Rect     bounds;
} BitMap;

typedef struct Cursor {
    Bits16   data;
    Bits16   mask;
    Point    hotSpot;
} Cursor;

typedef struct PenState {
    Point    pnLoc;
    Point    pnSize;
    short    pnMode;
    Pattern  pnPat;
} PenState;

typedef struct Region {
    short    rgnSize;
    Rect     rgnBBox;
    short    rgnData[0];
} Region, *RgnPtr, **RgnHandle;

typedef struct Picture {
    short    picSize;
    Rect     picFrame;
    short    picData[0];
} Picture, *PicPtr, **PicHandle;

typedef struct Polygon {
    short    polySize;
    Rect     polyBBox;
    Point    polyPoints[0];
} Polygon, *PolyPtr, **PolyHandle;

```

```

typedef struct QDProcs {
    ProcPtr  textProc;
    ProcPtr  lineProc;
    ProcPtr  rectProc;
    ProcPtr  rRectProc;
    ProcPtr  ovalProc;
    ProcPtr  arcProc;
    ProcPtr  polyProc;
    ProcPtr  rgnProc;
    ProcPtr  bitsProc;
    ProcPtr  commentProc;
    ProcPtr  txMeasProc;
    ProcPtr  getPicProc;
    ProcPtr  putPicProc;
} QDProcs, *QDProcsPtr;

typedef struct GrafPort {
    short      device;
    BitMap     portBits;
    Rect       portRect;
    RgnHandle  visRgn;
    RgnHandle  clipRgn;
    Pattern    bkPat;
    Pattern    fillPat;
    Point      pnLoc;
    Point      pnSize;
    short      pnMode;
    Pattern    pnPat;
    short      pnVis;
    short      txFont;
    Style      txFace;
    short      txMode;
    short      txSize;
    long       spExtra;
    long       fgColor;
    long       bkColor;
    short      colrBit;
    short      patStretch;
    PicHandle  picSave;
    RgnHandle  rgnSave;
    PolyHandle polySave;
    QDProcsPtr grafProcs;
} GrafPort, *GrafPtr;

/* External Variable Declarations */

extern struct qd {
    char      private[78];
    long      randSeed;
    BitMap    screenBits;
    Cursor    arrow;
    Pattern    dkGray;
    Pattern    ltGray;
    Pattern    gray;
    Pattern    black;

```



## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

```

    Pattern    white;
    GrafPtr    thePort;
} qd;

/* GrafPort Routines */

pascal void InitGraf(globalPtr)
    Ptr globalPtr;
pascal void OpenPort(port)
    GrafPtr port;
pascal void InitPort(port)
    GrafPtr port;
pascal void ClosePort(port)
    GrafPtr port;
pascal void SetPort(port)
    GrafPtr port;
pascal void GetPort(port)
    GrafPtr *port;
pascal void GrafDevice(device)
    short device;
pascal void SetPortBits(bm)
    BitMap *bm;
pascal void PortSize(width,height)
    short width,height;
pascal void MovePortTo(leftGlobal,rightGlobal)
    short leftGlobal,rightGlobal;
pascal void SetOrigin(h,v)
    short h,v;
pascal void SetClip(rgn)
    RgnHandle rgn;
pascal void GetClip(rgn)
    RgnHandle rgn;
pascal void ClipRect(r)
    Rect *r;
pascal void BackPat(pat)
    Pattern *pat;

/* Cursor Routines */

pascal void InitCursor()
pascal void SetCursor(crsr)
    Cursor *crsr;
pascal void HideCursor()
pascal void ShowCursor()
pascal void ObscureCursor()

/* Line Routines */

pascal void HidePen()
pascal void ShowPen()
pascal void GetPen(pt)
    Point *pt;
pascal void GetPenState(pnState)
    PenState *pnState;

```

```

pascal void SetPenState(pnState)
    PenState *pnState;
pascal void PenSize(width,height)
    short width,height;
pascal void PenMode(mode)
    short mode;
pascal void PenPat(pat)
    Pattern *pat;
pascal void PenNormal()
pascal void MoveTo(h,v)
    short h,v;
pascal void Move(dh,dv)
    short dh,dv;
pascal void LineTo(h,v)
    short h,v;
pascal void Line(dh,dv)
    short dh,dv;

/* Text Routines */

pascal void TextFont(font)
    short font;
pascal void TextFace(face)
    Style face;
pascal void TextMode(mode)
    short mode;
pascal void TextSize(size)
    short size;
pascal void SpaceExtra(extra)
    long extra;
pascal void DrawChar(ch)
    short ch;
void DrawString(s)
    char *s;
pascal void DrawText(textBuf,firstByte,byteCount)
    Ptr textBuf;
    short firstByte,byteCount;
pascal short CharWidth(ch)
    short ch;
short StringWidth(s)
    char *s;
pascal short TextWidth(textBuf,firstByte,byteCount)
    Ptr textBuf;
    short firstByte,byteCount;
pascal void GetFontInfo(info)
    FontInfo *info;

/* Drawing in Color */

pascal void ForeColor(color)
    long color;
pascal void BackColor(color)
    long color;
pascal void ColorBit(whichBit)
    short whichBit;

```

```

/* Rectangle Calculations */

pascal void SetRect (r, left, top, right, bottom)
    Rect *r;
    short left, top, right, bottom;
pascal void OffsetRect (r, dh, dv)
    Rect *r;
    short dh, dv;
pascal void InsetRect (r, dh, dv)
    Rect *r;
    short dh, dv;
pascal Boolean SectRect (srcRect1, srcRect2, dstRect)
    Rect *srcRect1, *srcRect2, *dstRect;
pascal void UnionRect (srcRect1, srcRect2, dstRect)
    Rect *srcRect1, *srcRect2, *dstRect;
Boolean PtInRect (pt, r)
    Point *pt;
    Rect *r;
void Pt2Rect (pt1, pt2, dstRect)
    Point *pt1, *pt2;
    Rect *dstRect;
void PtToAngle (r, pt, angle)
    Rect *r;
    Point *pt;
    short *angle;
pascal Boolean EqualRect (rect1, rect2)
    Rect *rect1, *rect2;
pascal Boolean EmptyRect (r)
    Rect *r;

/* Graphical Operations on Rectangles */

pascal void FrameRect (r)
    Rect *r;
pascal void PaintRect (r)
    Rect *r;
pascal void EraseRect (r)
    Rect *r;
pascal void InvertRect (r)
    Rect *r;
pascal void FillRect (r, pat)
    Rect *r;
    Pattern *pat;

/* Oval Routines */

pascal void FrameOval (r)
    Rect *r;
pascal void PaintOval (r)
    Rect *r;
pascal void EraseOval (r)
    Rect *r;
pascal void InvertOval (r)

```

## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

```

    Rect *r;
pascal void FillOval(r,pat)
    Rect *r;
    Pattern *pat;

/* RoundRect Routines */

pascal void FrameRoundRect(r, ovalWidth, ovalHeight)
    Rect *r;
    short ovalWidth, ovalHeight;
pascal void PaintRoundRect(r, ovalWidth, ovalHeight)
    Rect *r;
    short ovalWidth, ovalHeight;
pascal void EraseRoundRect(r, ovalWidth, ovalHeight)
    Rect *r;
    short ovalWidth, ovalHeight;
pascal void InvertRoundRect(r, ovalWidth, ovalHeight)
    Rect *r;
    short ovalWidth, ovalHeight;
pascal void FillRoundRect(r, ovalWidth, ovalHeight, pat)
    Rect *r;
    short ovalWidth, ovalHeight;
    Pattern *pat;

/* Arc Routines */

pascal void FrameArc(r, startAngle, arcAngle)
    Rect *r;
    short startAngle, arcAngle;
pascal void PaintArc(r, startAngle, arcAngle)
    Rect *r;
    short startAngle, arcAngle;
pascal void EraseArc(r, startAngle, arcAngle)
    Rect *r;
    short startAngle, arcAngle;
pascal void InvertArc(r, startAngle, arcAngle)
    Rect *r;
    short startAngle, arcAngle;
pascal void FillArc(r, startAngle, arcAngle, pat)
    Rect *r;
    short startAngle, arcAngle;
    Pattern *pat;

/* Region Calculations */

pascal RgnHandle NewRgn()
pascal void DisposeRgn(rgn)
    RgnHandle rgn;
pascal void CopyRgn(srcRgn, dstRgn)
    RgnHandle srcRgn, dstRgn;
pascal void SetEmptyRgn(rgn)
    RgnHandle rgn;
pascal void SetRectRgn(rgn, left, top, right, bottom)
    RgnHandle rgn;

```

## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

```

    short left,top,right,bottom;
pascal void RectRgn(rgn,r)
    RgnHandle rgn;
    Rect *r;
pascal void OpenRgn()
pascal void CloseRgn(dstRgn)
    RgnHandle dstRgn;
pascal void OffsetRgn(rgn,dh,dv)
    RgnHandle rgn;
    short dh,dv;
pascal void InsetRgn(rgn,dh,dv)
    RgnHandle rgn;
    short dh,dv;
pascal void SectRgn(srcRgnA,srcRgnB,dstRgn)
    RgnHandle srcRgnA,srcRgnB,dstRgn;
pascal void UnionRgn(srcRgnA,srcRgnB,dstRgn)
    RgnHandle srcRgnA,srcRgnB,dstRgn;
pascal void DiffRgn(srcRgnA,srcRgnB,dstRgn)
    RgnHandle srcRgnA,srcRgnB,dstRgn;
pascal void XorRgn(srcRgnA,srcRgnB,dstRgn)
    RgnHandle srcRgnA,srcRgnB,dstRgn;
Boolean PtInRgn(pt,rgn)
    Point *pt;
    RgnHandle rgn;
pascal Boolean RectInRgn(r,rgn)
    Rect *r;
    RgnHandle rgn;
pascal Boolean EqualRgn(rgnA,rgnB)
    RgnHandle rgnA,rgnB;
pascal Boolean EmptyRgn(rgn)
    RgnHandle rgn;

/* Graphical Operations on Regions */

pascal void FrameRgn(rgn)
    RgnHandle rgn;
pascal void PaintRgn(rgn)
    RgnHandle rgn;
pascal void EraseRgn(rgn)
    RgnHandle rgn;
pascal void InvertRgn(rgn)
    RgnHandle rgn;
pascal void FillRgn(rgn,pat)
    RgnHandle rgn;
    Pattern *pat;

/* Graphical Operations on Bit Maps */

pascal void ScrollRect(r,dh,dv,updateRgn)
    Rect *r;
    short dh,dv;
    RgnHandle updateRgn;
pascal void CopyBits(srcBits,dstBits,srcRect,dstRect,mode,maskRgn)
    BitMap *srcBits,*dstBits;
    Rect *srcRect,*dstRect;

```

## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

```

    short mode;
    RgnHandle maskRgn;

/* Picture Routines */

pascal PicHandle OpenPicture(picFrame)
    Rect *picFrame;
pascal void PicComment(kind,dataSize,dataHandle)
    short kind,dataSize;
    Handle dataHandle;
pascal void ClosePicture()
pascal void DrawPicture(myPicture,dstRect)
    PicHandle myPicture;
    Rect *dstRect;
pascal void KillPicture(myPicture)
    PicHandle myPicture;

/* Polygon Calculations */

pascal PolyHandle OpenPoly()
pascal void ClosePoly()
pascal void KillPoly(poly)
    PolyHandle poly;
pascal void OffsetPoly(poly,dh,dv)
    PolyHandle poly;
    short dh,dv;

/* Graphical Operations on Polygons */

pascal void FramePoly(poly)
    PolyHandle poly;
pascal void PaintPoly(poly)
    PolyHandle poly;
pascal void ErasePoly(poly)
    PolyHandle poly;
pascal void InvertPoly(poly)
    PolyHandle poly;
pascal void FillPoly(poly,pat)
    PolyHandle poly;
    Pattern *pat;

/* Point Calculations */

void AddPt(srcPt,dstPt)
    Point *srcPt,*dstPt;
void SubPt(srcPt,dstPt)
    Point *srcPt,*dstPt;
pascal void SetPt(pt,h,v)
    Point *pt;
    short h,v;
Boolean EqualPt(pt1,pt2)
    Point *pt1,*pt2;
pascal void LocalToGlobal(pt)

```

## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

```

    Point *pt;
    pascal void GlobalToLocal(pt)
        Point *pt;

/* Miscellaneous Utility Routines */

    pascal short Random()
    pascal Boolean GetPixel(h,v)
        short h,v;
    void StuffHex(thingPtr,s)
        Ptr thingPtr;
        char *s;
    pascal void ScalePt(pt,srcRect,dstRect)
        Point *pt;
        Rect *srcRect,*dstRect;
    pascal void MapPt(pt,srcRect,dstRect)
        Point *pt;
        Rect *srcRect,*dstRect;
    pascal void MapRect(r,srcRect,dstRect)
        Rect *r,*srcRect,*dstRect;
    pascal void MapRgn(rgn,srcRect,dstRect)
        RgnHandle rgn;
        Rect *srcRect,*dstRect;
    pascal void MapPoly(poly,srcRect,dstRect)
        PolyHandle poly;
        Rect *srcRect,*dstRect;

/* Bottleneck Interface */

    pascal void SetStdProcs(procs)
        QDProcsPtr procs;
    void StdText(byteCount,textAddr,numer,denom)
        short byteCount;
        Ptr textAddr;
        Point *numer,*denom;
    void StdLine(newPt)
        Point *newPt;
    pascal void StdRect(verb,r)
        GrafVerb verb;
        Rect *r;
    pascal void StdRRect(verb,r,ovalWidth,ovalHeight)
        GrafVerb verb;
        Rect *r;
        short ovalWidth,ovalHeight;
    pascal void StdOval(verb,r)
        GrafVerb verb;
        Rect *r;
    pascal void StdArc(verb,r,startAngle,arcAngle)
        GrafVerb verb;
        Rect *r;
        short startAngle,arcAngle;
    pascal void StdPoly(verb,poly)
        GrafVerb verb;
        PolyHandle poly;
    pascal void StdRgn(verb,rgn)

```

## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

```

    GrafVerb verb;
    RgnHandle rgn;
pascal void StdBits(srcBits,srcRect,dstRect,mode,maskRgn)
    BitMap *srcBits;
    Rect *srcRect,*dstRect;
    short mode;
    RgnHandle maskRgn;
pascal void StdComment(kind,dataSize,dataHandle)
    short kind,dataSize;
    Handle dataHandle;
pascal short StdTxMeas(byteCount,textAddr,numer,denom,info)
    short byteCount;
    Ptr textAddr;
    Point *numer,*denom;
    FontInfo *info;
pascal void StdGetPic(dataPtr,byteCount)
    Ptr dataPtr;
    short byteCount;
pascal void StdPutPic(dataPtr,byteCount)
    Ptr dataPtr;
    short byteCount;

```

## USER ROUTINES

```

pascal void MyText(byteCount,textAddr,numer,denom)
    short byteCount;
    Ptr textAddr;
    Point numer,denom;
pascal void MyLine(newPt)
    Point newPt;
pascal void MyRect(verb,r)
    GrafVerb verb;
    Rect *r;
pascal void MyRRect(verb,r,ovWd,ovHt)
    GrafVerb verb;
    Rect *r;
    short ovWd,ovHt;
pascal void MyOval(verb,r)
    GrafVerb verb;
    Rect *r;
pascal void MyArc(verb,r,startAngle,arcAngle)
    GrafVerb verb;
    Rect *r;
    short startAngle,arcAngle;
pascal void MyPoly(verb,poly)
    GrafVerb verb;
    PolyHandle poly;
pascal void MyRgn(verb,rgn)
    GrafVerb verb;
    RgnHandle rgn;
pascal void MyBits(srcBits,srcRect,dstRect,mode,maskRgn)
    BitMap *srcBits;
    Rect *srcRect,*dstRect;
    short mode;
    RgnHandle maskRgn;
pascal void MyComment(kind,dataSize,dataHandle)
    short kind,dataSize;

```



## QUICKDRAW

## Macintosh Interface Libraries

## QUICKDRAW

```
    Handle dataHandle;
    pascal short MyTxMeas(byteCount, textAddr, numer, denom, info)
        short byteCount;
        Ptr textAddr;
        Point *numer, *denom;
        FontInfo *info;
    pascal void MyGetPic(dataPtr, byteCount)
        Ptr dataPtr;
        short byteCount;
    pascal void MyPutPic(dataPtr, byteCount)
        Ptr dataPtr;
        short byteCount;
```

## DESCRIPTION

QuickDraw is the Macintosh graphics package.

Warning: User routines MyText and MyLine are not identical to their counterparts StdText and StdLine. Point parameters to MyText and MyLine are passed by value; the corresponding parameters to StdText and StdLine are passed by reference.

For more detailed information see the QuickDraw chapter of *Inside Macintosh*.

## RESOURCES

## Macintosh Interface Libraries

## RESOURCES

## NAME

resources—Resource Manager

## SYNOPSIS

```

#include <types.h>
#include <resources.h>

/* Resource Attributes */

#define resSysHeap      64      /* set if read into system heap */
#define resPurgeable   32      /* set if purgeable */
#define resLocked      16      /* set if locked */
#define resProtected   8       /* set if protected */
#define resPreload     4       /* set if to be preloaded */
#define resChanged     2       /* set if written to resource file */

/* Error Numbers */

#define resNotFound    (-192)   /* resource not found */
#define resFNotFound   (-193)   /* resource file not found */
#define addResFailed   (-194)   /* AddResource failed */
#define rmvResFailed   (-196)   /* RmveResource failed */

/* Resource File Attributes */

#define mapReadOnly    128     /* set if file is read-only */
#define mapCompact     64     /* set to compact file on update */
#define mapChanged     32     /* set if write map on update */

/* typedef long ResType;  appears in file TYPES */

/* Initialization */

pascal short InitResources()
pascal void RsrcZoneInit()

/* Opening and Closing Resource Files */

void CreateResFile(fileName)
char *fileName;
short OpenResFile(fileName)
char *fileName;
pascal void CloseResFile(refNum)
short refNum;

/* Checking for Errors */

pascal short ResError()

/* Setting the Current Resource File */

pascal short CurResFile()

```

## RESOURCES

## Macintosh Interface Libraries

## RESOURCES

```

pascal short HomeResFile(theResource)
    Handle theResource;
pascal void UseResFile(refNum)
    short refNum;

/* Getting Resource Types */

pascal short CountTypes()
pascal void GetIndType(theType, index)
    ResType *theType;
    short index;

/* Getting and Disposing of Resources */

pascal void SetResLoad(load)
    Boolean load;
pascal short CountResources(theType)
    ResType theType;
pascal Handle GetIndResource(theType, index)
    ResType theType;
    short index;
pascal Handle GetResource(theType, theID)
    ResType theType;
    short theID;
Handle GetNamedResource(theType, name)
    ResType theType;
    char *name;
pascal void LoadResource(theResource)
    Handle theResource;
pascal void ReleaseResource(theResource)
    Handle theResource;
pascal void DetachResource(theResource)
    Handle theResource;

/* Getting Resource Information */

pascal short UniqueID(theType)
    ResType theType;
void GetResInfo(theResource, theID, theType, name)
    Handle theResource;
    short *theID;
    ResType *theType;
    char *name;
pascal short GetResAttrs(theResource)
    Handle theResource;
pascal long SizeResource(theResource)
    Handle theResource;

/* Modifying Resources */

void SetResInfo(theResource, theID, name)
    Handle theResource;
    short theID;

```

## RESOURCES

## Macintosh Interface Libraries

## RESOURCES

```

    char *name;
    pascal void SetResAttrs(theResource, attrs)
        Handle theResource;
        short attrs;
    pascal void ChangedResource(theResource)
        Handle theResource;
    void AddResource(theData, theType, theID, name)
        Handle theData;
        ResType theType;
        short theID;
        char *name;
    pascal void RmveResource(theResource)
        Handle theResource;
    pascal void UpdateResFile(refNum)
        short refNum;
    pascal void WriteResource(theResource)
        Handle theResource;
    pascal void SetResPurge(install)
        Boolean install;

    /* Advanced Routines */

    pascal short GetResFileAttrs(refNum)
        short refNum;
    pascal void SetResFileAttrs(refNum, attrs)
        short refNum;
        short attrs;

```

## DESCRIPTION

The Resource Manager provides access to Macintosh resource files.

ResType may be specified as a character literal (e.g., 'MENU').

For more detailed information see the Resource Manager chapter of *Inside Macintosh*.

## RETRACE

## Macintosh Interface Libraries

## RETRACE

## NAME

retrace—Vertical Retrace Manager

## SYNOPSIS

```

#include <types.h>
#include <retrace.h>

/* error codes */

#define noErr          0          /* no error */
#define qErr          (-1)       /* task entry isn't in the queue */
#define vTypErr       (-2)       /* qType field isn't vType */

typedef struct VBLTask {
    struct QElem *qLink;          /* next queue entry */
    short        qType;          /* unique id for validity check */
    ProcPtr      vblAddr;        /* address of service routine */
    short        vblCount;       /* count field for timeout */
    short        vblPhase;       /* phase to allow synchronization */
} VBLTask;

OSErr VInstall(vblTaskPtr)
    QElemPtr vblTaskPtr;
OSErr VRemove(vblTaskPtr)
    QElemPtr vblTaskPtr;
struct QHdr *GetVBLQHdr()

```

## DESCRIPTION

The Vertical Retrace Manager schedules and performs recurrent tasks during vertical retrace interrupts.

For more detailed information see the Vertical Retrace Manager chapter of *Inside Macintosh*.

SANE

Macintosh Interface Libraries

SANE

## NAME

sane—SANE Numerics

## SYNOPSIS

```

#include <sane.h>

/* Decimal Representation Constants */

#define SIGDIGLEN      20    /* significant decimal digits */
#define DECSTROUTLEN  80    /* max length for decimal string */
/*      output      */

/* Decimal Formatting Styles */

#define FLOATDECIMAL   0
#define FIXEDDECIMAL  1

/* Exceptions */

#define INVALID        1
#define UNDERFLOW     2
#define OVERFLOW      4
#define DIVBYZERO     8
#define INEXACT       16

/* Ordering Relations */

#define GREATERTHAN   0
#define LESSTHAN      1
#define EQUALTO       2
#define UNORDERED    3

/* Inquiry Classes */

#define SNAN           0
#define QNAN           1
#define INFINITE       2
#define ZERONUM        3
#define NORMALNUM      4
#define DENORMALNUM    5

/* Rounding Directions */

#define TONEAREST      0
#define UPWARD         1
#define DOWNWARD       2
#define TOWARDZERO     3

/* Rounding Precisions */

#define EXTPRECISION   0
#define DBLPRECISION   1
#define FLOATPRECISION 2

typedef short exception;    /* sum of INVALID...INEXACT */

```

SANE

Macintosh Interface Libraries

SANE

```

typedef short relop;          /* relational operator          */
typedef short numclass;      /* inquiry class              */
typedef short rounddir;     /* rounding direction         */
typedef short roundpre;     /* rounding precision         */
typedef short environment;

typedef struct decimal {
    char sgn, unused;        /* sign 0 for +, 1 for -     */
    short exp;              /* decimal exponent          */
    struct {unsigned char length, text[SIGDIGLEN], unused} sig;
                             /* significant digits        */
} decimal;

typedef struct decform {
    char style, unused;     /* FLOATDECIMAL or FIXEDDECIMAL */
    short digits;
} decform;

typedef void (*haltvector)();

/* Conversions between Binary and Decimal Records */

void num2dec(f,x,d)         /* d <-- x, according to format f */
    decform *f;
    extended x;
    decimal *d;
extended dec2num(d)         /* returns d as extended          */
    decimal *d;

/* Conversions between Decimal Records and ASCII Strings */

void dec2str(f,d,s)         /* s <-- d, according to format f */
    decform *f;
    decimal *d;
    char *s;
void str2dec(s,ix,d,vp)     /* on input ix is starting index into s, on
    char *s;                /* output ix is one greater than index of last*/
    short *ix,*vp;         /* character of longest numeric substring;
    decimal *d;            /* boolean vp = "s begining at given ix is a
                             /* valid numeric string or a valid prefix of
                             /* some numeric string"
*/

/* Arithmetic, Auxiliary, and Elementary Functions */

extended fabs(x)           /* absolute value              */
    extended x;
extended remainder(x,y,quo) /* IEEE remainder; quo <-- 7 low order
    extended x,y;         /* bits of integer quotient x/y,
    short *quo;           /* -127 <= quo <= 127
    extended sqrt(x)      /* square root                 */
    extended x;

```

## SANE

## Macintosh Interface Libraries

## SANE

```

extended rint(x)          /* round to integral value      */
  extended x;
extended scalb(n,x)       /* binary scale: x * 2^n;        */
  short n;
  extended x;
extended logb(x)          /* binary log:                   */
  extended x;             /* binary exponent of normalized x */
extended copysign(x,y)    /* y with sign of x              */
  extended x,y;
extended nextfloat(x,y)  /* next float representation after */
  extended x,y;          /* (float) x in direction of (float) y */
extended nextdouble(x,y) /* next double representation after */
  extended x,y;          /* (double) x in direction of (double) y */
extended nextextended(x,y) /* next extended representation after x */
  extended x,y;          /* in direction of y                */
extended log2(x)          /* base-2 log                    */
  extended x;
extended log(x)           /* base-e log                    */
  extended x;
extended log1(x)          /* log(1 + x)                    */
  extended x;
extended exp2(x)          /* base-2 exponential            */
  extended x;
extended exp(x)           /* base-e exponential            */
  extended x;
extended exp1(x)          /* exp(x) - 1                    */
  extended x;
extended power(x,y)       /* general exponential: x ^ y    */
  extended x,y;
extended ipower(x,i)      /* integer exponential: x ^ i    */
  extended x;
  short i;
extended compound(r,n)    /* compound: (1 + r) ^ n         */
  extended r,n;
extended annuity(r,n)     /* annuity: (1 - (1 + r) ^ (-n)) / r */
  extended r,n;
extended tan(x)           /* tangent                        */
  extended x;
extended sin(x)           /* sine                          */
  extended x;
extended cos(x)           /* cosine                        */
  extended x;
extended atan(x)          /* arctangent                    */
  extended x;
extended randomx(x)       /* returns next random number; updates x; */
  extended *x;           /* x integral, 1 <= x <= 2^31 - 2 */

/* Inquiry Routines */

numclass classfloat(x)    /* class of (float) x            */
  extended x;
numclass classdouble(x)  /* class of (double) x          */
  extended x;
numclass classcomp(x)     /* class of (comp) x            */
  extended x;
numclass classextended(x) /* class of x                    */
  extended x;

```



SANE

Macintosh Interface Libraries

SANE

```

long signnum(x)          /* returns 0 for +, 1 for      */
    extended x;          /*                               */

/* Environment Access Routines */
/* An exception variable encodes the exceptions
   whose sum is its value */

void setexception(e,s)   /* clr's e flags if s is 0, sets e flags */
    exception e;        /* otherwise; may cause halt          */
    long s;

long testexception(e)    /* returns 1 if any e flag is set,      */
    exception e;        /* returns 0 otherwise                 */

void sethalt(e,s)       /* disables e halts if s is 0,        */
    exception e;        /* enables e halts otherwise          */
    long s;

long testhalt(e)        /* returns 1 if any e halt is enabled,  */
    exception e;        /* returns 0 otherwise                 */

void setround(r)        /* sets rounding direction to r        */
    rounddir r;

rounddir getround()     /* returns rounding direction          */

void setprecision(p)    /* sets rounding precision to p        */
    roundpre p;

roundpre getprecision() /* returns rounding precision          */

void setenvironment(e)  /* sets environment to e               */
    environment e;

void getenvironment(e)  /* e <-- environment                  */
    environment *e;

void procentry(e)       /* e <-- environment;                 */
    environment *e;    /* environment <-- IEEE default      */

void procexit(e)        /* temp <--exceptions; environment <-- e; */
    environment e;     /* signals exceptions in temp         */

haltvector gethaltvector() /* returns halt vector                */

void sethaltvector(v)   /* halt vector <-- v                  */
    haltvector v;

/* Comparision Routine */

relop relation(x,y)     /* returns relation such that          */
    extended x,y;      /* "x relation y" is true             */

/* NaNs and Special Constants */

extended nan(c)         /* returns NaN with code c            */
    unsigned char c;

extended inf()          /* infinity                            */

extended pi()           /* pi                                   */

```

## DESCRIPTION

These routines together with Apple's C language fully support the Standard Apple Numeric Environment (SANE). They comprise a scrupulously conforming implementation of extended-precision IEEE Standard 754 floating-point arithmetic.

The Standard Apple Numeric Environment is documented in the *Apple Numerics Manual*.

## SCRAP

## Macintosh Interface Libraries

## SCRAP

## NAME

scrap—Scrap Manager

## SYNOPSIS

```

#include <types.h>
#include <scrap.h>

#define noScrapErr    (-100)    /* desk scrap isn't initialized */
#define noTypeError  (-102)    /* no data of the requested type */

typedef struct ScrapStuff {
    long    scrapSize;
    Handle  scrapHandle;
    short   scrapCount;
    short   scrapState;
    StringPtr scrapName;
} ScrapStuff, *PScrapStuff;

/* Getting Desk Scrap Information */
pascal PScrapStuff InfoScrap()

/* Keeping the Desk Scrap on the Disk */
pascal long UnloadScrap()
pascal long LoadScrap()

/* Reading from the Desk Scrap */
pascal long GetScrap(hDest,theType,offset)
    Handle hDest;
    ResType theType;
    long *offset;

/* Writing to the Desk Scrap */
pascal long ZeroScrap()
pascal long PutScrap(length,theType,source)
    long length;
    ResType theType;
    Ptr source;

```

## DESCRIPTION

The Scrap Manager provides a mechanism for cutting and pasting between applications and desk accessories.

For more detailed information see the Scrap Manager chapter of *Inside Macintosh*.

## SEGLOAD

## Macintosh Interface Libraries

## SEGLOAD

## NAME

segload—Segment Loader

## SYNOPSIS

```
#include <types.h>
#include <segload.h>

/* Message returned by CountAppFiles */

#define appOpen      0      /* Open the document(s) */
#define appPrint     1      /* Print the document(s) */

typedef struct AppFile {
    short      vRefNum;      /* volume reference number */
    OSType     fType;        /* file type */
    short      versNum;      /* version number */
    Str255     fName;        /* file name */
} AppFile;

pascal void UnloadSeg(routineAddr)
    Ptr routineAddr;
void CountAppFiles(message, count)
    short *message, *count;
void GetAppFiles(index, theFile)
    short index;
    AppFile *theFile;
void ClrAppFiles(index)
    short index;
void GetAppParms(apName, apRefNum, apParam)
    char *apName;
    short *apRefNum;
    Handle *apParam;
pascal void ExitToShell()
```

## DESCRIPTION

The Segment Loader is the part of the Macintosh Operating System that lets you divide your application into several parts and have only some of them in memory at a time. When an application starts up, the Segment Loader also provides it with a list of files to open or print.

For more detailed information see the Segment Loader chapter of *Inside Macintosh*.

SERIAL

Macintosh Interface Libraries

SERIAL

## NAME

serial—Serial Drivers

## SYNOPSIS

```
#include <types.h>
#include <serial.h>
```

```
/* Driver reset information */
```

```
#define baud300      380    /* 300 baud */
#define baud600      189    /* 600 baud */
#define baud1200     94     /* 1200 baud */
#define baud1800     62     /* 1800 baud */
#define baud2400     46     /* 2400 baud */
#define baud3600     30     /* 3600 baud */
#define baud4800     22     /* 4800 baud */
#define baud7200     14     /* 7200 baud */
#define baud9600     10     /* 9600 baud */
#define baud19200    4      /* 19200 baud */
#define baud57600    0      /* 57600 baud */
#define stop10       16384  /* 1 stop bit */
#define stop15       (-32768) /* 1.5 stop bits */
#define stop20       (-16384) /* 2 stop bits */
#define noParity      0      /* no parity */
#define oddParity     4096   /* odd parity */
#define evenParity    12288  /* even parity */
#define data5         0      /* 5 data bits */
#define data6         2048   /* 6 data bits */
#define data7         1024   /* 7 data bits */
#define data8         3072   /* 8 data bits */
```

```
/* Masks for errors */
```

```
#define swOverrunErr 1      /* set if software overrun error */
#define parityErr    16     /* set if parity error */
#define hwOverrunErr 32     /* set if hardware overrun error */
#define framingErr   64     /* set if framing error */
```

```
/* Masks for changes that cause events to be posted */
```

```
#define ctsEvent     32     /* set if CTS change will cause event */
                          /* to be posted */
#define breakEvent   128    /* set if break status change will */
                          /* cause event to be posted */
```

```
/* Indication that an XOFF character was sent */
```

```
#define xOffWasSent 0x80   /* XOFF character was sent */
```

```
/* Result codes */
```

```
#define noErr        0     /* no error */
```

SERIAL

Macintosh Interlace Libraries

SERIAL

```

#define openErr      ( -23)  /* Open of RAM Serial Driver failed */

typedef enum {
    sPortA,                /* modem port */
    sPortB                 /* printer port */
} SPortSel;

typedef struct SerShk {
    char          fXOn;    /* XON/XOFF output flow control flag */
    char          fCTS;   /* CTS hardware handshake flag */
    unsigned char xOn;    /* XOn character */
    unsigned char xOff;   /* XOff character */
    char          errs;   /* errors that cause abort */
    char          evts;   /* status changes that cause events */
    char          fInX;   /* XOn/XOff input flow control flag */
    char          null;   /* not used */
} SerShk;

typedef struct SerStaRec {
    char          cumErrs; /* cumulative errors */
    char          xOffSent; /* XOff sent as input flow control */
    char          rdPend;  /* read pending flag */
    char          wrPend;  /* write pending flag */
    char          ctsHold; /* CTS flow control hold flag */
    char          xOffHold; /* XOff received as output flow control */
} SerStaRec;

/* Opening and Closing the RAM Serial Driver */

OSErr RAMSDOpen(whichPort)
    SPortSel whichPort;
void RAMSDClose(whichPort)
    SPortSel whichPort;

/* Changing Serial Driver Information */

OSErr SerReset(refNum,serConfig)
    short refNum,serConfig;
OSErr SerSetBuf(refNum,serBPtr,serBLen)
    short refNum;
    Ptr serBPtr;
    short serBLen;
OSErr SerHShake(refNum,flags);
    short refNum;
    SerShk *flags;
OSErr SerSetBrk(refNum)
    short refNum;
OSErr SerClrBrk(refNum)
    short refNum;

/* Getting Serial Driver Information */

```

**SERIAL**

**Macintosh Interface Libraries**

**SERIAL**

```
OSErr SerGetBuf (refNum, count)
    short refNum;
    long *count;
OSErr SerStatus (refNum, serSta)
    short refNum;
    SerStaRec *serSta;
```

**DESCRIPTION**

The RAM Serial Driver and the ROM Serial Driver are Macintosh device drivers for handling asynchronous serial communication between a Macintosh application and serial devices.

For more detailed information see the Serial Drivers chapter of *Inside Macintosh*.

## SOUND

## Macintosh Interface Libraries

## SOUND

## NAME

sound—Sound Driver

## SYNOPSIS

```

#include <types.h>
#include <sound.h>

/* Mode values for synthesizers */

#define swMode      (-1)    /* square-wave synthesizer */
#define ftMode      1      /* four-tone synthesizer */
#define ffMode      0      /* free-form synthesizer */

/* Free-Form synthesizer */
typedef unsigned char FreeWave[30001];

typedef struct FFSynthRec {
    short      mode;        /* always ffMode */
    Fixed      count;       /* "sizing" factor */
    FreeWave   waveBytes;   /* waveform description */
} FFSynthRec, *FFSynthPtr;

/* Square-Wave synthesizer */
typedef struct Tone {
    short      count;       /* frequency */
    short      amplitude;   /* amplitude, 0-255 */
    short      duration;    /* duration in ticks */
} Tone;

typedef Tone Tones[5001];

typedef struct SWSynthRec {
    short      mode;        /* always swMode */
    Tones      triplets;    /* sounds */
} SWSynthRec, *SWSynthPtr;

/* Four-Tone Synthesizer */
typedef unsigned char Wave[256];

typedef Wave *WavePtr;

typedef struct FTSoundRec {
    short      duration;    /* duration in ticks */
    Fixed      sound1Rate;  /* tone 1 cycle rate */
    long       sound1Phase; /* tone 1 byte offset */
    Fixed      sound2Rate;  /* tone 2 cycle rate */
    long       sound2Phase; /* tone 2 byte offset */
    Fixed      sound3Rate;  /* tone 3 cycle rate */
    long       sound3Phase; /* tone 3 byte offset */
    Fixed      sound4Rate;  /* tone 4 cycle rate */
}

```

## SOUND

## Macintosh Interface Libraries

## SOUND

```

    long      sound4Phase;    /* tone 4 byte offset */
    WavePtr   sound1Wave;    /* tone 1 wave form */
    WavePtr   sound2Wave;    /* tone 2 wave form */
    WavePtr   sound3Wave;    /* tone 3 wave form */
    WavePtr   sound4Wave;    /* tone 4 wave form */
} FTSoundRec, *FTSndRecPtr;

typedef struct FTSynthRec {
    short     mode;          /* always ftMode */
    FTSndRecPtr sndRec;    /* tones to play */
} FTSynthRec, *FTSynthPtr;

void StartSound(synthRec,numBytes,completionRtn)
    Ptr synthRec;
    long numBytes;
    ProcPtr completionRtn;
void StopSound()
Boolean SoundDone()
void GetSoundVol(level)
    short *level;
void SetSoundVol(level)
    short level

```

## DESCRIPTION

The Sound Driver is a Macintosh device driver for handling sound and music generation in a Macintosh application.

For more detailed information see the Sound Driver chapter of *Inside Macintosh*.



## STRINGS

## Macintosh Interface Libraries

## STRINGS

## NAME

strings—string conversions

## SYNOPSIS

```
#include <types.h>
#include <strings.h>
```

```
String(0) *c2pstr(s)
    char *s;
char *p2cstr(s)
    String(0) *s;
```

## DESCRIPTION

*C2pstr* converts *s* from a C string to a Pascal string. *P2cstr* converts *s* from a Pascal string to a C string. Both conversions are done in place. For convenience, *c2pstr* and *p2cstr* return *s* as their function result. Both functions will accept nil as their parameter and do nothing.

Pascal strings begin with a length byte. C strings are terminated by a zero byte. The macro *String* is defined in file *types.h*.

TEXTEDIT

Macintosh Interface Libraries

TEXTEDIT

## NAME

textedit—TextEdit

## SYNOPSIS

```

#include <types.h>
#include <textedit.h>

#define teJustLeft      0
#define teJustCenter   1
#define teJustRight    (-1)

typedef char Chars[32001];
typedef Chars *CharsPtr, **CharsHandle;

typedef struct Terec {
    Rect    destRect;          /* destination rectangle */
    Rect    viewRect;         /* view rectangle */
    Rect    selRect;          /* select rectangle */
    short   lineHeight;       /* current font lineHeight */
    short   fontAscent;       /* current font ascent */
    Point   selPoint;         /* selection point (mouseLoc) */
    short   selStart;         /* selection start */
    short   selEnd;           /* selection end */
    short   active;           /* != 0 if active */
    ProcPtr wordBreak;        /* word break routine */
    ProcPtr clickLoop;        /* click loop routine */
    long    clickTime;        /* time of first click */
    short   clickLoc;         /* char. location of click */
    long    caretTime;        /* time for next caret blink */
    short   caretState;       /* on/active booleans */
    short   just;             /* fill style */
    short   teLength;         /* length of text below */
    Handle  hText;            /* handle to actual text */
    short   recalBack;        /* != 0 if recal in background */
    short   recalLines;       /* line being recalculated */
    short   clickStuff;       /* click stuff (internal) */
    short   crOnly;           /* set to -1 if CR line breaks only */
    short   txFont;           /* text Font */
    Style   txFace;           /* text Face */
    short   txMode;           /* text Mode */
    short   txSize;           /* text Size */
    struct GrafPort *inPort;  /* GrafPort */
    ProcPtr highHook;         /* highlighting hook */
    ProcPtr caretHook;        /* highlighting hook */
    short   nLines;           /* number of lines */
    short   lineStarts[16001]; /* line starts */
} Terec, *TEPtr, **TEHandle;

/* Initialization and Allocation */

pascal void TEInit()
pascal TEHandle TENew(destRect,viewRect)
    Rect *destRect, *viewRect;
pascal void TEdispose(h)
    TEHandle h;

```

## TEXTEDIT

## Macintosh Interface Libraries

## TEXTEDIT

```

/* Accessing Text */

pascal void TEText(text, length, hTE)
    Ptr text;
    long length;
    TEHandle hTE;
pascal CharHandle TEGetText(hTE)
    TEHandle hTE;

/* Insertion Point and Selection Range */

pascal void TEIdle(hTE)
    TEHandle hTE;
void TEClick(pt, extend, hTE)
    Point *pt;
    Boolean extend;
    TEHandle hTE;
pascal void TETextSelect(selStart, selEnd, hTE)
    long selStart;
    long selEnd;
    TEHandle hTE;
pascal void TEActivate(hTE)
    TEHandle hTE;
pascal void TEDeactivate(hTE)
    TEHandle hTE;

/* Editing */

pascal void TEKey(key, hTE)
    short key;
    TEHandle hTE;
pascal void TECut(hTE)
    TEHandle hTE;
pascal void TECopy(hTE)
    TEHandle hTE;
pascal void TEPaste(hTE)
    TEHandle hTE;
pascal void TEDelete(hTE)
    TEHandle hTE;
pascal void TEInsert(text, length, hTE)
    Ptr text;
    long length;
    TEHandle hTE;

/* Text Display and Scrolling */

pascal void TETextJust(just, hTE)
    short just;
    TEHandle hTE;
pascal void TEUpdate(rUpdate, hTE)
    Rect *rUpdate;
    TEHandle hTE;
pascal void TextBox(text, length, box, just)
    Ptr text;
    long length;
    Rect *box;
    short just;

```

TEXTEDIT

Macintosh Interface Libraries

TEXTEDIT

```

pascal void TESScroll(dh,dv,hTE)
    short dh;
    short dv;
    TEHandle hTE;

/* Scrap Information */

OSErr TEFFromScrap()
OSErr TEToScrap()
Handle TEScrapHandle()
long TEGetScrapLen()
void TESSetScrapLen(length)
    long length;

/* Advanced Routines */

void SetWordBreak(wBrkProc,hTE)
    ProcPtr wBrkProc;
    TEHandle hTE;
void SetClikLoop(clikProc,hTE)
    ProcPtr clikProc;
    TEHandle hTE;
pascal void TECalText(hTE)
    TEHandle hTE;

```

## USER ROUTINES

```

Pascal Boolean MyWordBreak(text,charPos)
    Ptr text;
    short charPos;
Pascal Boolean MyClikLoop()

```

## DESCRIPTION

The TextEdit package provides basic text formatting and editing

For more detailed information see the TextEdit chapter of *Inside Macintosh*.

## NOTE

The user routines *highHook* and *caretHook* are called with register conventions and therefore can't be C routines.

## TOOLUTILS

## Macintosh Interface Libraries

## TOOLUTILS

## NAME

toolutils—Toolbox Utilities

## SYNOPSIS

```
#include <types.h>
#include <toolutils.h>

#define sysPatListID 0 /* resource ID of standard pattern list */

#define iBeamCursor 1 /* text selection */
#define crossCursor 2 /* drawing graphics */
#define plusCursor 3 /* cell selection */
#define watchCursor 4 /* indicating long delay */

typedef struct Int64Bit {
    long hiLong;
    long loLong;
} Int64Bit;

typedef struct Cursor *CursPtr, **CursHandle;
typedef struct Pattern *PatPtr, **PatHandle;

/* Fixed-Point Arithmetic */

pascal Fixed FixRatio( numer, denom)
    short numer, denom;
pascal Fixed FixMul( a, b)
    Fixed a, b;
pascal short FixRound( x)
    Fixed x;

/* String Manipulation */

StringHandle NewString( theString)
    char *theString;
void SetString( h, theString)
    StringHandle h;
    char *theString;
pascal StringHandle GetString( stringID)
    short stringID;
void GetIndString( theString, strListID, index)
    char *theString;
    short strListID;
    short index;

/* Byte Manipulation */

pascal long Munger( h, offset, ptr1, length1, ptr2, length2)
    Handle h;
    long offset;
    Ptr ptr1;
    long length1;
    Ptr ptr2;
    long length2;
pascal void PackBits( srcPtr, dstPtr, srcBytes)
```

## TOOLUTILS

## Macintosh Interface Libraries

## TOOLUTILS

```

    Ptr *srcPtr;
    Ptr *dstPtr;
    short srcBytes;
pascal void UnpackBits (srcPtr, dstPtr, dstBytes)
    Ptr *srcPtr;
    Ptr *dstPtr;
    short dstBytes;

/* Bit Manipulation */

pascal Boolean BitTst (bytePtr, bitNum)
    Ptr bytePtr;
    long bitNum;
pascal void BitSet (bytePtr, bitNum)
    Ptr bytePtr;
    long bitNum;
pascal void BitClr (bytePtr, bitNum)
    Ptr bytePtr;
    long bitNum;

/* Logical Operations */

pascal long BitAnd (value1, value2)
    long value1, value2;
pascal long BitOr (value1, value2)
    long value1, value2;
pascal long BitXor (value1, value2)
    long value1, value2;
pascal long BitNot (value)
    long value;
pascal long BitShift (value, count)
    long value;
    short count;

/* Other Operations on Ints */

pascal short HiWord (x)
    long x;
pascal short LoWord (x)
    long x;
pascal void LongMul (a, b, dest)
    long a, b;
    Int64Bit *dest;

/* Graphics Utilities */

void ScreenRes (scrnHRes, scrnVRes)
    short *scrnHRes;
    short *scrnVRes;
pascal Handle GetIcon (iconID)
    short iconID;
pascal void PlotIcon (theRect, theIcon)
    Rect *theRect;
    Handle theIcon;
pascal PatHandle GetPattern (patID)
    short patID;
void GetIndPattern (thePattern, patListID, index)

```

## TOOLUTILS

## Macintosh Interface Libraries

## TOOLUTILS

```

    struct Pattern *thePattern;
    short patListID;
    short index;
pascal CursHandle GetCursor(cursorID)
    short cursorID;
void ShieldCursor(shieldRect,offsetPt)
    Rect *shieldRect;
    Point *offsetPt;
pascal struct Picture **GetPicture(picID)
    short picID;

/* Miscellaneous Utilities */

long DeltaPoint(ptA,ptB)
    Point *ptA;
    Point *ptB;
pascal Fixed SlopeFromAngle(angle)
    short angle;
pascal short AngleFromSlope(slope)
    Fixed slope;

```

## DESCRIPTION

The Toolbox Utilities provide fixed-point arithmetic; string, byte, and bit manipulation; logical operations; and some graphics utilities.

**Warning:** *NewString* and *GetString* return handles to Pascal strings. *SetString* takes a C string as its parameter and converts it to a Pascal string before storing it in the memory location referred to by the string handle.

For more detailed information see the ToolBox Utilities chapter of *Inside Macintosh*.

## TYPES

## Macintosh Interface Libraries

## TYPES

## NAME

types—common defines and types

## SYNOPSIS

```
#include <types.h>

#define nil 0
#define NULL 0

typedef enum {false,true} Boolean;
typedef char *Ptr;
typedef Ptr *Handle;
typedef long (*ProcPtr)();
typedef ProcPtr *ProcHandle;
typedef long Fixed;
typedef unsigned long ResType;
typedef long OSType;
typedef short OSErr;
typedef short Style;
typedef struct Point {
    short    v;
    short    h;
} Point;
typedef struct Rect {
    short    top;
    short    left;
    short    bottom;
    short    right;
} Rect;

#define String(size) struct {\
    unsigned char length; unsigned char text[size];}
typedef String(255) Str255, *StringPtr, **StringHandle;
```

## DESCRIPTION

These defines and types are shared by several Macintosh libraries.

The define *String* approximates Pascal strings. It creates a struct, not an array. Remember to use `&` when passing structs as parameters.



## WINDOWS

## Macintosh Interface Libraries

## WINDOWS

## NAME

windows—Window Manager

## SYNOPSIS

```

#include <types.h>
#include <quickdraw.h>
#include <windows.h>

/* Window Definition Procedure IDs */

#define documentProc    0
#define dBoxProc       1
#define plainDBox      2
#define altDBoxProc    3
#define noGrowDocProc  4
#define rDocProc       16

/* Types of Windows */

#define dialogKind      2
#define userKind        8

/* FindWindow Result Codes */

#define inDesk          0
#define inMenuBar      1
#define inSysWindow    2
#define inContent      3
#define inDrag          4
#define inGrow         5
#define inGoAway       6

/* Axis Constraints for DragGrayRgn */

#define noConstraint    0
#define hAxisOnly      1
#define vAxisOnly      2

/* Messages to window definition functions */

#define wDraw           0
#define wHit            1
#define wCalcRgns      2
#define wNew            3
#define wDispose       4
#define wGrow          5
#define wDrawGIcon     6

/* defProc Hit Test Codes */

#define wNoHit          0
#define wInContent     1
#define wInDrag        2
#define wInGrow        3
#define wInGoAway     4

```

## WINDOWS

## Macintosh Interface Libraries

## WINDOWS

```

#define deskPatID      16

typedef GrafPtr WindowPtr;

typedef struct WindowRecord {
    GrafPort      port;
    short         windowKind;
    Boolean       visible;
    Boolean       hilited;
    Boolean       goAwayFlag;
    Boolean       spareFlag;
    RgnHandle     strucRgn;
    RgnHandle     contRgn;
    RgnHandle     updateRgn;
    ProcHandle    windowDefProc;
    Handle        dataHandle;
    StringHandle  titleHandle;
    short         titleWidth;
    struct ControlRecord **controlList;
    struct WindowRecord *nextWindow;
    PicHandle     windowPic;
    long          refCon;
} WindowRecord, *WindowPeek;

/* Initialization and Allocation */

pascal void InitWindows()
pascal void GetWMgrPort(wPort)
    GrafPtr *wPort;
WindowPtr NewWindow(wStorage, boundsRect, title, visible, procID, behind,
    goAwayFlag, refCon)
    Ptr wStorage;
    Rect *boundsRect;
    char *title;
    Boolean visible;
    short procID;
    WindowPtr behind;
    Boolean goAwayFlag;
    long refCon;
pascal WindowPtr GetNewWindow(windowID, wStorage, behind)
    short windowID;
    Ptr wStorage;
    WindowPtr behind;
pascal void CloseWindow(theWindow)
    WindowPtr theWindow;
pascal void DisposeWindow(theWindow)
    WindowPtr theWindow;

/* Window Display */

void SetWTitle(theWindow, title)
    WindowPtr theWindow;
    char *title;
void GetWTitle(theWindow, title)
    WindowPtr theWindow;
    char *title;

```

## WINDOWS

## Macintosh Interface Libraries

## WINDOWS

```

pascal void SelectWindow(theWindow)
    WindowPtr theWindow;
pascal void HideWindow(theWindow)
    WindowPtr theWindow;
pascal void ShowWindow(theWindow)
    WindowPtr theWindow;
pascal void ShowHide(theWindow, showFlag)
    WindowPtr theWindow;
    Boolean showFlag;
pascal void HiliteWindow(theWindow, fHiLite)
    WindowPtr theWindow;
    Boolean fHiLite;
pascal void BringToFront(theWindow)
    WindowPtr theWindow;
pascal void SendBehind(theWindow, behindWindow)
    WindowPtr theWindow;
    WindowPtr behindWindow;
pascal WindowPtr FrontWindow()
pascal void DrawGrowIcon(theWindow)
    WindowPtr theWindow;

/* Mouse Location */

short FindWindow(thePt, theWindow)
    Point *thePt;
    WindowPtr *theWindow;
Boolean TrackGoAway(theWindow, thePt)
    WindowPtr theWindow;
    Point *thePt;

/* Window Movement and Sizing */

pascal void MoveWindow(theWindow, hGlobal, vGlobal, front)
    WindowPtr theWindow;
    short hGlobal, vGlobal;
    Boolean front;
void DragWindow(theWindow, startPt, boundsRect)
    WindowPtr theWindow;
    Point *startPt;
    Rect *boundsRect;
long GrowWindow(theWindow, startPt, sizeRect)
    WindowPtr theWindow;
    Point *startPt;
    Rect *sizeRect;
pascal void SizeWindow(theWindow, w, h, fUpdate)
    WindowPtr theWindow;
    short w, h;
    Boolean fUpdate;

/* Update Region Maintenance */

pascal void InvalRect(badRect)
    Rect *badRect;
pascal void InvalRgn(badRgn)
    RgnHandle badRgn;
pascal void ValidRect(goodRect)
    Rect *goodRect;

```

## WINDOWS

## Macintosh Interface Libraries

## WINDOWS

```

pascal void ValidRgn(goodRgn)
    RgnHandle goodRgn;
pascal void BeginUpdate(theWindow)
    WindowPtr theWindow;
pascal void EndUpdate(theWindow)
    WindowPtr theWindow;

/* Miscellaneous Utilities */

pascal void SetWRefCon(theWindow,data)
    WindowPtr theWindow;
    long data;
pascal long GetWRefCon(theWindow)
    WindowPtr theWindow;
pascal void SetWindowPic(theWindow,pic)
    WindowPtr theWindow;
    PicHandle pic;
pascal PicHandle GetWindowPic(theWindow)
    WindowPtr theWindow;
long PinRect(theRect,thePt)
    Rect *theRect;
    Point *thePt;
long DragGrayRgn(theRgn,startPt,limitRect,slopRect,axis,actionProc)
    RgnHandle theRgn;
    Point *startPt;
    Rect *limitRect;
    Rect *slopRect;
    short axis;
    ProcPtr actionProc;

/* Low-Level Routines */

pascal Boolean CheckUpdate(theEvent)
    struct EventRecord *theEvent;
pascal void ClipAbove(window)
    WindowPeek window;
pascal void SaveOld(window)
    WindowPeek window;
pascal void DrawNew(window,update)
    WindowPeek window;
    Boolean update;
pascal void PaintOne(window,clobberedRgn)
    WindowPeek window;
    RgnHandle clobberedRgn;
pascal void PaintBehind(startWindow,clobberedRgn)
    WindowPeek startWindow;
    RgnHandle clobberedRgn;
pascal void CalcVis(window)
    WindowPeek window;
pascal void CalcVisBehind(startWindow,clobberedRgn)
    WindowPeek startWindow;
    RgnHandle clobberedRgn;

```

## USER ROUTINES

```

pascal MyAction()

```

WINDOWS

Macintosh Interface Libraries

WINDOWS

```
pascal long MyWindow(varCode,theWindow,message,param)
  short varCode;
  WindowPtr theWindow;
  short message;
  long param;
```

DESCRIPTION

The Window Manager provides routines for creating and manipulating windows.

For more detailed information see the Window Manager chapter of *Inside Macintosh*.

## **Lisa Workshop C User's Guide**

### **8. Library Index**

The Library Index contains an index entry for all the defines, types, enumeration literals, global variables, and functions defined in the Standard C Library section and the Macintosh Interface Libraries section. These sections are organized alphabetically by library header.

Column 1 contains an alphabetical list of the index entries.

Column 2 specifies the type of declaration (for example, literal) for the index entry.

Column 3 contains the library header under which documentation for the index entry can be found in Section 6 or 7. If column 3 contains "(C)" following the library header—for example, abs(C)—look in the Standard C Library section. Otherwise, look in the Macintosh Interface Libraries section.

**Lisa Workshop C User's Guide**

**LIBRARY INDEX**

<u>Identifier</u>	<u>Type</u>	<u>Library</u>			
abbrevDate	literal	packages	baud600	define	serial
abortErr	define	devices	baud7200	define	serial
abs	function	abs(C)	baud9600	define	serial
acos	function	trig(C)	bdConv	define	packages
activateEvt	define	events	bDevCItch	define	printing
activeFlag	define	events	bDevLaser	define	printing
activMask	define	events	bdNamErr	define	files
AddDrive	function	files	bdDraftLoop	define	printing
AddPt	function	quickdraw	BeginUpdate	function	windows
addResFailed	define	resources	BitAnd	function	toolutils
AddResMenu	function	menus	BitClr	function	toolutils
AddResource	function	resources	BitMap	type	quickdraw
Alert	function	dialogs	BitNot	function	toolutils
AlertTemplate	type	dialogs	BitOr	function	toolutils
AlertTfHndl	type	dialogs	Bits16	type	quickdraw
AlertTPtr	type	dialogs	BitSet	function	toolutils
Allocate	function	files	BitShift	function	toolutils
alphaLock	define	events	BitTst	function	toolutils
altDBoxProc	define	windows	BitXor	function	toolutils
AngleFromSlope	function	toolutils	blackBit	define	quickdraw
annuity	function	sane	blackColor	define	quickdraw
applEvt	define	events	BlockMove	function	memory
applMask	define	events	blueBit	define	quickdraw
app2Evt	define	events	blueColor	define	quickdraw
app2Mask	define	events	bold	define	quickdraw
app3Evt	define	events	Boolean	type	types
app3Mask	define	events	breakEvent	define	serial
app4Evt	define	events	BringToFront	function	windows
app4Mask	define	events	bSpoolLoop	define	printing
AppendMenu	function	menus	btnCtrl	define	dialogs
AppFile	type	segload	btnState	define	events
appleMark	define	fonts	BUFSIZ	define	setbuf(C)
applFont	define	fonts	Button	function	events
ApplicZone	function	memory	c2pstr	function	strings
appOpen	define	segload	cairo	define	fonts
appPrint	define	segload	calcCRgns	define	controls
asin	function	trig(C)	CalcMenuSize	function	menus
atan	function	sane	CalcVis	function	windows
atan2	function	trig(C)	CalcVisBehind	function	windows
athens	define	fonts	calloc	function	malloc(C)
atof	function	atoi(C)	cancel	define	dialogs
atoi	function	atoi(C)	cantStepErr	define	disks
autoKey	define	events	CautionAlert	function	dialogs
autoKeyMask	define	events	ceil	function	floor(C)
autoTrack	define	controls	century	define	packages
BackColor	function	quickdraw	ChangedResource	function	resources
BackPat	function	quickdraw	char	type	quickdraw
badBtSlpErr	define	disks	char	type	sound
badCksmErr	define	disks	charCodeMask	define	events
badDBtSlp	define	disks	Chars	type	textedit
badDCKsum	define	disks	CharsHandle	type	textedit
badMDBErr	define	files	CharsPtr	type	textedit
badUnitErr	define	devices	CharWidth	function	quickdraw
baud1200	define	serial	checkBoxProc	define	controls
baud1800	define	serial	CheckItem	function	menus
baud19200	define	serial	checkMark	define	fonts
baud2400	define	serial	CheckUpdate	function	windows
baud300	define	serial	chkCtrl	define	dialogs
baud3600	define	serial	classcomp	function	sane
baud4800	define	serial	classdouble	function	sane
baud57600	define	serial	classextended	function	sane
			classfloat	function	sane
			clearerr	macro	ferror(C)

**LIBRARY INDEX**

**Lisa Workshop C User's Guide**

ClearMenuBar	function	menus	dataVerErr	define	disks
ClipAbove	function	windows	Date2Secs	function	osutils
ClipRect	function	quickdraw	DateForm	type	packages
clkRdErr	define	osutils	DateTimeRec	type	osutils
clkWrErr	define	osutils	dayLdingZ	define	packages
close	function	close (C)	DBLPRECISION	define	sane
CloseDeskAcc	function	desk	dBoxProc	define	windows
CloseDialog	function	dialogs	DctlEntry	type	devices
CloseDriver	function	devices	DctlHandle	type	devices
ClosePicture	function	quickdraw	DctlPtr	type	devices
ClosePoly	function	quickdraw	dec2num	function	sane
ClosePort	function	quickdraw	dec2str	function	sane
CloseResFile	function	resources	decform	type	sane
CloseRgn	function	quickdraw	decimal	type	sane
CloseWindow	function	windows	DECSTROUTLEN	define	sane
ClrAppFiles	function	segload	Delay	function	osutils
cmdKey	define	events	DeleteMenu	function	menus
CntrlParam	type	devices	DeltaPoint	function	toolutils
ColorBit	function	quickdraw	DENORMALNUM	define	sane
commandMark	define	fonts	Dequeue	function	osutils
CompactMem	function	memory	deskPatID	define	windows
compound	function	sane	DetachResource	function	resources
condense	define	quickdraw	dialogKind	define	windows
Control	function	devices	DialogPeek	type	dialogs
controlErr	define	devices	DialogPtr	type	dialogs
ControlHandle	type	controls	DialogRecord	type	dialogs
ControlPtr	type	controls	DialogSelect	function	dialogs
ControlRecord	type	controls	DialogTemplate	type	dialogs
CopyBits	function	quickdraw	DialogTHndl	type	dialogs
CopyRgn	function	quickdraw	DialogTPtr	type	dialogs
copysign	function	sane	diamondMark	define	fonts
cos	function	sane	DIBadMount	function	packages
cos	function	trig (C)	DiffRgn	function	quickdraw
cosh	function	cosh (C)	DIFormat	function	packages
CouldAlert	function	dialogs	DILoad	function	packages
CouldDialog	function	dialogs	dInstErr	define	devices
CountAppFiles	function	segload	dirFulErr	define	files
CountMItems	function	menus	DisableItem	function	menus
CountResources	function	resources	DiskEject	function	disks
CountTypes	function	resources	diskEvt	define	events
courier	define	fonts	diskMask	define	events
creat	function	creat (C)	dispCntl	define	controls
Create	function	files	DisposDialog	function	dialogs
CreateResFile	function	resources	DisposeControl	function	controls
crossCursor	define	toolutils	DisposeMenu	function	menus
ctnIcon	define	dialogs	DisposeRgn	function	quickdraw
ctrlItem	define	dialogs	DisposeWindow	function	windows
ctsEvent	define	serial	DisposHandle	function	memory
CurResFile	function	resources	DisposPtr	function	memory
currLeadingZ	define	packages	DIUnLoad	function	packages
currNegSym	define	packages	DIVBYZERO	define	sane
currSymLead	define	packages	DIVerify	function	packages
currTrailingZ	define	packages	DIZero	function	packages
CursHandle	type	toolutils	DlgCopy	function	dialogs
Cursor	type	quickdraw	DlgCut	function	dialogs
Cursor	type	toolutils	DlgDelete	function	dialogs
CursPtr	type	toolutils	DlgPaste	function	dialogs
cyanBit	define	quickdraw	dmy	define	packages
cyanColor	define	quickdraw	documentProc	define	windows
data5	define	serial	DOWNWARD	define	sane
data6	define	serial	dragCntl	define	controls
data7	define	serial	DragControl	function	controls
data8	define	serial	DragGrayRgn	function	windows



Lisa Workshop C User's Guide

LIBRARY INDEX

DragWindow	function	windows	EMFILE	define	Error Numbers (C)
DrawChar	function	quickdraw	EmptyHandle	function	memory
drawCntl	define	controls	EmptyRect	function	quickdraw
DrawControls	function	controls	EmptyRgn	function	quickdraw
DrawDialog	function	dialogs	EnableItem	function	menus
DrawGrowIcon	function	windows	EndUpdate	function	windows
DrawMenuBar	function	menus	ENFILE	define	Error Numbers (C)
DrawNew	function	windows	ENODEV	define	Error Numbers (C)
DrawPicture	function	quickdraw	ENOENT	define	Error Numbers (C)
DrawString	function	quickdraw	ENOMEM	define	Error Numbers (C)
DrawText	function	quickdraw	ENOSPC	define	Error Numbers (C)
dRemoveErr	define	devices	ENOTDIR	define	Error Numbers (C)
driverEvt	define	events	Enqueue	function	osutils
driverMask	define	events	environment	type	sane
DriveStatus	function	disks	Environs	function	osutils
DrvQEL	type	files	ENXIO	define	Error Numbers (C)
DrvQELPtr	type	files	EOF	define	stdio (C)
drvQType	literal	osutils	eofErr	define	files
DrvSts	type	disks	EPERM	define	Error Numbers (C)
dsAddressErr	define	error	EqualPt	function	quickdraw
dsBadLaunch	define	error	EqualRect	function	quickdraw
dsBusErr	define	error	EqualRgn	function	quickdraw
dsChkErr	define	error	EqualString	function	osutils
dsCoreErr	define	error	EQUALTO	define	sane
dsFPerr	define	error	erase	literal	quickdraw
dsFSerr	define	error	EraseArc	function	quickdraw
dsIllInstErr	define	error	EraseOval	function	quickdraw
dsIOCoreErr	define	error	ErasePoly	function	quickdraw
dsIrqErr	define	error	EraseRect	function	quickdraw
dskFulErr	define	files	EraseRgn	function	quickdraw
dskInit	define	packages	EraseRoundRect	function	quickdraw
dsLineAErr	define	error	EROFS	define	Error Numbers (C)
dsLineFErr	define	error	ErrorSound	function	dialogs
dsLoadErr	define	error	ESPIPE	define	Error Numbers (C)
dsMemFullErr	define	error	evenParity	define	serial
dsMiscErr	define	error	EventAvail	function	events
dsNoPackErr	define	error	EventRecord	type	events
dsNoPk1	define	error	everyEvent	define	events
dsNoPk2	define	error	EvQEL	type	osevents
dsNoPk3	define	error	evType	literal	osutils
dsNoPk4	define	error	exception	type	sane
dsNoPk5	define	error	exit	function	exit (C)
dsNoPk6	define	error	_exit	function	exit (C)
dsNoPk7	define	error	ExitToShell	function	segload
dsNotThe1	define	error	exp	function	exp (C)
dsOvflowErr	define	error	exp	function	sane
dsPrivErr	define	error	expl	function	sane
dsReinsert	define	error	exp2	function	sane
dsStkNHeap	define	error	expand	define	quickdraw
dsSysErr	define	error	extFSErr	define	files
dsTraceErr	define	error	EXTPRECISION	define	sane
dsZeroDivErr	define	error	fabs	function	floor (C)
dummyType	literal	osutils	fabs	function	sane
dupFNerr	define	files	false	literal	types
EACCESS	define	Error Numbers (C)	fBsyErr	define	files
EBADF	define	Error Numbers (C)	fclose	function	fclose (C)
ecvt	function	ecvt (C)	fcvt	function	ecvt (C)
editText	define	dialogs	fDesktop	define	files
EEXIST	define	Error Numbers (C)	fDisk	define	files
EINVAL	define	Error Numbers (C)	fdopen	function	fopen (C)
EIO	define	Error Numbers (C)	feedCut	literal	printing
EISDIR	define	Error Numbers (C)	feedFanfold	literal	printing
Eject	function	files	feedMechCut	literal	printing

**LIBRARY INDEX**

**Lisa Workshop C User's Guide**

feedOther	literal	printing	free	function	malloc (C)
feof	macro	ferror (C)	FreeAlert	function	dialogs
ferror	macro	ferror (C)	FreeDialog	function	dialogs
fflush	function	fclose (C)	FreeMem	function	memory
ffMode	define	sound	FreeWave	type	sound
FFSynthPtr	type	sound	freopen	function	fopen (C)
FFSynthRec	type	sound	frexp	function	frexp (C)
fgetc	function	getc (C)	FrontWindow	function	windows
fgets	function	gets (C)	fsAtMark	define	files
fHasBundle	define	files	fscanf	function	scanf (C)
FILE	define	stdio (C)	FSClose	function	files
fileno	macro	ferror (C)	fsCurPerm	define	files
FileParam	type	files	FSDelete	function	files
fill	literal	quickdraw	fseek	function	fseek (C)
FillArc	function	quickdraw	fsFromEOF	define	files
FillOval	function	quickdraw	fsFromMark	define	files
FillPoly	function	quickdraw	fsFromStart	define	files
FillRect	function	quickdraw	FSOpen	function	files
FillRgn	function	quickdraw	fsQType	literal	osutils
FillRoundRect	function	quickdraw	fsRdPerm	define	files
FindControl	function	controls	fsRdWrPerm	define	files
FindWindow	function	windows	FSRead	function	files
FInfo	type	files	fsRnErr	define	files
FInitQueue	function	files	FSWrite	function	files
fInvisible	define	files	fsWrPerm	define	files
firstDskErr	define	disks	ftell	function	fseek (C)
Fixed	type	types	ftMode	define	sound
FIXEDECIMAL	define	sane	fTrash	define	files
fixedFont	define	fonts	FTSndRecPtr	type	sound
FixMul	function	toolutils	FTSoundRec	type	sound
FixRatio	function	toolutils	FTSynthPtr	type	sound
FixRound	function	toolutils	FTSynthRec	type	sound
FlashMenuBar	function	menus	fwrite	function	sound (C)
fLckdErr	define	files	geneva	define	fonts
FLOATDECIMAL	define	sane	GetAlrtStage	function	dialogs
FLOATPRECISION	define	sane	GetAppFiles	function	segload
floor	function	floor (C)	GetApplLimit	function	memory
flPoint	define	packages	GetAppParms	function	segload
FlushEvents	function	osevents	getc	macro	getc (C)
FlushVol	function	files	getCancel	define	packages
FMInput	type	fonts	GetCaretTime	function	events
fmod	function	floor (C)	getchar	function	getc (C)
FMOutPtr	type	fonts	GetClip	function	quickdraw
FMOutput	type	fonts	GetCRefCon	function	controls
fnfErr	define	files	GetCTitle	function	controls
fnOpnErr	define	files	GetCtlAction	function	controls
FontInfo	type	quickdraw	GetCtlMax	function	controls
FontRec	type	fonts	GetCtlMin	function	controls
fontWid	define	fonts	GetCtlValue	function	controls
fopen	function	fopen (C)	GetCursor	function	toolutils
ForeColor	function	quickdraw	GetDateTime	function	osutils
fprintf	function	printf (C)	GetDblTime	function	events
fputc	function	putc (C)	GetDctlEntry	function	devices
fputs	function	puts (C)	GetDItem	function	dialogs
frame	literal	quickdraw	getDlgID	define	packages
FrameArc	function	quickdraw	getDrive	define	packages
FrameOval	function	quickdraw	GetDrvQHdr	function	files
FramePoly	function	quickdraw	getEject	define	packages
FrameRect	function	quickdraw	getenvironment	function	sane
FrameRgn	function	quickdraw	GetEOF	function	files
FrameRoundRect	function	quickdraw	GetEvQHdr	function	osevents
framingErr	define	serial	GetFInfo	function	files
fread	function	fread (C)	GetFNum	function	fonts

**Lisa Workshop C User's Guide**

**LIBRARY INDEX**

GetFontInfo	function	quickdraw	GrafDevice	function	quickdraw
GetFontName	function	fonts	GrafPort	type	quickdraw
GetFPos	function	files	GrafPtr	type	quickdraw
GetFSQHdr	function	files	GrafVerb	type	quickdraw
gethaltvector	function	sane	GREATERTHAN	define	sane
GetHandleSize	function	memory	greenBit	define	quickdraw
GetIcon	function	toolutils	greenColor	define	quickdraw
GetIndPattern	function	toolutils	GrowWindow	function	windows
GetIndResource	function	resources	GZCritical	function	memory
GetIndString	function	toolutils	GZSaveHnd	function	memory
GetIndType	function	resources	haltvector	type	sane
GetItem	function	menus	HandAndHand	function	osutils
GetItemIcon	function	menus	Handle	type	types
GetItemMark	function	menus	HandleZone	function	memory
GetItemStyle	function	menus	HandToHand	function	osutils
GetIText	function	dialogs	hAxisOnly	define	controls
GetKeys	function	events	hAxisOnly	define	windows
GetMenu	function	menus	helvetica	define	fonts
GetMenuBar	function	menus	HideControl	function	controls
GetMHandle	function	menus	HideCursor	function	quickdraw
GetMouse	function	events	HidePen	function	quickdraw
GetNamedResource	function	resources	HideWindow	function	windows
GetNewControl	function	controls	HiliteControl	function	controls
GetNewDialog	function	dialogs	HiliteMenu	function	menus
GetNewMBar	function	menus	HiliteWindow	function	windows
GetNewWindow	function	windows	HiWord	function	toolutils
GetNextEvent	function	events	HLock	function	memory
getNmList	define	packages	HNoPurge	function	memory
getOpen	define	packages	HomeResFile	function	resources
GetOSEvent	function	osevents	HPurge	function	memory
GetPattern	function	toolutils	hrLeadingZ	define	packages
GetPen	function	quickdraw	HUnlock	function	memory
GetPenState	function	quickdraw	hwOverrunErr	define	serial
GetPicture	function	toolutils	hypot	function	hypot (C)
GetPixel	function	quickdraw	iBeamCursor	define	toolutils
GetPort	function	quickdraw	iconItem	define	dialogs
getprecision	function	sane	iIOAbort	define	printing
GetPtrSize	function	memory	iMemFullErr	define	printing
GetResAttr	function	resources	inButton	define	controls
GetResFileAttr	function	resources	inCheckbox	define	controls
GetResInfo	function	resources	inContent	define	windows
GetResource	function	resources	inDesk	define	windows
getround	function	sane	inDownButton	define	controls
gets	function	gets (C)	inDrag	define	windows
GetScrap	function	scrap	INEXACT	define	sane
getScroll	define	packages	inf	function	sane
GetSoundVol	function	sound	INFINITE	define	sane
GetString	function	toolutils	InfoScrap	function	scrap
GetSysPPtr	function	osutils	inGoAway	define	windows
GetTime	function	osutils	inGrow	define	windows
GetTrapAddress	function	osutils	InitAllPacks	function	packages
GetVBLQHdr	function	retrace	InitApplZone	function	memory
GetVCBQHdr	function	files	initCntl	define	controls
GetVInfo	function	files	InitCursor	function	quickdraw
GetVol	function	files	InitDialogs	function	dialogs
GetVRefNum	function	files	InitFonts	function	fonts
getw	function	getc (C)	InitGraf	function	quickdraw
GetWindowPic	function	windows	initIWMErr	define	disks
GetWMgrPort	function	windows	InitMenus	function	menus
GetWRefCon	function	windows	InitPack	function	packages
GetWTitle	function	windows	InitPort	function	quickdraw
GetZone	function	memory	InitResources	function	resources
GlobalToLocal	function	quickdraw	InitUtil	function	osutils

LIBRARY INDEX

Lisa Workshop C User's Guide

InitWindows	function	windows	IUGetInt1	function	packages
InitZone	function	memory	IUMagIDString	function	packages
inMenuBar	define	windows	IUMagString	function	packages
inPageDown	define	controls	IUMetric	function	packages
inPageUp	define	controls	IUSetInt1	function	packages
InsertMenu	function	menus	IUTimePString	function	packages
InsertResMenu	function	menus	IUTimeString	function	packages
InsetRect	function	quickdraw	kanji	define	fonts
InsetRgn	function	quickdraw	keyCodeMask	define	events
inSysWindow	define	windows	keyDown	define	events
Int64Bit	type	toolutils	keyDownMask	define	events
inThumb	define	controls	KeyMap	type	events
Int10Hndl	type	packages	keyUp	define	events
Int10Ptr	type	packages	keyUpMask	define	events
Int10Rec	type	packages	KillControls	function	controls
Int11Hndl	type	packages	KillIO	function	devices
Int11Ptr	type	packages	KillPicture	function	quickdraw
Int11Rec	type	packages	KillPoly	function	quickdraw
intUtil	define	packages	lastDskErr	define	disks
inUpButton	define	controls	ldexp	function	frexp(C)
INVALID	define	sane	LESSTHAN	define	sane
InvalRect	function	windows	Line	function	quickdraw
InvalRgn	function	windows	LineTo	function	quickdraw
inverseBit	define	quickdraw	LoadResource	function	resources
invert	literal	quickdraw	LoadScrap	function	scrap
InvertArc	function	quickdraw	LocalToGlobal	function	quickdraw
InvertOval	function	quickdraw	log	function	exp(C)
InvertPoly	function	quickdraw	log	function	sane
InvertRect	function	quickdraw	log1	function	sane
InvertRgn	function	quickdraw	log10	function	exp(C)
InvertRoundRect	function	quickdraw	log2	function	sane
ioctl	function	ioctl(C)	logb	function	sane
ioErr	define	files	london	define	fonts
IOParm	type	files	long	type	types
ioQType	literal	osutils	longDate	literal	packages
iPFMaxPgs	define	printing	LongMul	function	toolutils
ipower	function	sane	losAngeles	define	fonts
iPrAbort	define	printing	LoWord	function	toolutils
iPrBitsCtl	define	printing	lPaintBits	define	printing
iPrDevCtl	define	printing	lPrLFSixth	define	printing
iPrDrvrRef	define	printing	lPrLineFeed	define	printing
iPrIOctl	define	printing	lPrPageEnd	define	printing
iPrPgFract	define	printing	lPrReset	define	printing
iPrSavPFil	define	printing	lScreenBits	define	printing
isalnum	macro	ctype(C)	lseek	function	lseek(C)
isalpha	macro	ctype(C)	macMachine	define	osutils
isascii	macro	ctype(C)	macXMLMachine	define	osutils
iscntrl	macro	ctype(C)	magentaBit	define	quickdraw
IsDialogEvent	function	dialogs	magentaColor	define	quickdraw
isdigit	macro	ctype(C)	malloc	function	malloc(C)
isgraph	macro	ctype(C)	mapChanged	define	resources
islower	macro	ctype(C)	mapCompact	define	resources
isprint	macro	ctype(C)	MapPoly	function	quickdraw
ispunct	macro	ctype(C)	MapPt	function	quickdraw
isspace	macro	ctype(C)	mapReadOnly	define	resources
isupper	macro	ctype(C)	MapRect	function	quickdraw
isxdigit	macro	ctype(C)	MapRgn	function	quickdraw
italic	define	quickdraw	MaxApplZone	function	memory
itemDisable	define	dialogs	MaxMem	function	memory
IUCompString	function	packages	maxSize	define	memory
IUDatePString	function	packages	mChooseMsg	define	menus
IUDateString	function	packages	mDownMask	define	events
IUEqualString	function	packages	mDrawMsg	define	menus

Lisa Workshop C User's Guide

LIBRARY INDEX

mdy	define	packages	networkMask	define	events
memccpy	function	memory (C)	NewControl	function	controls
memchr	function	memory (C)	NewDialog	function	dialogs
memcmp	function	memory (C)	NewHandle	function	memory
memcpy	function	memory (C)	NewMenu	function	menus
MemError	function	memory	NewPtr	function	memory
memFullErr	define	memory	NewRgn	function	quickdraw
memFullErr	define	osutils	NewString	function	toolutils
memLockedErr	define	memory	NewWindow	function	windows
memPurErr	define	memory	newYork	define	fonts
memset	function	memory (C)	nextdouble	function	sane
memWZErr	define	memory	nextextended	function	sane
memWZErr	define	osutils	nextfloat	function	sane
MenuHandle	type	menus	nil	define	types
MenuInfo	type	menus	nilHandleErr	define	memory
MenuKey	function	menus	nilHandleErr	define	osutils
MenuPtr	type	menus	noAdrMkErr	define	disks
MenuSelect	function	menus	noConstraint	define	controls
minLeadingZ	define	packages	noConstraint	define	windows
mntLdingZ	define	packages	noDriveErr	define	disks
ModalDialog	function	dialogs	noDtMkErr	define	disks
modf	function	frexp (C)	noErr	define	devices
monaco	define	fonts	noErr	define	disks
MoreMasters	function	memory	noErr	define	files
mouseDown	define	events	noErr	define	memory
mouseUp	define	events	noErr	define	osutils
Move	function	quickdraw	noErr	define	printing
MoveControl	function	controls	noErr	define	retrace
MoveHHi	function	memory	noErr	define	serial
MovePortTo	function	quickdraw	noGrowDocProc	define	windows
MoveTo	function	quickdraw	noMacDskErr	define	files
MoveWindow	function	windows	noMark	define	menus
mSizeMsg	define	menus	noNybErr	define	disks
Munger	function	toolutils	noParity	define	serial
mUpMask	define	events	normal	define	quickdraw
MyAction	function	controls	normalBit	define	quickdraw
MyAction	function	windows	NORMALNUM	define	sane
MyArc	function	quickdraw	noScrapErr	define	scrap
MyBits	function	quickdraw	NoteAlert	function	dialogs
MyClikLoop	function	textedit	noteIcon	define	dialogs
MyComment	function	quickdraw	notOpenErr	define	devices
MyControl	function	controls	notPatBic	define	quickdraw
MyDlg	function	packages	notPatCopy	define	quickdraw
MyFileFilter	function	packages	notPatOr	define	quickdraw
MyFilter	function	dialogs	notPatXor	define	quickdraw
MyGetPic	function	quickdraw	notSrcBic	define	quickdraw
MyGrowZone	function	memory	notSrcCopy	define	quickdraw
MyItem	function	dialogs	notSrcOr	define	quickdraw
MyLine	function	quickdraw	notSrcXor	define	quickdraw
MyMenu	function	menus	noTypeErr	define	scrap
MyOval	function	quickdraw	nsDrvErr	define	disks
MyPoly	function	quickdraw	nsDrvErr	define	files
MyPutPic	function	quickdraw	nsvErr	define	files
MyRect	function	quickdraw	NULL	define	stdio (C)
MyRgn	function	quickdraw	NULL	define	types
MyRRect	function	quickdraw	nullEvent	define	events
MySound	function	dialogs	num2dec	function	sane
MyText	function	quickdraw	numclass	type	sane
MyTxMeas	function	quickdraw	NumToString	function	packages
MyWindow	function	windows	O_APPEND	define	open (C)
MyWordBreak	function	textedit	ObscureCursor	function	quickdraw
nan	function	sane	O_CREAT	define	open (C)
networkEvt	define	events	oddParity	define	serial

**LIBRARY INDEX**

**Lisa Workshop C User's Guide**

O_EXCL	define	open(C)	PBGetVol	function	files
offLinErr	define	disks	PBKillIO	function	devices
OffsetPoly	function	quickdraw	PBMountVol	function	files
OffsetRect	function	quickdraw	PBOffLine	function	files
OffsetRgn	function	quickdraw	PBOpen	function	files
ok	define	dialogs	PBOpenRF	function	files
open	function	open(C)	PBRead	function	files
OpenDeskAcc	function	desk	PBRename	function	files
OpenDriver	function	devices	PBRstFLock	function	files
openErr	define	devices	PBSetEOF	function	files
openErr	define	serial	PBSetFInfo	function	files
OpenPicture	function	quickdraw	PBSetFLock	function	files
OpenPoly	function	quickdraw	PBSetFPos	function	files
OpenPort	function	quickdraw	PBSetFVers	function	files
OpenResFile	function	resources	PBSetVol	function	files
OpenRF	function	files	PBStatus	function	devices
OpenRgn	function	quickdraw	PBUnmountVol	function	files
optionKey	define	events	PBWrite	function	files
opWrErr	define	files	PenMode	function	quickdraw
O_RDONLY	define	open(C)	PenNormal	function	quickdraw
O_RDWR	define	open(C)	PenPat	function	quickdraw
OSErr	type	types	PenSize	function	quickdraw
OSEventAvail	function	osevents	PenState	type	quickdraw
OSType	type	types	permErr	define	files
O_TRUNC	define	open(C)	pi	function	sane
outline	define	quickdraw	PicComment	function	quickdraw
OVERFLOW	define	sane	PicHandle	type	quickdraw
O_WRONLY	define	open(C)	picItem	define	dialogs
p2cstr	function	strings	picLParen	define	quickdraw
PackBits	function	toolutils	PicPtr	type	quickdraw
paint	literal	quickdraw	picRParen	define	quickdraw
PaintArc	function	quickdraw	Picture	type	quickdraw
PaintBehind	function	windows	PinRect	function	windows
PaintOne	function	windows	plainDBox	define	windows
PaintOval	function	quickdraw	PlotIcon	function	toolutils
PaintPoly	function	quickdraw	plusCursor	define	toolutils
PaintRect	function	quickdraw	Point	type	types
PaintRgn	function	quickdraw	Polygon	type	quickdraw
PaintRoundRect	function	quickdraw	PolyHandle	type	quickdraw
paramErr	define	disks	PolyPtr	type	quickdraw
paramErr	define	files	PortSize	function	quickdraw
ParamText	function	dialogs	posCntl	define	controls
parityErr	define	serial	posErr	define	files
patBic	define	quickdraw	PostEvent	function	osevents
patCopy	define	quickdraw	pow	function	exp(C)
PatHandle	type	toolutils	power	function	sane
patOr	define	quickdraw	PrClose	function	printing
PatPtr	type	toolutils	PrCloseDoc	function	printing
Pattern	type	quickdraw	PrClosePage	function	printing
Pattern	type	toolutils	PrCtlCall	function	printing
patXor	define	quickdraw	PrDrvrClose	function	printing
PBAllocate	function	files	PrDrvrDCE	function	printing
PBClose	function	files	PrDrvrOpen	function	printing
PBControl	function	devices	PrDrvrVers	function	printing
PBCreate	function	files	PrError	function	printing
PBDelete	function	files	prInitErr	define	osutils
PBEject	function	files	PrintDefault	function	printing
PBFlushFile	function	files	printf	function	printf(C)
PBFlushVol	function	files	PrJobDialog	function	printing
PBGetEOF	function	files	PrJobMerge	function	printing
PBGetFInfo	function	files	procentry	function	sane
PBGetFPos	function	files	procexit	function	sane
PBGetVInfo	function	files	ProcHandle	type	types

Lisa Workshop C User's Guide

LIBRARY INDEX

ProcPtr	type	types	redColor	define	quickdraw
PrOpen	function	printing	Region	type	quickdraw
PrOpenDoc	function	printing	relation	function	sane
PrOpenPage	function	printing	ReleaseResource	function	resources
propFont	define	fonts	relop	type	sane
PrPicFile	function	printing	remainder	function	sane
PrSetError	function	printing	Rename	function	files
PrStlDialog	function	printing	resChanged	define	resources
PrValidate	function	printing	resCtrl	define	dialogs
prWrErr	define	osutils	ResError	function	resources
PScrapStuff	type	scrap	ResetAlrtStage	function	dialogs
Pt2Rect	function	quickdraw	resNotFound	define	resources
PtInRect	function	quickdraw	resLocked	define	resources
PtInRgn	function	quickdraw	resNotFound	define	resources
Ptr	type	types	resPreload	define	resources
PtrAndHand	function	osutils	resProtected	define	resources
PtrToHand	function	osutils	resPurgeable	define	resources
PtrToXHand	function	osutils	ResrvMem	function	memory
PtrZone	function	memory	resSysHeap	define	resources
PtToAngle	function	quickdraw	Restart	function	osutils
PurgeMem	function	memory	ResType	type	types
pushButProc	define	controls	rewind	function	fseek(C)
putc	macro	putc(C)	rNumErr	define	files
putCancel	define	packages	RgnHandle	type	quickdraw
putchar	macro	putc(C)	RgnPtr	type	quickdraw
putDlgID	define	packages	rint	function	sane
putDrive	define	packages	RmvResource	function	resources
putEject	define	packages	rmvResFailed	define	resources
putName	define	packages	rounddir	type	sane
puts	function	puts(C)	roundpre	type	sane
putSave	define	packages	RsrcZoneInit	function	resources
PutScrap	function	scrap	RstFlock	function	files
putw	function	putc(C)	sanFran	define	fonts
QDProcs	type	quickdraw	SaveOld	function	windows
QDProcsPtr	type	quickdraw	scalb	function	sane
QElem	type	osutils	ScalePt	function	quickdraw
QElemPtr	type	osutils	scanBT	literal	printing
qErr	define	osutils	scanf	function	scanf(C)
qErr	define	retrace	scanLR	literal	printing
QHdr	type	osutils	scanRL	literal	printing
QHdrPtr	type	osutils	scanTB	literal	printing
QNaN	define	sane	ScrapStuff	type	scrap
QTypes	type	osutils	ScreenRes	function	toolutils
radCtrl	define	dialogs	scrollBarProc	define	controls
radioButProc	define	controls	ScrollRect	function	quickdraw
RAMSDClose	function	serial	secLeadingZ	define	packages
RAMSDOpen	function	serial	Secs2Date	function	osutils
rand	function	rand(C)	sectNFErr	define	disks
Random	function	quickdraw	SectRect	function	quickdraw
randomx	function	sane	SectRgn	function	quickdraw
rDocProc	define	windows	seekErr	define	disks
rdVerify	define	files	SelectWindow	function	windows
read	function	read(C)	SellText	function	dialogs
ReadDateTime	function	osutils	SendBehind	function	windows
readErr	define	devices	SerClrBrk	function	serial
RealFont	function	fonts	SerGetBuf	function	serial
realloc	function	malloc(C)	SerHShake	function	serial
ReallocHandle	function	memory	SerReset	function	serial
RecoverHandle	function	memory	SerSetBrk	function	serial
Rect	type	types	SerSetBuf	function	serial
RectInRgn	function	quickdraw	SerShk	type	serial
RectRgn	function	quickdraw	SerStaRec	type	serial
redBit	define	quickdraw	SerStatus	function	serial

**LIBRARY INDEX**

**Lisa Workshop C User's Guide**

SetApplBase	function	memory	SFPGetFile	function	packages
SetApplLimit	function	memory	SFPPutFile	function	packages
setbuf	function	setbuf(C)	SFPutFile	function	packages
SetClikLoop	function	textedit	SFReply	type	packages
SetClip	function	quickdraw	SFTypeList	type	packages
SetCRefCon	function	controls	shadow	define	quickdraw
SetCTitle	function	controls	ShieldCursor	function	toolutils
SetCtlAction	function	controls	shiftKey	define	events
SetCtlMax	function	controls	shortDate	literal	packages
SetCtlMin	function	controls	ShowControl	function	controls
SetCtlValue	function	controls	ShowCursor	function	quickdraw
SetCursor	function	quickdraw	ShowHide	function	windows
SetDAFont	function	dialogs	ShowPen	function	quickdraw
SetDateTime	function	osutils	ShowWindow	function	windows
SetDItem	function	dialogs	SIGDIGLEN	define	sane
SetEmptyRgn	function	quickdraw	signnum	function	sane
setenvironment	function	sane	sin	function	sane
SetEOF	function	files	sin	function	trig(C)
SetEventMask	function	osevents	sinh	function	sinh(C)
setexception	function	sane	Size	type	memory
SetFInfo	function	files	SizeControl	function	controls
SetFLock	function	files	SizeResource	function	resources
SetFontLock	function	fonts	SizeWindow	function	windows
SetFPos	function	files	SlopeFromAngle	function	toolutils
SetGrowZone	function	memory	SNAN	define	sane
sethalt	function	sane	SoundDone	function	sound
sethaltvector	function	sane	SpaceExtra	function	quickdraw
SetHandleSize	function	memory	spdAdjErr	define	disks
SetItem	function	menus	sPortA	literal	serial
SetItemIcon	function	menus	sPortB	literal	serial
SetItemMark	function	menus	SPortSel	type	serial
SetItemStyle	function	menus	sPrDrvr	define	printing
SetIText	function	dialogs	sprintf	function	printf(C)
SetMenuBar	function	menus	sqrt	function	exp(C)
SetMenuFlash	function	menus	sqrt	function	sane
SetOrigin	function	quickdraw	srand	function	rand(C)
SetPenState	function	quickdraw	srcBic	define	quickdraw
SetPort	function	quickdraw	srcCopy	define	quickdraw
SetPortBits	function	quickdraw	srcOr	define	quickdraw
setprecision	function	sane	srcXor	define	quickdraw
SetPt	function	quickdraw	sscanf	function	scanf(C)
SetPtrSize	function	memory	StageList	type	dialogs
SetRect	function	quickdraw	StartSound	function	sound
SetRectRgn	function	quickdraw	statText	define	dialogs
SetResAttrs	function	resources	Status	function	devices
SetResFileAttrs	function	resources	statusErr	define	devices
SetResInfo	function	resources	StdArc	function	quickdraw
SetResLoad	function	resources	StdBits	function	quickdraw
SetResPurge	function	resources	StdComment	function	quickdraw
setround	function	sane	stderr	define	stdio(C)
SetSoundVol	function	sound	stdFile	define	packages
SetStdProcs	function	quickdraw	StdGetPic	function	quickdraw
SetString	function	toolutils	stdin	define	stdio(C)
SetTagBuffer	function	disks	StdLine	function	quickdraw
SetTime	function	osutils	stdout	define	stdio(C)
SetTrapAddress	function	osutils	StdOval	function	quickdraw
SetVol	function	files	StdPoly	function	quickdraw
SetWindowPic	function	windows	StdPutPic	function	quickdraw
SetWordBreak	function	textedit	StdRect	function	quickdraw
SetWRefCon	function	windows	StdRgn	function	quickdraw
SetWTitle	function	windows	StdRRect	function	quickdraw
SetZone	function	memory	StdText	function	quickdraw
SFGetFile	function	packages	StdTxMeas	function	quickdraw



Lisa Workshop C User's Guide

LIBRARY INDEX

StillDown	function	events	teJustCenter	define	textedit
stop10	define	serial	teJustLeft	define	textedit
stop15	define	serial	teJustRight	define	textedit
stop20	define	serial	TEKey	function	textedit
StopAlert	function	dialogs	TENew	function	textedit
stopIcon	define	dialogs	TEPaste	function	textedit
StopSound	function	sound	TEPtr	type	textedit
Str255	type	types	TERec	type	textedit
str2dec	function	sane	TEScrapHandle	function	textedit
strcat	function	string (C)	TEScroll	function	textedit
strchr	function	string (C)	TESetJust	function	textedit
strcmp	function	string (C)	TESetScrapLen	function	textedit
strcpy	function	string (C)	TESetSelect	function	textedit
String	define	types	TESetText	function	textedit
StringHandle	type	types	testCntl	define	controls
StringPtr	type	types	TestControl	function	controls
StringToNum	function	packages	testexception	function	sane
StringWidth	function	quickdraw	testhalt	function	sane
strlen	function	string (C)	TEToScrap	function	textedit
strncat	function	string (C)	TEUpdate	function	textedit
strncmp	function	string (C)	TextBox	function	textedit
strncpy	function	string (C)	TextFace	function	quickdraw
strrchr	function	string (C)	TextFont	function	quickdraw
StuffHex	function	quickdraw	textMenuProc	define	menus
Style	type	types	TextMode	function	quickdraw
SubPt	function	quickdraw	TextSize	function	quickdraw
SwapFont	function	fonts	TextWidth	function	quickdraw
swMode	define	sound	TFeed	type	printing
swOverrunErr	define	serial	THPrint	type	printing
SWSynthPtr	type	sound	thumbCntl	define	controls
SWSynthRec	type	sound	THz	type	memory
symbol	define	fonts	TickCount	function	events
SysBeep	function	osutils	times	define	fonts
SysError	function	error	tk0BadErr	define	disks
SysParmType	type	osutils	tmfoErr	define	files
sysPatListID	define	toolutils	toascii	function	conv (C)
SysPPtr	type	osutils	tolower	function	conv (C)
SystemClick	function	desk	_tolower	macro	conv (C)
SystemEdit	function	desk	Tone	type	sound
SystemEvent	function	desk	TONEAREST	define	sane
systemFont	define	fonts	Tones	type	sound
SystemMenu	function	desk	TopMem	function	memory
SystemTask	function	desk	toronto	define	fonts
SystemZone	function	memory	toupper	function	conv (C)
taliesin	define	fonts	_toupper	macro	conv (C)
tan	function	sane	TOWARDZERO	define	sane
tan	function	trig (C)	TPPrint	type	printing
tanh	function	tanh (C)	TPPrPort	type	printing
TEActivate	function	textedit	TPRect	type	printing
TECalText	function	textedit	TPrInfo	type	printing
TEClick	function	textedit	TPrint	type	printing
TECopy	function	textedit	TPrJob	type	printing
TECut	function	textedit	TPrPort	type	printing
TEDeactivate	function	textedit	TPrStatus	type	printing
TEDelete	function	textedit	TPrStl	type	printing
TEDispose	function	textedit	TPrXInfo	type	printing
TEFromScrap	function	textedit	TrackControl	function	controls
TEGetScrapLen	function	textedit	TrackGoAway	function	windows
TEGetText	function	textedit	trFunc	define	packages
TEHandle	type	textedit	true	literal	types
TEIdle	function	textedit	TScan	type	printing
TEInit	function	textedit	twoSideErr	define	disks
TEInsert	function	textedit	UNDERFLOW	define	sane

**LIBRARY INDEX**

**Lisa Workshop C User's Guide**

underline	define	quickdraw	vType	literal	osutils
ungetc	function	ungetc(C)	vTypErr	define	retrace
UnionRect	function	quickdraw	WaitMouseUp	function	events
UnionRgn	function	quickdraw	watchCursor	define	toolutils
UniqueID	function	resources	Wave	type	sound
unitEmptyErr	define	devices	WavePtr	type	sound
unlink	function	unlink(C)	wCalcRgns	define	windows
UnloadScrap	function	scrap	wDispose	define	windows
UnloadSeg	function	segload	wDraw	define	windows
UnmountVol	function	files	wDrawGIcon	define	windows
UNORDERED	define	sane	wGrow	define	windows
UnpackBits	function	toolutils	wHit	define	windows
updateEvt	define	events	whiteColor	define	quickdraw
updateMask	define	events	wInContent	define	windows
UpdateResFile	function	resources	WindowPeek	type	windows
UprString	function	osutils	WindowPtr	type	windows
UPWARD	define	sane	WindowRecord	type	windows
useAsync	define	osutils	wInDrag	define	windows
useATalk	define	osutils	wInGoAway	define	windows
useFree	define	osutils	wInGrow	define	windows
UseResFile	function	resources	wNew	define	windows
userItem	define	dialogs	wNoHit	define	windows
userKind	define	windows	wPrErr	define	disks
useWFont	define	controls	wPrErr	define	files
ValidRect	function	windows	write	function	write(C)
ValidRgn	function	windows	WriteParam	function	osutils
vAxisOnly	define	controls	WriteResource	function	resources
vAxisOnly	define	windows	writErr	define	devices
VBLTask	type	retrace	wrPermErr	define	files
VCB	type	files	wrUnderrun	define	disks
venice	define	fonts	xOffWasSent	define	serial
verArabia	define	packages	XorRgn	function	quickdraw
verAustralia	define	packages	yellowBit	define	quickdraw
verBelgiumLux	define	packages	yellowColor	define	quickdraw
verBritain	define	packages	ynd	define	packages
verCyprus	define	packages	ZERONUM	define	sane
verDenmark	define	packages	ZeroScrap	function	scrap
verFinland	define	packages	Zone	type	memory
verFrance	define	packages			
verFrCanada	define	packages			
verFrSwiss	define	packages			
verGermany	define	packages			
verGreece	define	packages			
verGrSwiss	define	packages			
verIceland	define	packages			
verIsrael	define	packages			
verItaly	define	packages			
verJapan	define	packages			
verMalta	define	packages			
verNetherlands	define	packages			
verNorway	define	packages			
verPortugal	define	packages			
verSpain	define	packages			
verSweden	define	packages			
verTurkey	define	packages			
verUS	define	packages			
verYugoslavia	define	packages			
VInstall	function	retrace			
vLckdErr	define	files			
volOffLinErr	define	files			
volOnLinErr	define	files			
VolumeParam	type	files			
VRemove	function	retrace			

A-Ø

 Apple Lisa Computer Information 

# Lisa Workshop C System Manual Extra

Disk  
Covers

A-1




A-2



Disk I/O error 13 Sep 89  
when Disk Copy  
used  
Scavange  
or re-copy on  
Lisa

A-3



*B-Ø*

 Apple Lisa Computer Information 

# Lisa Workshop C System

## Manual Extra

Disk  
Catalogs

B-1

\*\*\*\*\*  
 \*\*\*\*\* LISA WORKSHOP C DISK DIRECTORY \*\*\*\*\*  
 \*\*\*\*\*

LISA WORKSHOP C DISK 1

Filename	Size	Psize	Last-Mod-Date	Creation-Date	Attr
C.OBJ	201216	393	09/04/85-11:20	09/04/85-11:15	
MAC/C/LIB/CRUNTIME.OBJ	1536	3	09/04/85-13:59	09/04/85-13:59	
MAC/C/LIB/CRUNTIM...OBJ	1536	3	09/04/85-14:00	09/04/85-13:59	
MAC/C/LIB/INTERFACE.OBJ	27648	54	08/27/85-16:21	08/27/85-16:18	
MAC/C/LIB/MATH.OBJ	6656	13	07/10/85-16:47	07/10/85-16:45	
MAC/C/LIB/RUNTIME.OBJ	1536	3	09/04/85-13:59	09/04/85-13:59	
MAC/C/LIB/SANELIB.OBJ	6144	12	09/18/85-19:46	09/18/85-19:44	
MAC/C/LIB/STDCLIB.OBJ	32256	63	09/04/85-14:09	09/04/85-14:00	
MAC/C/LIB/STDCPRINTF.OBJ	5120	10	09/04/85-14:11	09/04/85-14:09	

554 total blocks for files listed

- C.OBJ
- MAC/C/LIB/CRUNTIME.OBJ
- MAC/C/LIB/CRUNTIMEARGV.OBJ
- MAC/C/LIB/INTERFACE.OBJ
- MAC/C/LIB/MATH.OBJ
- MAC/C/LIB/RUNTIME.OBJ
- MAC/C/LIB/SANELIB.OBJ
- MAC/C/LIB/STDCLIB.OBJ
- MAC/C/LIB/STDCPRINTF.OBJ

LISA WORKSHOP C DISK 2

Filename	Size	Psize	Last-Mod-Date	Creation-Date	Attr
MAC/C/INCLUDE/CON...TEXT	4096	8	08/15/85-17:53	08/15/85-17:53	
MAC/C/INCLUDE/CTY...TEXT	3072	6	06/24/85-17:10	03/13/85-12:00	
MAC/C/INCLUDE/DES...TEXT	2048	4	05/23/85-10:34	05/23/85-10:34	
MAC/C/INCLUDE/DEV...TEXT	3072	6	08/15/85-17:53	08/15/85-17:53	
MAC/C/INCLUDE/DIA...TEXT	4096	8	08/26/85-11:56	08/26/85-11:55	
MAC/C/INCLUDE/DIS...TEXT	3072	6	08/15/85-17:53	08/15/85-17:53	
MAC/C/INCLUDE/ERR...TEXT	5120	10	06/24/85-17:10	03/13/85-12:00	
MAC/C/INCLUDE/ERR...TEXT	2048	4	05/23/85-10:34	05/23/85-10:34	
MAC/C/INCLUDE/EVE...TEXT	3072	6	05/23/85-10:34	05/23/85-10:34	
MAC/C/INCLUDE/FCN...TEXT	3072	6	06/24/85-17:11	03/13/85-12:00	
MAC/C/INCLUDE/FIL...TEXT	5120	10	08/15/85-17:53	08/15/85-17:53	
MAC/C/INCLUDE/FON...TEXT	3072	6	05/23/85-10:34	05/23/85-10:34	
MAC/C/INCLUDE/IOC...TEXT	2048	4	06/24/85-17:12	03/29/85-19:31	
MAC/C/INCLUDE/MAT...TEXT	2048	4	07/10/85-11:16	03/13/85-12:00	
MAC/C/INCLUDE/MEM...TEXT	2048	4	05/23/85-10:35	05/23/85-10:35	
MAC/C/INCLUDE/MEN...TEXT	4096	8	05/23/85-10:35	05/23/85-10:35	
MAC/C/INCLUDE/OSE...TEXT	2048	4	05/23/85-10:35	05/23/85-10:35	
MAC/C/INCLUDE/OSU...TEXT	3072	6	08/15/85-17:54	08/15/85-17:53	
MAC/C/INCLUDE/PAC...TEXT	4096	8	05/23/85-10:35	05/23/85-10:35	
MAC/C/INCLUDE/PRI...TEXT	5120	10	08/15/85-18:00	08/15/85-18:00	
MAC/C/INCLUDE/QUI...TEXT	14336	28	08/09/85-09:52	08/09/85-09:48	
MAC/C/INCLUDE/RES...TEXT	4096	8	05/23/85-10:35	05/23/85-10:35	



B-2

MAC/C/INCLUDE/RET...TEXT	2048	4	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/SAN...TEXT	3072	6	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/SCR...TEXT	2048	4	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/SEG...TEXT	2048	4	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/SER...TEXT	3072	6	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/SOU...TEXT	3072	6	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/STD...TEXT	3072	6	06/24/85-17:13	03/13/85-12:00
MAC/C/INCLUDE/STR...TEXT	2048	4	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/TEX...TEXT	4096	8	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/TOO...TEXT	4096	8	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/TYP...TEXT	2048	4	05/23/85-10:35	05/23/85-10:35
MAC/C/INCLUDE/VAL...TEXT	3072	6	07/10/85-11:16	03/13/85-12:00
MAC/C/INCLUDE/WIN...TEXT	6144	12	05/23/85-10:35	05/23/85-10:35
MAC/C/MAKE.TEXT	7168	14	07/17/85-10:28	02/18/85-16:19
MAC/C/SAMPLE/QDSA...TEXT	12288	24	02/27/85-18:30	09/01/84-10:34
MAC/C/SAMPLE/QDSA...TEXT	2048	4	03/01/85-14:12	07/19/84-17:15

284 total blocks for files listed

- MAC/C/INCLUDE/CONTROLS.H.TEXT
- MAC/C/INCLUDE/CTYPE.H.TEXT
- MAC/C/INCLUDE/DESK.H.TEXT
- MAC/C/INCLUDE/DEVICES.H.TEXT
- MAC/C/INCLUDE/DIALOGS.H.TEXT
- MAC/C/INCLUDE/DISKS.H.TEXT
- MAC/C/INCLUDE/ERRNO.H.TEXT
- MAC/C/INCLUDE/ERROR.H.TEXT
- MAC/C/INCLUDE/EVENTS.H.TEXT
- MAC/C/INCLUDE/FCNTL.H.TEXT
- MAC/C/INCLUDE/FILES.H.TEXT
- MAC/C/INCLUDE/FONTS.H.TEXT
- MAC/C/INCLUDE/IOCTL.H.TEXT
- MAC/C/INCLUDE/MATH.H.TEXT
- MAC/C/INCLUDE/MEMORY.H.TEXT
- MAC/C/INCLUDE/MENUS.H.TEXT
- MAC/C/INCLUDE/OSEVENTS.H.TEXT
- MAC/C/INCLUDE/OSUTILS.H.TEXT
- MAC/C/INCLUDE/PACKAGES.H.TEXT
- MAC/C/INCLUDE/PRINTING.H.TEXT
- MAC/C/INCLUDE/QUICKDRAW.H.TEXT
- MAC/C/INCLUDE/RESOURCES.H.TEXT
- MAC/C/INCLUDE/RETRACE.H.TEXT
- MAC/C/INCLUDE/SANE.H.TEXT
- MAC/C/INCLUDE/SCRAP.H.TEXT
- MAC/C/INCLUDE/SEGLoad.H.TEXT
- MAC/C/INCLUDE/SERIAL.H.TEXT
- MAC/C/INCLUDE/SOUND.H.TEXT
- MAC/C/INCLUDE/STDIO.H.TEXT
- MAC/C/INCLUDE/STRINGS.H.TEXT
- MAC/C/INCLUDE/TEXTEDIT.H.TEXT
- MAC/C/INCLUDE/TOOLUTILS.H.TEXT
- MAC/C/INCLUDE/TYPES.H.TEXT
- MAC/C/INCLUDE/VALUES.H.TEXT
- MAC/C/INCLUDE/WINDOWS.H.TEXT
- MAC/C/MAKE.TEXT
- MAC/C/SAMPLE/QDSAMPLE.C.TEXT

MAC/C/SAMPLE/QDSAMPLE.R.TEXT

*B-3*

The End.

C-φ

 Apple Lisa Computer Information 

# Lisa Workshop C System

## Manual Extra

C-Specific  
Headers

C-1

File: -LOWER-MAC/C/INCLUDE/STDIO.H

[11-Jun-1986] Page - 1

```

< 1) /*
< 2)  stdio.h -- Standard C I/O Package
< 3)
< 4)  Copyright American Telephone & Telegraph
< 5)  Used with permission, Apple Computer Inc. (1985)
< 6)  All rights reserved.
< 7) */
< 8)
< 9) #ifndef __STDIO__
< 10) #define __STDIO__
< 11)
< 12) /*      @(#)stdio.h      2.1      */
< 13)
< 14) #define _NFILE 20
< 15) #define BUFSIZ 1024
< 16)
< 17) /* buffer size for multi-character output to unbuffered files */
< 18) #define _SBFSIZ 8
< 19)
< 20) typedef struct (
< 21)     int      _cnt;
< 22)     unsigned char  *_ptr;
< 23)     unsigned char  *_base;
< 24)     char      _flag;
< 25)     char      _file;
< 26) ) FILE;
< 27)
< 28) /*
< 29) * _IOLBF means a file is a terminal; this means, in particular,
< 30) * that output will be buffered line by line
< 31) */
< 32) #define _IOREAD      0001
< 33) #define _IOMRT      0002
< 34) #define _IONBF      0004
< 35) #define _IOMYBUF    0010
< 36) #define _IOEOF      0020
< 37) #define _IOERR      0040
< 38) #define _IOLBF      0100
< 39) #define _IORW       0200
< 40)
< 41) #ifndef NULL
< 42) #define NULL          0
< 43) #endif
< 44) #ifndef EOF
< 45) #define EOF          (-1)
< 46) #endif
< 47)
< 48) #define stdin        (&_job[0])
< 49) #define stdout       (&_job[1])
< 50) #define stderr       (&_job[2])
< 51)
< 52) #define _bufend(p)  _bufendtab[(p)->_file]

```

Lisa Workshop C StdIO Interface

C-2

File: -LOWER-MAC/C/INCLUDE/STDIO.H

[11-Jun-1986] Page - 2

```

< 53> #define _bufsiz(p)      (_bufend(p) - (p)->_base)
< 54>
< 55> #ifndef lint
< 56> #define getc(p)          (--(p)->_cnt >= 0 ? (int) *(p)->_ptr++ : _filbuf(p))
< 57> #define putc(x, p)      (--(p)->_cnt >= 0 ? \
< 58> ((int) (*(p)->_ptr++ = (unsigned char) (x))) : \
< 59> _flsbuf((unsigned char) (x), (p)))
< 60> #define getchar()      getc(stdin)
< 61> #define putchar(x)     putc((x), stdout)
< 62> #define clearerr(p)    ((void) ((p)->_flag &= ~(_IOERR | _IOEOF)))
< 63> #define feof(p)        ((p)->_flag & _IOEOF)
< 64> #define ferror(p)      ((p)->_flag & _IOERR)
< 65> #define fileno(p)      (p)->_file
< 66> #endif lint
< 67>
< 68> extern FILE      _io[ _NFILE ];
< 69> extern FILE      *fopen(), *fdopen(), *freopen();
< 70> extern long      ftell();
< 71> extern void      rewind(), setbuf();
< 72> extern char      *fgets(), *gets();
< 73> extern unsigned char *_bufendtab[];
< 74>
< 75> #endif __STDIO__
< 76>

```

---



---

 Lisa Workshop C StdIO Interface
 

---



---

C-3

File: -LOWER-MAC/C/INCLUDE/FCNTL.H

[11-Jun-1986] Page - 1

```

< 1> /*
< 2>  fcntl.h -- open mode flags
< 3>
< 4>  Copyright American Telephone & Telegraph
< 5>  Used with permission, Apple Computer Inc. (1985)
< 6>  All rights reserved.
< 7> */
< 8>
< 9> #ifndef __FCNTL__
< 10> #define __FCNTL__
< 11>
< 12> /*  @(#)fcntl.h      2.1      */
< 13> /*  3.0 SID #      1.2      */
< 14> /* Flag values accessible to open(2) and fcntl(2) */
< 15> /* (The first three can only be set by open) */
< 16> #define O_RDONLY 0
< 17> #define O_WRONLY 1
< 18> #define O_RDWR 2
< 19> /* #define O_NDELAY 04      /* Non-blocking I/O */
< 20> #define O_APPEND 010      /* append (writes guaranteed at the end) */
< 21>
< 22> /* Flag values accessible only to open(2) */
< 23> #define O_CREAT 00400      /* open with file create (uses third open arg)*/
< 24> #define O_TRUNC 01000      /* open with truncation */
< 25> #define O_EXCL 02000      /* exclusive open */
< 26>
< 27> /* fcntl(2) requests */
< 28> /* #define F_DUPFD 0      /* Duplicate fildes */
< 29> /* #define F_GETFD 1      /* Get fildes flags */
< 30> /* #define F_SETFD 2      /* Set fildes flags */
< 31> /* #define F_GETFL 3      /* Get file flags */
< 32> /* #define F_SETFL 4      /* Set file flags */
< 33>
< 34> #endif __FCNTL__
< 35>

```

---

 Lisa Workshop C Fcntl Interface
 

---

C-4

File: -LOWER-MAC/C/INCLUDE/CTYPE.H

[11-Jun-1986] Page - 1

```

< 1> /*
< 2>  ctype.h -- character types
< 3>
< 4>  Copyright American Telephone & Telegraph
< 5>  Used with permission, Apple Computer Inc. (1985)
< 6>  All rights reserved.
< 7> */
< 8>
< 9> #ifndef __CTYPE__
< 10> #define __CTYPE__
< 11>
< 12> /*      @(#)ctype.h      2.1      */
< 13> /*      3.0 SID #      1.2      */
< 14> #define _U      01
< 15> #define _L      02
< 16> #define _N      04
< 17> #define _S      010
< 18> #define _P      020
< 19> #define _C      040
< 20> #define _B      0100
< 21> #define _X      0200
< 22>
< 23> extern char      _ctype[];
< 24>
< 25> #ifndef lint
< 26> #define isalpha(c)      ((_ctype+1)[c]&(_U|_L))
< 27> #define isupper(c)      ((_ctype+1)[c]&_U)
< 28> #define islower(c)      ((_ctype+1)[c]&_L)
< 29> #define isdigit(c)      ((_ctype+1)[c]&_N)
< 30> #define isxdigit(c)      ((_ctype+1)[c]&_X)
< 31> #define isalnum(c)      ((_ctype+1)[c]&(_U|_L|_N))
< 32> #define isspace(c)      ((_ctype+1)[c]&_S)
< 33> #define ispunct(c)      ((_ctype+1)[c]&_P)
< 34> #define isprint(c)      ((_ctype+1)[c]&(_P|_U|_L|_N|_B))
< 35> #define isgraph(c)      ((_ctype+1)[c]&(_P|_U|_L|_N))
< 36> #define iscntrl(c)      ((_ctype+1)[c]&_C)
< 37> #define isascii(c)      ((unsigned char)(c)<=0177)
< 38> #define _toupper(c)      ((c)-'a'+'A')
< 39> #define _tolower(c)      ((c)-'A'+'a')
< 40> #define toascii(c)      ((c)&0177)
< 41> #endif
< 42>
< 43> #endif __CTYPE__
< 44>

```

Lisa Workshop C CType Interface

C-5

File: -LOWER-MAC/C/INCLUDE/ERRNO.H

[11-Jun-1986] Page - 1

```

< 1) /*
< 2)   errno.h -- error return codes
< 3)
< 4)   Copyright American Telephone & Telegraph
< 5)   Used with permission, Apple Computer Inc. (1985)
< 6)   All rights reserved.
< 7) */
< 8)
< 9) #ifndef  _ERRNO_
< 10) #define  _ERRNO_
< 11)
< 12) /*   @(#)errno.h   2.1   */
< 13) /*   3.0 SID #   1.3   */
< 14) /*
< 15) * Error codes
< 16) */
< 17)
< 18) extern int errno;
< 19)
< 20) #define EPERM 1 /* Not super-user */
< 21) #define ENOENT 2 /* No such file or directory */
< 22) /* #define ESRCH 3 /* No such process */
< 23) #define EINTR 4 /* interrupted system call */
< 24) #define EIO 5 /* I/O error */
< 25) #define ENXIO 6 /* No such device or address */
< 26) /* #define E2BIG 7 /* Arg list too long */
< 27) /* #define ENOEXEC 8 /* Exec format error */
< 28) #define EBADF 9 /* Bad file number */
< 29) /* #define ECHILD 10 /* No children */
< 30) /* #define EAGAIN 11 /* No more processes */
< 31) #define ENOMEM 12 /* Not enough core */
< 32) #define EACCES 13 /* Permission denied */
< 33) #define EFAULT 14 /* Bad address */
< 34) #define ENOTBLK 15 /* Block device required */
< 35) #define EBUSY 16 /* Mount device busy */
< 36) #define EEXIST 17 /* File exists */
< 37) #define EXDEV 18 /* Cross-device link */
< 38) #define ENODEV 19 /* No such device */
< 39) #define ENOTDIR 20 /* Not a directory */
< 40) #define EISDIR 21 /* Is a directory */
< 41) #define EINVAL 22 /* Invalid argument */
< 42) #define ENFILE 23 /* File table overflow */
< 43) #define EMFILE 24 /* Too many open files */
< 44) #define ENOTTY 25 /* Not a typewriter */
< 45) #define ETXTBSY 26 /* Text file busy */
< 46) #define EFBIG 27 /* File too large */
< 47) #define ENOSPC 28 /* No space left on device */
< 48) #define EPIPE 29 /* Illegal seek */
< 49) #define EROFS 30 /* Read-only file system */
< 50) #define EMLINK 31 /* Too many links */
< 51) /* #define EPIPE 32 /* Broken pipe */
< 52) #define EDOM 33 /* Math arg out of domain of fun. */

```

---

 Lisa Workshop C ErrNo Interface
 

---



C-6



File: -LOWER-MAC/C/INCLUDE/ERRNO.H

[11-Jun-1986] Page - 2

```
< 53> #define ERANGE 34 /* Math result not representable */
< 54> /* #define ENMSG 35 /* No message of desired type */
< 55> /* #define EIDRM 36 /* Identifier removed */
< 56> /* #define ECHRNG 37 /* Channel number out of range */
< 57> /* #define EL2NSYNC 38 /* Level 2 not synchronized */
< 58> /* #define EL3HLT 39 /* Level 3 halted */
< 59> /* #define EL3RST 40 /* Level 3 reset */
< 60> /* #define ELNRNG 41 /* Link number out of range */
< 61> /* #define EUNATCH 42 /* Protocol driver not attached */
< 62> /* #define ENOCSI 43 /* No CSI structure available */
< 63> /* #define EL2HLT 44 /* Level 2 halted */
< 64>
< 65> #endif __ERRNO__
< 66>
```

Lisa Workshop C ErrNo Interface

D-0

 Apple Lisa Computer Information 

# Lisa Workshop C System

## Manual Extra

# C Make File

( in the Lisa Workshop EXEC language )

D-1

File: -LOWER-MAC/C/MAKE

[11-Jun-1985] Page - 1

```

< 1> # ( C program Compile, Assemble, Link, RMaker, and MacDom. )
< 2> # ( )
< 3> # ( Usage: <mac/c/make(mac/c/sample/program) )
< 4> # ( )
< 5> # ( Tries to do minimum work necessary. Can force any stage by passing 'T' )
< 6> # ( for the appropriate stage desired. For example to force the program to )
< 7> # ( be recompiled (and thus Link, RMaker and MacDom) types )
< 8> # ( <mac/c/make(mac/c/sample/program,T) )
< 9> # ( )
< 10> # ( File naming conventions: )
< 11> # ( )
< 12> # ( program.c.text -- C source )
< 13> # ( program.asm.text -- assembly language (optional) )
< 14> # ( program.r.text -- input to resource compiler )
< 15> # ( )
< 16> # ( program.c.obj -- C object )
< 17> # ( program.asm.obj -- assembly language object (optional) )
< 18> # ( program.obj -- linked object )
< 19> # ( program.rsrc -- Mac executable (output of resource compiler) )
< 20> # ( )
< 21> # ( )
< 22> # exec (program, ( program name, (do not include ".c" suffix) )
< 23> needCompile, ( pass T to force compile )
< 24> needAsm, ( pass T to force assemble )
< 25> needLink, ( pass T to force link )
< 26> needRsrc, ( pass T to force Rmaker)
< 27> CText, ( string concatenation temporary )
< 28> CObj, ( string concatenation temporary )
< 29> AsmText, ( string concatenation temporary )
< 30> AsmObj, ( string concatenation temporary )
< 31> Obj, ( string concatenation temporary )
< 32> RText, ( string concatenation temporary )
< 33> Rsrc) ( string concatenation temporary )
< 34> # ( )
< 35> # ( )
< 36> # default needCompile to 'F'
< 37> # default needAsm to 'F'
< 38> # default needLink to 'F'
< 39> # default needRsrc to 'F'
< 40> # ( )
< 41> # set CText to concat(program, '.c.text')
< 42> # set CObj to concat(program, '.c.obj')
< 43> # set AsmText to concat(program, '.asm.text')
< 44> # set AsmObj to concat(program, '.asm.obj')
< 45> # set Obj to concat(program, '.obj')
< 46> # set RText to concat(program, '.r.text')
< 47> # set Rsrc to concat(program, '.rsrc')
< 48> # ( )
< 49> # ( )
< 50> # ( Check if compile is necessary )
< 51> # ( )
< 52> # if not (exists(CObj)) then

```

Lisa Workshop C Macintosh Application Exec Maker

D-2

File: -LOWER-MAC/C/MAKE

[11-Jun-1986] Page - 2

```

< 53> #   set needCompile to 'T'
< 54> # elseif newer(CText, CObj) then
< 55> #   set needCompile to 'T'
< 56> # endif
< 57> #
< 58> # if needCompile = 'T' then
< 59> #   writeln CText, ' needs compiling.'
< 60> #   r(un)c
< 61> #   ?                ( Set options )
< 62> #                   ( No options )
< 63> #   [program].c
< 64> #   (listing file)
< 65> #   (object file)
< 66> # else
< 67> #   writeln CText, ' does not need compiling.'
< 68> # endif
< 69> #
< 70> #
< 71> # ( Check if assemble is necessary )
< 72> #
< 73> # if exists(AsmText) then
< 74> #   if not (exists(AsmObj)) then
< 75> #     set needAsm to 'T'
< 76> #   elseif newer(AsmText, AsmObj) then
< 77> #     set needAsm to 'T'
< 78> #   endif
< 79> # endif
< 80> #
< 81> # if needAsm = 'T' then
< 82> #   writeln AsmText, ' needs to be assembled.'
< 83> #   a(semble)[program].asm
< 84> #   (no list file)
< 85> #   (same output name)
< 86> # elseif exists(AsmText) then
< 87> #   writeln AsmText, ' does not need assembling.'
< 88> # endif
< 89> #
< 90> #
< 91> # ( Check if link is necessary )
< 92> #
< 93> # if needCompile = 'T' then
< 94> #   set needLink to 'T'
< 95> # elseif needAsm = 'T' then
< 96> #   set needLink to 'T'
< 97> # elseif needLink = 'F' then
< 98> #   if not (exists(Obj)) then
< 99> #     set needLink to 'T'
< 100> #   elseif newer(CObj, Obj) then
< 101> #     set needLink to 'T'
< 102> #   elseif exists(AsmObj) then
< 103> #     if newer(AsmObj, Obj) then

```

---

 Lisa Workshop C Macintosh Application Exec Maker
 

---

D-3

Files: -LOWER-MAC/C/MAKE

[11-Jun-1984] Page - 2

```

< 104) $      set needLink to 'T'
< 105) $      endif
< 106) $      endif
< 107) $ endif
< 108) $
< 109) $ if needLink = 'T' then
< 110) $   writeln program, ' needs linking.'
< 111) $   r(un)linker
< 112) $   ?
< 113) $   +X
< 114) $   (no more options)
< 115) $   [program].c           ( C program )
< 116) $ if needAsm = 'T' or exists(AsmObj) then
< 117) $   [program].asm       ( Assembly language (optional) )
< 118) $ endif
< 119) $   mac/c/lib/runtime      ( Initialization )
< 120) $ ( mac/c/lib/cruntime      Standard C Library initialization w/out argv,argc )
< 121) $ ( mac/c/lib/cruntimeargv  Standard C Library initialization w/ argv,argc )
< 122) $ ( mac/c/lib/stdclib       Standard C Library )
< 123) $ ( mac/c/lib/stdcprintf    Standard C Library printf )
< 124) $ ( mac/c/lib/sanelib       SANE Numerics )
< 125) $   mac/c/lib/interface   ( Inside Macintosh Interface )
< 126) $ ( mac/c/lib/prlink        High-Level Printing Interfaces )
< 127) $ ( mac/c/lib/prscreen      Low-Level Printing Interfaces )
< 128) $   ( no more object files )
< 129) $   (no listing file)
< 130) $   [program]
< 131) $ else
< 132) $   writeln program, ' does not need linking.'
< 133) $ endif
< 134) $
< 135) $
< 136) $ ( Check if RMaker is necessary )
< 137) $
< 138) $ if needLink = 'T' then
< 139) $   set needRsrc to 'T'
< 140) $ elseif needRsrc = 'F' then
< 141) $   if not (exists(Rsrc)) then
< 142) $     set needRsrc to 'T'
< 143) $   elseif newer(Obj, Rsrc) then
< 144) $     set needRsrc to 'T'
< 145) $   elseif newer(RText, Rsrc) then
< 146) $     set needRsrc to 'T'
< 147) $   endif
< 148) $ endif
< 149) $
< 150) $ if needRsrc = 'T' then
< 151) $   writeln program, ' needs RMaker.'
< 152) $   r(un)mac/rmaker
< 153) $   [program].r
< 154) $ else

```

---

 Lisa Workshop C Macintosh Application Exec Maker
 

---

D-4


File: -LOWER-MAC/C/MAKE

[11-Jun-1986] Page - 4

```
< 155> $    writeIn program, ' does not need RMaker.'
< 156> $ endif
< 157> $
< 158> $
< 159> $    ( Copy the resource file to a Mac formatted micro-floppy in the lower drive )
< 160> $
< 161>      r(un)mac/macrom
< 162>      F(inderInfo)Y(es)L(isa->Mac)[program].resrc
< 163>      [program]
< 164>      APPL    ( Type )
< 165>      ( Creator [?????] )
< 166>      N(o)    ( Set Bundle Bit )
< 167>      Eject)Q(uit)
< 168> $
< 169> $ endexec
< 170>
```

Lisa Workshop C Macintosh Application Exec Maker

E-φ

 Apple Lisa Computer Information 

# Lisa Workshop C System

## Manual Extra

QDSample  
Program  
Listing







E-3

File: -LOWER-MAC/C/SAMPLE/QDSAMPLE.C

[11-Jun-1986] Page - 3

```

< 104>
< 105> drawIcon(whichIcon,h,v)
< 106>     short whichIcon,h,v;
< 107>
< 108>     (
< 109>     BitMap srcBits;
< 110>     Rect srcRect,dstRect;
< 111>
< 112>
< 113>     srcBits.baseAddr = (Ptr) &icons[whichIcon][0];
< 114>     srcBits.rowBytes = 6;
< 115>     SetRect(&(srcBits.bounds),0,0,48,32);
< 116>     srcRect = srcBits.bounds;
< 117>     dstRect = srcRect;
< 118>     OffsetRect(&dstRect,h,v);
< 119>     CopyBits(&srcBits,&qd.thePort->portBits,&srcRect,&dstRect,srcOr,nil);
< 120>     )
< 121>
< 122>
< 123> drawStuff()
< 124>
< 125>     (
< 126>     short i;
< 127>     Rect tempRect;
< 128>     Polygon **myPoly;
< 129>     Region **myRgn;
< 130>     Pattern myPattern;
< 131>
< 132>     StuffHex(myPattern,"8040200002040800");
< 133>
< 134>     SetRect(&tempRect,0,0,512,342);
< 135>     ClipRect(&tempRect);
< 136>     EraseRoundRect(&tempRect,30,20);
< 137>     FrameRoundRect(&tempRect,30,20);
< 138>
< 139>     /* draw two horizontal lines across the top */
< 140>     MoveTo(0,17);
< 141>     LineTo(511,17);
< 142>     MoveTo(0,19);
< 143>     LineTo(511,19);
< 144>
< 145>     /* draw divider lines */
< 146>     MoveTo(0,126);
< 147>     LineTo(511,126);
< 148>     MoveTo(0,233);
< 149>     LineTo(511,233);
< 150>     MoveTo(170,20);
< 151>     LineTo(170,342);
< 152>     MoveTo(340,20);
< 153>     LineTo(340,341);
< 154>

```

Lisa Workshop C Macintosh Sample Application

E-4

File: -LOWER-MAC/C/SAMPLE/QDSAMPLE.C

[11-Jun-1986] Page - 4

```

< 155>      /* draw title */
< 156>
< 157>      TextFont(0);
< 158>      TextSize(0);
< 159>      TextMode(srcOr);
< 160>      SpaceExtra(6);
< 161>      MoveTo(120,14);
< 162>      DrawString("Look what you can draw with QuickDraw");
< 163>
< 164>
< 165>      /*----- draw text samples ----- */
< 166>
< 167>      MoveTo(68,33); DrawString("Text");
< 168>
< 169>      TextFace(bold);
< 170>      MoveTo(54,53); DrawString("bold");
< 171>
< 172>      TextFace(italic);
< 173>      MoveTo(54,68); DrawString("italic");
< 174>
< 175>      TextFace(underline);
< 176>      MoveTo(54,83); DrawString("underline");
< 177>
< 178>      TextFace(outline);
< 179>      MoveTo(54,98); DrawString("outline");
< 180>
< 181>      TextFace(shadow);
< 182>      MoveTo(54,113); DrawString("shadow");
< 183>
< 184>      TextFace(normal);
< 185>
< 186>
< 187>      /* ----- draw Line samples ----- */
< 188>
< 189>      MoveTo(240,33); DrawString("Lines");
< 190>      MoveTo(200,31); Line(110,30);
< 191>
< 192>      PenSize(3,2);
< 193>      MoveTo(200,40); Line(110,30);
< 194>
< 195>      PenSize(6,4);
< 196>      MoveTo(200,50); Line(110,30);
< 197>
< 198>      PenSize(12,8);
< 199>      PenPat(qd.gray);
< 200>      MoveTo(200,64); Line(110,30);
< 201>
< 202>      PenSize(15,8);
< 203>      PenPat(myPattern);
< 204>      MoveTo(200,80); Line(110,30);
< 205>      PenNormal();

```

---

 Lisa Workshop C Macintosh Sample Application
 

---

E-5

File: -LOWER-MAC/C/SAMPLE/QDSAMPLE.C

[11-Jun-1986] Page - 5

```
< 206>
< 207>
< 208>
< 209> /* ----- draw rectangle samples ----- */
< 210>
< 211> MoveTo(390,33); DrawString("Rectangles");
< 212> SetRect(&tempRect,360,42,415,70);
< 213> FrameRect(&tempRect);
< 214>
< 215> OffsetRect(&tempRect,20,11);
< 216> PenSize(3,2);
< 217> EraseRect(&tempRect);
< 218> FrameRect(&tempRect);
< 219>
< 220> OffsetRect(&tempRect,20,11);
< 221> PaintRect(&tempRect);
< 222>
< 223> OffsetRect(&tempRect,20,11);
< 224> PenNormal();
< 225> FillRect(&tempRect,qd.gray);
< 226> FrameRect(&tempRect);
< 227>
< 228> OffsetRect(&tempRect,20,11);
< 229> FillRect(&tempRect,myPattern);
< 230> FrameRect(&tempRect);
< 231>
< 232>
< 233> /* ----- draw roundRect samples ----- */
< 234>
< 235> MoveTo(45,140); DrawString("RoundRects");
< 236> SetRect(&tempRect,20,149,75,177);
< 237> FrameRoundRect(&tempRect,30,20);
< 238>
< 239> OffsetRect(&tempRect,20,11);
< 240> PenSize(3,2);
< 241> EraseRoundRect(&tempRect,30,20);
< 242> FrameRoundRect(&tempRect,30,20);
< 243>
< 244> OffsetRect(&tempRect,20,11);
< 245> PaintRoundRect(&tempRect,30,20);
< 246>
< 247> OffsetRect(&tempRect,20,11);
< 248> PenNormal();
< 249> FillRoundRect(&tempRect,30,20,qd.gray);
< 250> FrameRoundRect(&tempRect,30,20);
< 251>
< 252> OffsetRect(&tempRect,20,11);
< 253> FillRoundRect(&tempRect,30,20,myPattern);
< 254> FrameRoundRect(&tempRect,30,20);
< 255>
< 256> /* ----- draw BitMap samples ----- */
```

Lisa Workshop C Macintosh Sample Application

E-6

File: -LOWER-MAC/C/SAMPLE/QDSAMPLE.C

[11-Jun-1986] Page - 6

```

< 257>
< 258>     MoveTo(232,140); DrawString("BitMaps");
< 259>     drawIcon(0,180,148);
< 260>     drawIcon(1,232,148);
< 261>     drawIcon(2,284,148);
< 262>     drawIcon(3,180,192);
< 263>     drawIcon(4,232,192);
< 264>     drawIcon(5,284,192);
< 265>
< 266>
< 267>     /* ----- draw ARC samples ----- */
< 268>
< 269>     MoveTo(410,140); DrawString("Arcs");
< 270>     SetRect(&tempRect,360,149,476,220);
< 271>     FillArc(&tempRect,135,65,qd.dkGray);
< 272>     FillArc(&tempRect,280,130,myPattern);
< 273>     FillArc(&tempRect,330,75,qd.gray);
< 274>     FrameArc(&tempRect,135,270);
< 275>     OffsetRect(&tempRect,20,0);
< 276>     PaintArc(&tempRect,45,90);
< 277>
< 278>
< 279>     /* ----- draw Polygon samples ----- */
< 280>
< 281>     MoveTo(52,247); DrawString("Polygons");
< 282>     myPoly = OpenPoly();
< 283>     MoveTo(20,284);
< 284>     LineTo(20,268);
< 285>     LineTo(32,256);
< 286>     LineTo(75,256);
< 287>     LineTo(62,270);
< 288>     LineTo(75,284);
< 289>     LineTo(20,284);
< 290>     ClosePoly();      /* end of definition */
< 291>
< 292>     FramePoly(myPoly);
< 293>     OffsetPoly(myPoly,20,11);
< 294>     PenSize(3,2);
< 295>     ErasePoly(myPoly);
< 296>     FramePoly(myPoly);
< 297>     OffsetPoly(myPoly,20,11);
< 298>     PaintPoly(myPoly);
< 299>     OffsetPoly(myPoly,20,11);
< 300>     PenNormal();
< 301>     FillPoly(myPoly,qd.gray);
< 302>     FramePoly(myPoly);
< 303>     OffsetPoly(myPoly,20,11);
< 304>     FillPoly(myPoly,myPattern);
< 305>     FramePoly(myPoly);
< 306>     KillPoly(myPoly);
< 307>

```

---

 Lisa Workshop C Macintosh Sample Application
 

---

E-7

File: -LOWER-MAC/C/SAMPLE/QDSAMPLE.C

[11-Jun-1986] Page - 7

```

< 308>
< 309> /* ----- demonstrate Region clipping ----- */
< 310>
< 311> MoveTo(232,247); DrawString("Regions");
< 312> myRgn = NewRgn();
< 313> OpenRgn();
< 314> ShowPen();
< 315>
< 316> SetRect(&tempRect,190,255,320,328);
< 317> FrameRoundRect(&tempRect,24,16);
< 318>
< 319> MoveTo(195,312); /* define triangular hole */
< 320> LineTo(230,270);
< 321> LineTo(265,312);
< 322> LineTo(195,312);
< 323>
< 324> SetRect(&tempRect,260,262,310,302); /* oval hole */
< 325> FrameOval(&tempRect);
< 326> HidePen();
< 327> CloseRgn(myRgn); /* end of definition */
< 328>
< 329> SetClip(myRgn);
< 330>
< 331> for (i=0;i<=6;i++) {
< 332>     MoveTo(190,266+12*i);
< 333>     DrawString(" Arbitrary Clipping ");
< 334> }
< 335>
< 336> ClipRect(&gd.thePort->portRect);
< 337> DisposeRgn(myRgn);
< 338>
< 339>
< 340> /* ----- draw oval samples ----- */
< 341>
< 342> MoveTo(406,247); DrawString("Ovals");
< 343> SetRect(&tempRect,360,42,415,70);
< 344> SetRect(&tempRect,360,256,415,284);
< 345> FrameOval(&tempRect);
< 346>
< 347> OffsetRect(&tempRect,20,11);
< 348> PenSize(3,2);
< 349> EraseOval(&tempRect);
< 350> FrameOval(&tempRect);
< 351>
< 352> OffsetRect(&tempRect,20,11);
< 353> PaintOval(&tempRect);
< 354>
< 355> OffsetRect(&tempRect,20,11);
< 356> PenNormal();
< 357> FillOval(&tempRect,gd.gray);
< 358> FrameOval(&tempRect);

```

Lisa Workshop C Macintosh Sample Application

E-8

File: -LOWER-MAC/C/SAMPLE/QDSAMPLE.C

[11-Jun-1986] Page - 8

```
< 359>
< 360>     OffsetRect(&tempRect,20,11);
< 361>     FillOval(&tempRect,myPattern);
< 362>     FrameOval(&tempRect);
< 363>
< 364>     ) /* drawStuff */
< 365>
< 366>
< 367> main() /* main program */
< 368>
< 369>     (
< 370>     InitGraf(&qd.thePort);
< 371>     OpenPort(&myPort);
< 372>     InitCursor();
< 373>     HideCursor();
< 374>     InitFonts();
< 375>     PaintRect(&qd.thePort->portRect);
< 376>     initIcons();
< 377>     drawStuff();
< 378>     while (!Button());
< 379>     )
< 380>
< 381>
< 382>
< 383>
< 384>
< 385>
```

---

---

Lisa Workshop C Macintosh Sample Application

---

---

E-9

---

---

File: -LOWER-MAC/C/SAMPLE/QDSAMPLE.R

---

---

[11-Jun-1986] Page - 1

```
< 1> * Resource File qdsample
< 2>
< 3>
< 4> mac/c/sample/qdsample.rsrc
< 5>
< 6> type CODE
< 7> mac/c/sample/qdsample,0
< 8>
< 9>
```

---

---

Lisa Workshop C Macintosh Sample Resource File

---

---



E-11

Look what you can draw with QuickDraw

<p>Text</p> <p><b>Bold</b></p> <p><i>Italic</i></p> <p><u>Underline</u></p> <p><b>Outline</b></p> <p><b>Shadow</b></p>	<p>Lines</p>	<p>Rectangles</p>
<p>RoundRects</p>	<p>Bit Images</p>	<p>Wedges</p>
<p>Polygons</p>	<p>Regions</p>	<p>Ovals</p>

F-φ

 Apple Lisa Computer Information 

Lisa Workshop C System

Manual Extra

Lisa C  
Packing Slip

F-1

CA. 1986

FROM: APPLE COMPUTER, INC.  
MILESTONE GROUP LTD.  
MAILING FACILITY  
3250 KELLER STREET/SUITE 1  
SANTA CLARA CA 95054

PACKING SLIP

TO: P3, INC  
DAVID CRAIG



1211  
UPS

949 PARKLANE CTR

WICHITA KS 67218

<u>PRODUCT</u>	<u>DESCRIPTION</u>	<u>QTY SHIPPED</u>	<u>QTY BACKORDERED</u>
FG19	APPLETALK		
FG31	C LANGUAGE	1	0
FG33	DEC '85 ADDITION		
FG34	MAY '85 SUPPLEMENT		
FG35	LASERWRITER		
FG36	MARCH '86 ADDITION		
FG40	'85 APPLE TECH NOTES		
FG41	'85 MAC TECH NOTES		
FG42	'86 MAC TECH NOTES		
FG43	'86 APPLE TECH NOTES		
FG44	'86 MAC TECH NOTES/DISK		
FG45	'86 APPLE TECH NOTES/DISK		
FG46	'85 MAC TECH NOTES/DISK		
FG47	'85 APPLE TECH NOTES/DISK		

THIS IS A PACKING SLIP ONLY!!!! NOT AN INVOICE!!!!

 Apple Lisa Computer Information 

Lisa Workshop C System

*The End*