# 15.011 Does anyone have the pin-to-pin mapping that would allow me to construct a suitable internal cable for a IIe numeric keypad?

Description

This article is from the Apple II Csa2 FAQ, by Jeff Hurlburt with numerous contributions by others.

15.011 Does anyone have the pin-to-pin mapping that would allow me to construct a suitable internal cable for a IIe numeric keypad?

```
   You need a female Dsub-15 to 11 pin female header.  If the female Dsub-15 is
numbered like this:


_____\                                /
 \  8    7    6    5    4    3    2    1  /
  \   15   14   13   12   11   10   9   /
   _____/



And the 11 pin header is numbered like this:

_____|                              |
|   11  10  9  8  7  6  5  4  3  2  1  |
|_____|



Then:

DB-15      |     Header
_____|_____

   12            11
   11            10
   10             9
    9             8
   NC             7
    7             6
    6             5
    5             4
    3             3
    2             2
    1             1


The header is as viewed on the motherboard.  The DB-15 is the female connector
that you would plug the keypad into.
```

Continue to:

Share and Enjoy

Bookmark this story so others can enjoy it:

Tags

[pc](#), [hardware](#), [Apple II](#), [Apple][or Apple //](#), [apple](#), [programming](#)

Last modified Fri Feb 20 19:19:33 2009