

### 2.17.3 Jitter

Jitter of the disk motor speed shall be less than 1.8% peak - peak when measured at a motor speed of between 390 and 605 RPM. Jitter is defined as:

$$\text{Jitter} = \frac{4 S_x}{S_m} \times 100\%$$

where :  $S_x$  is the standard deviation of the TACH pulse period sampled randomly 100 points and  $S_m$  is the mean of Tach pulse period.

### 2.17.4 Thermal drift

Thermal drift of disk motor speed for any speed between 390 and 605 rpm shall be less than 3%. The definition of the thermal drift:

$$\text{Thermal drift} = \left| \frac{V_x - V_r}{V_r} \right| \times 100\%$$

where :  $V_r$  : Disk motor speed at 25 C ambient temperature.

$V_x$  : Disk motor speed between 5 C to 50 C ambient temperature.

### 2.17.5 Initial drift

Initial drift of disk motor speed shall be less than 1.0%. Initial drift is defined as:

$$\text{Initial drift} = \left| \frac{V_x - V_r}{V_r} \right| \times 100\%$$

where :  $V_r$  : Disk motor speed at 1 sec after disk motor is turned on.

$V_x$  : Disk motor speed at 120 sec after disk motor is turned on.

### 2.17.6 Speed - Torque characteristics

The change of speed with torque is:

Ratio of speed/torque : -0.25% /gram cm

 apple computer inc.

SIZE  
A

DRAWING NUMBER  
699-0285-A

SCALE:

SHEET 16 OF 39