



# Tech Info Library

## AppleWorks: Using it with the IIe and the Epson DX-20 printer

Revised: 4/24/86  
Security: Everyone

AppleWorks: Using it with the IIe and the Epson DX-20 printer

=====

This article describes how to run AppleWorks on a IIe with an Epson DX-20 printer.

### Configuration:

- Apple IIe
- Super Serial Card
- CompuCable, P/N MTB0201
- Epson DX-20 Letter Quality Printer
- AppleWorks, version 1.3

### Super Serial Card switch settings:

SW 1-1: OFF	SW 2-1: ON
SW 1-2: ON	SW 2-2: OFF
SW 1-3: ON	SW 2-3: OFF
SW 1-4: ON	SW 2-4: OFF
SW 1-5: ON	SW 2-5: ON
SW 1-6: ON	SW 2-6: OFF
SW 1-7: ON	SW 2-7: OFF

### DX-20 switch settings:

SW 1-1: OFF	SW 2: all OFF
SW 1-2: OFF	
SW 1-3: ON	
SW 1-4: OFF	
SW 1-5: OFF	
SW 1-6: ON	
SW 1-7: OFF	
SW 1-8: OFF	

### AppleWorks configuration:

Needs line feed after each return:	NO
Accepts top-of-page commands:	NO

Stop at end of each page: YES or NO (NO is preferable)  
Platen width: 13.0  
Printer codes:  
    Characters per inch: no codes  
    Lines per inch: no codes  
Boldface, subscript and superscript:  
    Boldface begin: ESC-W  
    Boldface end: ESC-&  
    Subscript begin: ESC-U  
    Subscript end: ESC-D  
    Superscript begin: ESC-D  
    Superscript end: ESC-U  
Underlining (printer has start/stop underlining commands):  
    Underlining begin: ESC-E  
    Underlining end: ESC-R

Apple Technical Communications

Tech Info Library Article Number:1914